










## CORNERED AUDIO

Preisliste gültig ab 26. Januar 2021

ARTIKEL	BEZEICHNUNG	UVP (CHF)	Info
<b>PRO Series Professional Install Line • IP65 &amp; EN54 Rating</b>			
<b>Ci2</b>	 Install Loudspeaker • 2½" Woofer & ¾" Tweeter • 30 Wrms / 120 Wpeak • 8 Ω • 90° Housing • IP65 • New Slider System for install • 100° x 100° Dispersion • 140-20'000 Hz • 105 dB Peak Ci2-BK • black Ci2-WH • white	<b>110.00</b>	
<b>Ci4</b>	 Install Loudspeaker • 2 x 4" Woofer & 1" Tweeter • 60 Wrms / 240 Wpeak • 8 Ω • 90° Housing • IP65 • New Slider System for install • 100° x 100° Dispersion • 60-20'000 Hz • 110 dB Peak Ci4-BL • black Ci4-WH • white	<b>220.00</b>	
<b>Ci4-V</b>	 Install Loudspeaker • 2 x 4" Woofer & 1" Tweeter • 60 W @ 8 Ω / 30 W @ 100V • 90° Housing • IP65 • New Slider System for install • 100° x 100° • 60-20'000 Hz • 110 dB Peak Ci4V-BL • black Ci4V-WH • white	<b>270.00</b>	
<b>Ci5</b>	 Install Loudspeaker • 2 x 5¼" Woofer & 1" Tweeter • 80 Wrms / 320 Wpeak • 8 Ω • 90° Housing • IP65 • New Slider System • 100° x 100° Dispersion • 55-20'000 Hz • 113 dB Peak Ci5-BK • black Ci5WH • white	<b>290.00</b>	
<b>Ci5-V</b>	 Install Loudspeaker • 2 x 5¼" Woofer & 1" Tweeter • 80 W @ 8 Ω / 30 W @ 100V • 90° Housing • IP65 • New Slider System for install • 100° x 100° • 55-20'000 Hz • 110 dB Peak Ci5V-BK • black Ci5V-WH • white	<b>330.00</b>	







PRO Series	DSP Amplifier		
<b>CA280DSP</b>	 2 x 140W @ 8 Ohm or 4 ohm / 1 x 280 W bridged / 100V • 2 x 2 Matrix DSP with top grade 48 kHz/24bit • RMS-Compressor • Limiter • dynamic Loudness • Automated room Equalizer • Delay in time and distance • Sound masking • Auto Power on/of • noiseless without fan • USB, RJ45 or Wi-Fi connection for system setup, monitoring and control via remote PC software (included) • Simultaneous control up to 32 units via PC software • Presets for Cornered loudspeakers • GPIO connection for remote volume control...	<b>1'340.00</b>	

Accessories	Installation Cable		
<b>CSP2</b>	 Special Install Loudspeker Cable • cornered shape for invisible installation in corners • 100 m roll • price / m	<b>5.30</b>	




## CORNERED AUDIO

Preisliste gültig ab 26. Januar 2021

ARTIKEL	BEZEICHNUNG	UVP (CHF)	Info
<b>ALU Series Aluminium Install Line</b>			
<b>C3</b>	 Install Loudspeaker • 4" woofer & 1" silk dome tweeter • 80 Wrms / 320 Wpeak • 111 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape <b>ABS</b> housing • 100° x 100° dispersion • 371 x 174 x 121 mm • 2.7 kg C3-BK • black C3-WH • white	<b>300.00</b>	
<b>C5</b>	 Install Loudspeaker • 5¼" woofer + 5¼" slave woofer & 1" silk dome tweeter • 100 Wrms / 400 Wpeak • 114 dB max. SPL peak • 59-25'000 Hz • 8 Ω • cornered shape <b>alu</b> housing • 100° x 100° dispersion • 434 x 213 x 154 mm • 4.1 kg C5-BK • black C5-WH • white C5-ALU • aluminium	<b>550.00</b>	
<b>C5TRM</b>	 Install Loudspeaker • 5¼" woofer + 5¼" slave woofer & 1" horn loaded tweeter • 150 Wrms / 600 Wpeak • 118 dB max. SPL peak • 55-25'000 Hz • 8 Ω • cornered shape <b>alu</b> housing • 90° x 90° dispersion • 439 x 213 x 154 mm • 4.8 kg C5TRM-BK • black C5TRM-WH • white C5TRM-ALU • aluminium	<b>680.00</b>	
<b>C6</b>	 Install Loudspeaker • 6½" woofer + 6½" slave woofer & 1" silk dome tweeter • 125 Wrms / 500 Wpeak • 117 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape <b>alu</b> housing • 100° x 100° dispersion • 502 x 232 x 167 mm • 5.2 kg C6-BK • black C6-WH • white C6-ALU • aluminium	<b>690.00</b>	
<b>C6TRM</b>	 Install Loudspeaker • 6½" neodyn. Woofer & 2 x 1" horn loaded tweeter • 250 Wrms / 1'000 Wpeak • 122 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape <b>alu</b> housing • 90° x 90° dispersion • 502 x 232 x 167 mm • 5.9 kg C6TRM-BK • black C6TRM-WH • white C6TRM-ALU • aluminium	<b>1'050.00</b>	
<b>LS1</b>	 Install Loudspeaker / Line Source • 6½" woofer & 1" horn loaded tweeter • 250 Wrms / 1'000 Wpeak • 122 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape <b>alu</b> housing • 90° x 60° dispersion • 502 x 232 x 167 mm • 6.4 kg LS1-BK • black LS1-WH • white LS1-ALU • aluminium	<b>1'250.00</b>	

**SUB Series High Grade Subwoofer**

<b>C15NC</b>	 Passive Subwoofer • 15" woofer • 1'000 Wrms / 4'000 Wpeak • black or white <b>18mm Plywood</b> Cabinet, 2mm Steel Grille • 133 dB • 32-940 Hz • 8 Ohm • 28 kg	<b>2'590.00</b> <i>new</i>	
--------------	---	----------------------------	--

Important: Price per piece / can only be ordered in pairs! (Exeptional Subwoofers)