











CORNERED AUDIO

Preisliste gültig ab 5. Januar 2023

Preise pro Stück / Ci-Serie kann nur paarweise bestellt werden (Ausser Subwoofer & Aktiv-Set)







ARTIKEL	BEZEICHNUNG	UVP (CHF)	Info
Ci Series Professional Install Line • IP65 & EN54 Rating			
Ci2	 Install Loudspeaker • 2½" Woofer & ¾" Tweeter • 30 Wrms / 120 Wpeak • 8 Ω • 90° Housing • IP65 • New Slider System for install • 100° x 100° Dispersion • 140-20'000 Hz • 105 dB Peak Ci2-BK • black Ci2-WH • white	130.00	
Ci4	 Install Loudspeaker • 2 x 4" Woofer & 1" Tweeter • 60 Wrms / 240 Wpeak • 8 Ω • 90° Housing • IP65 • New Slider System for install • 100° x 100° Dispersion • 60-20'000 Hz • 110 dB Peak Ci4-BL • black Ci4-WH • white	260.00	
Ci4-V	 Install Loudspeaker • 2 x 4" Woofer & 1" Tweeter • 60 W @ 8 Ω / 30 W @ 100V • 90° Housing • IP65 • New Slider System for install • 100° x 100° • 60-20'000 Hz • 110 dB Peak Ci4V-BL • black Ci4V-WH • white	300.00	
Ci5	 Install Loudspeaker • 2 x 5¼" Woofer & 1" Tweeter • 80 Wrms / 320 Wpeak • 8 Ω • 90° Housing • IP65 • New Slider System • 100° x 100° Dispersion • 55-20'000 Hz • 113 dB Peak Ci5-BK • black Ci5WH • white	340.00	
Ci5-V	 Install Loudspeaker • 2 x 5¼" Woofer & 1" Tweeter • 80 W @ 8 Ω / 30 W @ 100V • 90° Housing • IP65 • New Slider System for install • 100° x 100° • 55-20'000 Hz • 110 dB Peak Ci5V-BK • black Ci5V-WH • white	415.00	
A Series Professional Install Line • Aktiv-Set (Aktiver LS + passiver Slave)			
A3-WH	 Aktiv-Set mit 2 x 60W Verstärker und DSP • Bluetooth 5.0 mit erweiterter BT-Reichweite (bis zu 30 m) • Frequenzgang: 55-25'000 Hz • max. SPL: 111 dB • THD: < 0.03% A3-WH • weiss (SET-Preis)	740.00	neu!
PRO Series DSP Amplifier			
CA280DSP	 2 x 140W @ 8 Ohm or 4 ohm / 1 x 280 W bridged / 100V • 2 x 2 Matrix DSP with top grade 48 kHz/24bit • RMS-Compressor • Limiter • dynamic Loudness • Automated room Equalizer • Delay in time and distance • Sound masking • Auto Power on/of • noiseless without fan • USB, RJ45 or Wi-Fi connection for system setup, monitoring and control via remote PC software (included) • Simultaneous control up to 32 units via PC software • Presets for Cornered loudspeakers • GPIO connection for remote volume control...	1'445.00	
Accessories Installation Cable			
CSP2	 Special Install Loudspeaker Cable • cornered shape for invisible installation in corners • 100 m roll • price / m	5.70	





CORNERED AUDIO

Preisliste gültig ab 5. Januar 2023

Preise pro Stück / Ci-Serie kann nur paarweise bestellt werden (Ausser Subwoofer & Aktiv-Set)

ARTIKEL	BEZEICHNUNG	UVP (CHF)	Info
ALU Series Aluminium Install Line			
C3	 Install Loudspeaker • 4" woofer & 1" silk dome tweeter • 80 Wrms / 320 Wpeak • 111 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape ABS housing • 100° x 100° dispersion • 371 x 174 x 121 mm • 2.7 kg C3-BK • black C3-WH • white	340.00	
C5	 Install Loudspeaker • 5¼" woofer + 5¼" slave woofer & 1" silk dome tweeter • 100 Wrms / 400 Wpeak • 114 dB max. SPL peak • 59-25'000 Hz • 8 Ω • cornered shape alu housing • 100° x 100° dispersion • 434 x 213 x 154 mm • 4.1 kg C5-BK • black C5-WH • white C5-ALU • aluminium	620.00	
C5TRM	 Install Loudspeaker • 5¼" woofer + 5¼" slave woofer & 1" horn loaded tweeter • 150 Wrms / 600 Wpeak • 118 dB max. SPL peak • 55-25'000 Hz • 8 Ω • cornered shape alu housing • 90° x 90° dispersion • 439 x 213 x 154 mm • 4.8 kg C5TRM-BK • black C5TRM-WH • white C5TRM-ALU • aluminium	820.00	
C6	 Install Loudspeaker • 6½" woofer + 6½" slave woofer & 1" silk dome tweeter • 125 Wrms / 500 Wpeak • 117 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape alu housing • 100° x 100° dispersion • 502 x 232 x 167 mm • 5.2 kg C6-BK • black C6-WH • white C6-ALU • aluminium	775.00	
C6TRM	 Install Loudspeaker • 6½" neodyn. Woofer & 2 x 1" horn loaded tweeter • 250 Wrms / 1'000 Wpeak • 122 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape alu housing • 90° x 90° dispersion • 502 x 232 x 167 mm • 5.9 kg C6TRM-BK • black C6TRM-WH • white C6TRM-ALU • aluminium	1'170.00	
LS1	 Install Loudspeaker / Line Source • 6½" woofer & 1" horn loaded tweeter • 250 Wrms / 1'000 Wpeak • 122 dB max. SPL peak • 70-25'000 Hz • 8 Ω • cornered shape alu housing • 90° x 60° dispersion • 502 x 232 x 167 mm • 6.4 kg LS1-BK • black LS1-WH • white LS1-ALU • aluminium	1'325.00	

SUB Series High Grade Subwoofer

C15NC	 Passive Subwoofer • 15" woofer • 1'000 Wrms / 4'000 Wpeak • black or white 18mm Plywood Cabinet, 2mm Steel Grille • 133 dB • 32-940 Hz • 8 Ohm • 28 kg	2'690.00	
C8S	 Passive Subwoofer • 8" woofer + 8" Slave • 100 Wrms / 400 Wpeak • white • 114 dB • 34-240 Hz • 8 Ohm • 10.6 kg	920.00	