



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|
|---------|-------------|----------|-------|

COMET LED • Track-Adaptor included

Comet LED, a combination of technology and design, linear and slim, integrates perfectly with the electrified track, almost disappearing. Comet LED is the perfect combination of light efficiency, visual comfort and thanks to its geometry it is easy to use even in not too high environments. Comet LED offers a wide choice of options to create the desired lighting effect without compromising lighting performance, such as color rendering (CRI > 90) and beam uniformity.

One-sided asymmetrical optics, ideal for lighting applications in retail environments where uniform distribution of light in shelves is required even at a certain height. Comet LED uses Samsung LED light source excellent in the quality of light output and also in light quality.

Single Side (25° x 90°)

| | | | |
|--------------|---|--------|----|
| TCK5551B-RWW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 2700K, on/off | 380.00 | 12 |
| TCK5551B-WW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 3000K, on/off | 380.00 | 12 |
| TCK5551B-NW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 4000K, on/off | 380.00 | 12 |

Double Side (2 x 25° x 90°)

| | | | |
|--------------|---|--------|----|
| TCK5552B-RWW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 2700K, on/off | 380.00 | 12 |
| TCK5552B-WW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 3000K, on/off | 380.00 | 12 |
| TCK5552B-NW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 4000K, on/off | 380.00 | 12 |

Wide (down, 85°)

| | | | |
|--------------|---|--------|----|
| TCK5553B-RWW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 2700K, on/off | 380.00 | 12 |
| TCK5553B-WW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 3000K, on/off | 380.00 | 12 |
| TCK5553B-NW | COMET LED, 55W, 230Vac, CRI≥90, Aluminium Body, 928 mm, 4000K, on/off | 380.00 | 12 |

BOUTIQUE ELITE Series • Track-Adaptor included, white body – optional grey & black

| | | | |
|---------------|---|--------|----|
| TCK2335B-GNW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 18°, 4200K, on/off | 590.00 | 13 |
| TCK2335B-GWW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 18°, 3200K, on/off | 610.00 | 13 |
| TCK2335B-P | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 18°, natural pink, on/off | 610.00 | 13 |
| TCK2336B-GNW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 30°, 4200K, on/off | 590.00 | 13 |
| TCK2336B-GWW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 30°, 3200K, on/off | 610.00 | 13 |
| TCK2336B-P | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 30°, natural pink, on/off | 610.00 | 13 |
| TCK2337B-GNW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97 51°, 4200K, on/off | 590.00 | 13 |
| TCK2337B-GWW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 51°, 3200K, on/off | 610.00 | 13 |
| TCK2337B-P | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 51°, natural pink, on/off | 610.00 | 13 |
| TCKD2335B-GNW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 18°, 4200K, DALI | 680.00 | 13 |
| TCKD2335B-GWW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 18°, 3200K, DALI | 695.00 | 13 |
| TCKD2335B-P | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 18°, natural pink, DALI | 690.00 | 13 |
| TCKD2336B-GNW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 30°, 4200K, DALI | 680.00 | 13 |
| TCKD2336B-GWW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 30°, 3200K, DALI | 695.00 | 13 |
| TCKD2336B-P | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97, 30°, natural pink, DALI | 690.00 | 13 |
| TCKD2337B-GNW | BOUTIQUE LED Elite 45W, 230Vac, CRI≥97 51°, 4200K, DALI | 680.00 | 13 |


**ARCHITECTURAL LIGHTING
CATALOGUE**
Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------------|--|----------|-------|
| TCKD2337B-GWW | BOUTIQUE LED Elite 45W,230Vac, CRI≥97, 51°, 3200K, DALI | 695.00 | 13 |
| TCKD2337B-P | BOUTIQUE LED Elite 45W,230Vac, CRI≥97, 51°, natural pink, DALI | 690.00 | 13 |

ETHOS ELITE Series • Track-Adaptor included, white body – optional grey & black

| | | | |
|--------------|--|--------|----|
| TCK2335B-WW | ETHOS LED Elite 35W,230Vac, CRI≥90, 18°, 3000K, dimmable with phase cut dimmer | 530.00 | 14 |
| TCK2335B-NW | ETHOS LED Elite 35W,230Vac, CRI≥90, 18°, 4000K, dimmable with phase cut dimmer | 530.00 | 14 |
| TCK2336B-WW | ETHOS LED Elite 35W,230Vac, CRI≥90, 30°, 3000K, dimmable with phase cut dimmer | 530.00 | 14 |
| TCK2336B-NW | ETHOS LED Elite 35W,230Vac, CRI≥90, 30°, 4000K, dimmable with phase cut dimmer | 530.00 | 14 |
| TCK2337B-WW | ETHOS LED Elite 35W,230Vac, CRI≥90, 51°, 3000K, dimmable with phase cut dimmer | 530.00 | 14 |
| TCK2337B-NW | ETHOS LED Elite 35W,230Vac, CRI≥90, 51°, 4000K, dimmable with phase cut dimmer | 530.00 | 14 |
| TCKD2335B-WW | ETHOS LED Elite 35W,230Vac, CRI≥90, 18°, 3000K, DALI | 730.00 | 14 |
| TCKD2335B-NW | ETHOS LED Elite 35W,230Vac, CRI≥90, 18°, 4000K, DALI | 730.00 | 14 |
| TCKD2336B-WW | ETHOS LED Elite 35W,230Vac, CRI≥90, 30°, 3000K, DALI | 730.00 | 14 |
| TCKD2336B-NW | ETHOS LED Elite 35W,230Vac, CRI≥90, 30°, 4000K, DALI | 730.00 | 14 |
| TCKD2337B-WW | ETHOS LED Elite 35W,230Vac, CRI≥90, 51°, 3000K, DALI | 730.00 | 14 |
| TCKD2337B-NW | ETHOS LED Elite 35W,230Vac, CRI≥90, 51°, 4000K, DALI | 730.00 | 14 |

NEBULA ELITE Series • Track-Adaptor included, white body – optional grey & black

| | | | |
|--------------|---|--------|----|
| TCK2135B-WW | NEBULA LED Elite 35W,230Vac, CRI≥90, 18°, 3000K, dimmable with phase cut dimmer | 470.00 | 14 |
| TCK2135B-NW | NEBULA LED Elite 35W,230Vac, CRI≥90, 18°, 4000K, dimmable with phase cut dimmer | 470.00 | 14 |
| TCK2136B-WW | NEBULA LED Elite 35W,230Vac, CRI≥90, 30°, 3000K, dimmable with phase cut dimmer | 470.00 | 14 |
| TCK2136B-NW | NEBULA LED Elite 35W,230Vac, CRI≥90, 30°, 4000K, dimmable with phase cut dimmer | 470.00 | 14 |
| TCK2137B-WW | NEBULA LED Elite 35W,230Vac, CRI≥90, 51°, 3000K, dimmable with phase cut dimmer | 470.00 | 14 |
| TCK2137B-NW | NEBULA LED Elite 35W,230Vac, CRI≥90, 51°, 4000K, dimmable with phase cut dimmer | 470.00 | 14 |
| TCKD2135B-WW | NEBULA LED Elite 35W,230Vac, CRI≥90, 18°, 3000K, DALI | 690.00 | 14 |
| TCKD2135B-NW | NEBULA LED Elite 35W,230Vac, CRI≥90, 18°, 4000K, DALI | 690.00 | 14 |
| TCKD2136B-WW | NEBULA LED Elite 35W,230Vac, CRI≥90, 30°, 3000K, DALI | 690.00 | 14 |
| TCKD2136B-NW | NEBULA LED Elite 35W,230Vac, CRI≥90, 30°, 4000K, DALI | 690.00 | 14 |
| TCKD2137B-WW | NEBULA LED Elite 35W,230Vac, CRI≥90, 51°, 3000K, DALI | 690.00 | 14 |
| TCKD2137B-NW | NEBULA LED Elite 35W,230Vac, CRI≥90, 51°, 4000K, DALI | 690.00 | 14 |

ARDENA ELITE Series • Track-Adaptor included, white body – optional grey & black

| | | | |
|-------------|---|--------|----|
| TCK2125B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 18°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2125B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 18°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |


ARCHITECTURAL LIGHTING
CATALOGUE
Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--------------|---|----------|-------|
| TCK2126B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 30°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2126B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 30°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2127B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 51°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2127B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 51°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2128B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 72°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2128B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 72°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCKD2125B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 18°, 3000K, DALI | 590.00 | 15 |
| TCKD2125B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 18°, 4000K, DALI | 590.00 | 15 |
| TCKD2126B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 30°, 3000K, DALI | 590.00 | 15 |
| TCKD2126B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 30°, 4000K, DALI | 590.00 | 15 |
| TCKD2127B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 51°, 3000K, DALI | 590.00 | 15 |
| TCKD2127B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 51°, 4000K, DALI | 590.00 | 15 |
| TCKD2128B-NW | ARDENA LED Elite 25W,230Vac, CRI≥90, 72°, 3000K, DALI | 590.00 | 15 |
| TCKD2128B-WW | ARDENA LED Elite 25W,230Vac, CRI≥90, 72°, 4000K, DALI | 590.00 | 15 |

ALTAIR ELITE Series • Track-Adaptor included, white body – optional grey & black

| | | | |
|--------------|---|--------|----|
| TCK2311B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 18°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2311B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 18°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2312B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 30°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2312B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 30°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2313B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 51°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2313B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 51°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2314B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 72°, 3000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCK2314B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 72°, 4000K, dimmable with phase cut dimmer | 390.00 | 15 |
| TCKD2311B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 18°, 3000K, DALI | 590.00 | 15 |
| TCKD2311B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 18°, 4000K, DALI | 590.00 | 15 |
| TCKD2312B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 30°, 3000K, DALI | 590.00 | 15 |
| TCKD2312B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 30°, 4000K, DALI | 590.00 | 15 |
| TCKD2313B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 51°, 3000K, DALI | 590.00 | 15 |
| TCKD2313B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 51°, 4000K, DALI | 590.00 | 15 |
| TCKD2314B-NW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 72°, 3000K, DALI | 590.00 | 15 |
| TCKD2314B-WW | ALTAIR LED Elite 11W,230Vac, CRI≥90, 72°, 4000K, DALI | 590.00 | 15 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---|---|----------|-------|
| STAR Series • Track-Adaptor included, white body | | | |
| TCK52515B-RWW | STAR LED 25W,230Vac, CRI≥90, 18°, 2700K, on/off | 220.00 | 16 |
| TCK52515B-WW | STAR LED 25W,230Vac, CRI≥90, 18°, 3000K, on/off | 220.00 | 16 |
| TCK52515B-NW | STAR LED 25W,230Vac, CRI≥90, 18°, 4000K, on/off | 220.00 | 16 |
| TCK52538B-RWW | STAR LED 25W,230Vac, CRI≥90, 38°, 2700K, on/off | 220.00 | 16 |
| TCK52538B-WW | STAR LED 25W,230Vac, CRI≥90, 38°, 3000K, on/off | 220.00 | 16 |
| TCK52538B-NW | STAR LED 25W,230Vac, CRI≥90, 38°, 4000K, on/off | 220.00 | 16 |
| TCK52560B-RWW | STAR LED 25W,230Vac, CRI≥90, 60°, 2700K, on/off | 220.00 | 16 |
| TCK52560B-WW | STAR LED 25W,230Vac, CRI≥90, 60°, 3000K, on/off | 220.00 | 16 |
| TCK52560B-NW | STAR LED 25W,230Vac, CRI≥90, 60°, 4000K, on/off | 220.00 | 16 |

HYDRA ZOOM ELITE Series • Track-Adaptor included, white body – optional grey & black

| | | | |
|-------------|---|--------|----|
| TCK2088B-WW | HYDRA LED ZOOM 29°-41° Elite 35W,230Vac, CRI≥90, 3000K, dimmable with phase c. d. | 750.00 | 16 |
| TCK2088B-NW | HYDRA LED ZOOM 29°-41° Elite 35W,230Vac, CRI≥90, 4000K, dimmable with phase c. d. | 750.00 | 16 |

ATI ZOOM ELITE Series • Track-Adaptor included, white body – optional grey & black

| | | | |
|-------------|---|--------|----|
| TCK3088B-WW | ATI LED ZOOM 20°-45° Elite 65W,230Vac, CRI≥90, 3000K, integrated dimmer potentiometer | 750.00 | 17 |
| TCK3088B-NW | ATI LED ZOOM 20°-45° Elite 65W,230Vac, CRI≥90, 4000K, integrated dimmer potentiometer | 750.00 | 17 |

BARIO ZOOM ELITE Series • Track-Adaptor included, black body – optional grey & white

| | | | |
|----------------|--|--------|----|
| PRF-0351935-WW | BARIO Profile LED SPOT, 19°-35°, 35W CRI≥90, 3000K, dimmable with phase cut dimmer | 990.00 | 17 |
| PRF-0351935-NW | BARIO Profile LED SPOT, 19°-35°, 35W CRI≥90, 4000K, dimmable with phase cut dimmer | 990.00 | 17 |

TRACK SYSTEM with 3 separate Electric Lines

Three-phase track for 3 separate electrical circuits. Rectangular section made of extruded aluminium, contains a PVC profile insulator with 4 copper conductors, while the profile is itself the grounding of the system. Maximum load: 16 A for the whole system. At the top of the track are slots for fixing of accessories. Most of the adapters to 3-lines system in commerce can be mounted on the track (ERCO, EUTRACK etc.). The system can be suspended or fixed directly to the ceiling. PL1424-PL1425 is for recessed montage.

Technical Informations: 230Vac / 50/60 Hz, 3P+N • 16 A max. on neutral wire • 0.9 kg/m

surface or suspended montage:

| | | | |
|---------|--|--------|----|
| PL1422 | 3-line Track System, 1 m, white | 59.00 | 18 |
| PL1422N | 3-line Track System, 1 m, black (nero) | 59.00 | 18 |
| PL1422S | 3-line Track System, 1 m, silver | 59.00 | 18 |
| PL1423 | 3-line Track System, 2 m, white | 115.00 | 18 |
| PL1423N | 3-line Track System, 2 m, black (nero) | 115.00 | 18 |


**ARCHITECTURAL LIGHTING
CATALOGUE**
Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|----------|--|----------|-------|
| PL1423S | 3-line Track System, 2 m, silver | 115.00 | 18 |
| | recessed montage: | | |
| PL1424 | 3-line Track System, 1 m, white | 68.00 | 18 |
| PL1425 | 3-line Track System, 2 m, white | 130.00 | 18 |
| APL1422 | Suspension Kit, 2 m of steel cable, plate & cover | 17.00 | 18 |
| APL1423 | Power Feeder, left, white | 22.00 | 18 |
| APL1423N | Power Feeder, left, black (nero) | 22.00 | 18 |
| APL1423S | Power Feeder, left, silver | 22.00 | 18 |
| APL1424 | Power Feeder, right, white | 22.00 | 18 |
| APL1424N | Power Feeder, right, black (nero) | 22.00 | 18 |
| APL1424S | Power Feeder, right, silver | 22.00 | 18 |
| APL1427 | Double (both sides) Power Feeder, right | 43.00 | 18 |
| APL1427N | Double (both sides) Power Feeder, right, black (nero) | 43.00 | 18 |
| APL1427S | Double (both sides) Power Feeder, right, silver | 43.00 | 18 |
| APL1431 | "L" Connector 90°, left, white | 47.00 | 18 |
| APL1431N | "L" Connector 90°, left, black (nero) | 47.00 | 18 |
| APL1431S | "L" Connector 90°, left, silver | 47.00 | 18 |
| APL1432 | "L" Connector 90°, right, white | 47.00 | 18 |
| APL1432N | "L" Connector 90°, right, black (nero) | 47.00 | 18 |
| APL1432S | "L" Connector 90°, right, silver | 47.00 | 18 |
| APL1425 | End cup, white | 2.50 | 18 |
| APL1425N | End cup, black (nero) | 2.50 | 18 |
| APL1425S | End cup, silver | 2.50 | 18 |
| APL1428 | Flexibel Connector, white | 59.00 | 18 |
| APL1428N | Flexibel Connector, black (nero) | 59.00 | 18 |
| APL1428S | Flexibel Connector, silver | 59.00 | 18 |
| APL1433 | "T" Reverse Connector, left, white | 72.00 | 18 |
| APL1433N | "T" Reverse Connecto, left, black (nero) | 72.00 | 18 |
| APL1433S | "T" Reverse Connector, left, silver | 72.00 | 18 |
| APL1434 | "T" Reverse Connector, right, white | 72.00 | 18 |
| APL1434N | "T" Reverse Connecto, right, black (nero) | 72.00 | 18 |
| APL1434S | "T" Reverse Connector, right, silver | 72.00 | 18 |
| APL1426 | Junction Connector (connecting piece between two rails), white | 13.90 | 18 |
| APL1426N | Junction Connector (connecting piece between two rails), black (nero) | 13.90 | 18 |
| APL1426S | Junction Connector (connecting piece between two rails), silver | 13.90 | 18 |
| APL1443 | Track Power Adaptor (to mount directly a lamp of max. 5 kg load), white | 26.00 | 18 |
| APL1443N | Track Power Adaptor (to mount directly a lamp of max. 5 kg load), black (nero) | 26.00 | 18 |
| APL1443S | Track Power Adaptor (to mount directly a lamp of max. 5 kg load), silver | 26.00 | 18 |
| APL1440 | "X" Connector, white | 95.00 | 18 |
| APL1440N | "X" Connector, black (nero) | 95.00 | 18 |
| APL1440S | "X" Connector, silver | 95.00 | 18 |



| | | | |
|---------|-------------|----------|-------|
| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|

TRACK SYSTEM special for dimmable systems with DALI/0-10V

Technical Informations: 230Vac / 50/60 Hz, 1 power line (L1 + N) & control lines (+/-) • 16 A max. on neutral wire • 0.9 kg/m

surface or suspended montage:

| | | | |
|----------|---|--------|----|
| PL2422 | DALI Track System, 1 m, white | 66.00 | 19 |
| PL2422N | DALI Track System, 1 m, black (nero) | 66.00 | 19 |
| PL2422S | DALI Track System, 1 m, silver | 66.00 | 19 |
| PL2423 | DALI Track System, 2 m, white | 126.00 | 19 |
| PL2423N | DALI Track System, 2 m, black (nero) | 126.00 | 19 |
| PL2423S | DALI Track System, 2 m, silver | 126.00 | 19 |
| | | | |
| APL1422 | Suspension Kit, 2 m of steel cable, plate & cover | 17.00 | 19 |
| APL2423 | Power Feeder, left, white | 23.00 | 19 |
| APL2423N | Power Feeder, left, black (nero) | 23.00 | 19 |
| APL2423S | Power Feeder, left, silver | 23.00 | 19 |
| APL2424 | Power Feeder, right, white | 23.00 | 19 |
| APL2424N | Power Feeder, right, black (nero) | 23.00 | 19 |
| APL2424S | Power Feeder, right, silver | 23.00 | 19 |
| APL2427 | Double (both sides) Power Feeder, right | 49.00 | 19 |
| APL2427N | Double (both sides) Power Feeder, right, black (nero) | 49.00 | 19 |
| APL2427S | Double (both sides) Power Feeder, right, silver | 49.00 | 19 |
| APL2431 | "L" Connector 90°, left, white | 47.00 | 19 |
| APL2431N | "L" Connector 90°, left, black (nero) | 47.00 | 19 |
| APL2431S | "L" Connector 90°, left, silver | 47.00 | 19 |
| APL2432 | "L" Connector 90°, right, white | 47.00 | 19 |
| APL2432N | "L" Connector 90°, right, black (nero) | 47.00 | 19 |
| APL2432S | "L" Connector 90°, right, silver | 47.00 | 19 |
| APL2425 | End cup, white | 2.50 | 19 |
| APL2425N | End cup, black (nero) | 2.50 | 19 |
| APL2425S | End cup, silver | 2.50 | 19 |
| APL2428 | Flexibel Connector, white | 59.00 | 19 |
| APL2428N | Flexibel Connector, black (nero) | 59.00 | 19 |
| APL2428S | Flexibel Connector, silver | 59.00 | 19 |
| APL2433 | "T" Reverse Connector, left, white | 72.00 | 19 |
| APL2433N | "T" Reverse Connecto, left, black (nero) | 72.00 | 19 |
| APL2433S | "T" Reverse Connector, left, silver | 72.00 | 19 |
| APL2434 | "T" Reverse Connector, right, white | 72.00 | 19 |
| APL2434N | "T" Reverse Connecto, right, black (nero) | 72.00 | 19 |
| APL2434S | "T" Reverse Connector, right, silver | 72.00 | 19 |
| APL2426 | Junction Connector (connecting piece between two rails), white | 13.90 | 19 |
| APL2426N | Junction Connector (connecting piece between two rails), black (nero) | 13.90 | 19 |
| APL2426S | Junction Connector (connecting piece between two rails), silver | 13.90 | 19 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|----------|--|----------|-------|
| APL2443 | Track Power Adaptor (to mount directly a lamp of max. 5 kg load), white | 37.00 | 19 |
| APL2443N | Track Power Adaptor (to mount directly a lamp of max. 5 kg load), black (nero) | 37.00 | 19 |
| APL2443S | Track Power Adaptor (to mount directly a lamp of max. 5 kg load), silver | 37.00 | 19 |
| APL2440 | "X" Connector, white | 95.00 | 19 |
| APL2440N | "X" Connector, black (nero) | 95.00 | 19 |
| APL2440S | "X" Connector, silver | 95.00 | 19 |

DK LED 60x60 · Light Panels for recessed or suspended installation

LED panel equipped with modular DARK optics. Glare limitation as EN 12464:2011, $L65 < 1000 \text{ cd} / \text{m}^2$ at 65° in each direction and $UGR \leq 16$ for video terminal jobs. Light direction control with linear DARK reflector optics for maximum efficiency, perfect shielding and light distribution. High brightness LED, 140 lm/W , $\text{CRI} \geq 80$, available with color temperatures 3000K and 4000K. On-Off versions as well as dimmable via DALI BUS or in push-button mode (N.O.). Features: Aluminium body, ELITE versions comes with electronics made in Italy.

ELITE Versions

| | | | |
|--------------|--|--------|----|
| PNL6060i-WW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 3000K, on/off | 350.00 | 20 |
| PNL6060i-NW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 4000K, on/off | 350.00 | 20 |
| PNLD6060i-WW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 3000K, DALI | 440.00 | 20 |
| PNLD6060i-NW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 4000K, DALI | 440.00 | 20 |

STANDARD Versions

| | | | |
|------------|--|--------|----|
| PNL6060-WW | DK LED, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 3000K, on/off | 240.00 | 20 |
| PNL6060-NW | DK LED, 30W, 230Va, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 4000K, on/off | 240.00 | 20 |

Accessories

| | | | |
|-----------|--|-------|----|
| APNL6060 | Hanging Kit for suspended installation, steel cables, 2 m | 45.00 | 20 |
| APL6060-P | Sleeve for ceiling installation, 603 x 603 x 55 mm (APL1100) | 39.00 | 20 |
| APL1200 | Sleeve for recessed installation, 600 x 600 | 85.00 | 20 |

DK LED 30x120 · Light Panels for recessed or suspended installation

ELITE Versions

| | | | |
|---------------|---|--------|----|
| PNL30120i-WW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 3000K, on/off | 370.00 | 21 |
| PNL30120i-NW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 4000K, on/off | 370.00 | 21 |
| PNLD30120i-WW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 3000K, DALI | 450.00 | 21 |
| PNLD30120i-NW | DK LED Elite, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 4000K, DALI | 450.00 | 21 |

STANDARD Versions

| | | | |
|-------------|---|--------|----|
| PNL30120-WW | DK LED, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 3000K, on/off | 250.00 | 21 |
| PNL30120-NW | DK LED, 30W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 4000K, on/off | 250.00 | 21 |

Accessories

| | | | |
|----------|---|-------|----|
| APNL6060 | Hanging Kit for suspended installation, steel cables, 2 m | 45.00 | 21 |
|----------|---|-------|----|



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|-----------|---|----------|-------|
| APL3012-P | Sleeve for ceiling installation, 303 x 1203 x 55 mm | 140.00 | 21 |
| APL3012-I | Sleeve for recessed installation, 310 x 1210 | 115.00 | 21 |

HIVE LED 60x60 • Light Panels for recessed or suspended installation

Hive LED is an innovative panel equipped with DARK optics. Glare limitation as EN 12464-2011, $L65 < 1000 \text{ cd/m}^2$ at 65° in each direction and $UG < 16$ for terminal video jobs. Light direction control with square lenticular optics for maximum efficiency, perfect shielding and light distribution. High brightness LED, 140 lm/W , $\text{CRI} \geq 80$, available with color temperatures 3000K and 4000. On/Off versions as well as dimmable via DALI-Bus or in push-button mode (N.O.).

ELITE Versions

| | | | |
|--------------|--|--------|----|
| PNL5040i-WW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 3000K, on/off | 290.00 | 22 |
| PNL5040i-NW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 4000K, on/off | 290.00 | 22 |
| PNLD5040i-WW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 3000K, DALI | 440.00 | 22 |
| PNLD5040i-NW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 4000K, DALI | 440.00 | 22 |

STANDARD Versions

| | | | |
|------------|--|--------|----|
| PNL5040-WW | HIVE LED, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 3000K, on/off | 240.00 | 22 |
| PNL5040-NW | HIVE LED, 40W, 230Va, 65° , $\text{CRI} \geq 80$, 595 x 595 mm, 4000K, on/off | 250.00 | 22 |

Accessories

| | | | |
|-----------|--|-------|----|
| APNL6060 | Hanging Kit for suspended installation, steel cables, 2 m | 45.00 | 22 |
| APL6060-P | Sleeve for ceiling installation, 603 x 603 x 55 mm (APL1100) | 39.00 | 20 |
| APL1200 | Sleeve for recessed installation, 600 x 600 | 85.00 | 20 |

HIVE LED 30x120 • Light Panels for recessed or suspended installation

ELITE Versions

| | | | |
|--------------|---|--------|----|
| PNL5060i-WW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 3000K, on/off | 350.00 | 23 |
| PNL5060i-NW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 4000K, on/off | 350.00 | 23 |
| PNLD5060i-WW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 3000K, DALI | 395.00 | 23 |
| PNLD5060i-NW | HIVE LED Elite, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 4000K, DALI | 395.00 | 23 |

STANDARD Versions

| | | | |
|------------|---|--------|----|
| PNL5060-WW | HIVE LED, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 3000K, on/off | 250.00 | 23 |
| PNL5060-NW | HIVE LED, 40W, 230Vac, 65° , $\text{CRI} \geq 80$, 295 x 1195 mm, 4000K, on/off | 250.00 | 23 |

Accessories

| | | | |
|-----------|---|--------|----|
| APNL1236S | Hanging Kit for suspended installation, steel cables, 2 m | 45.00 | 23 |
| APL3012-P | Sleeve for ceiling installation, 303 x 1203 x 55 mm | 140.00 | 23 |
| APL3012-I | Sleeve for recessed installation, 310 x 1210 | 115.00 | 23 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---|---|----------|-------|
| HIVE LED 30x60 • Light Panels for recessed or suspended installation | | | |
| ELITE Versions | | | |
| PNL5020i-WW | HIVE LED Elite, 20W, 230Vac, 65°, CRI≥80, 295 x 595 mm, 3000K, on/off | 270.00 | 24 |
| PNL5020i-NW | HIVE LED Elite, 20W, 230Vac, 65°, CRI≥80, 295 x 595 mm, 4000K, on/off | 270.00 | 24 |
| PNLD5020i-WW | HIVE LED Elite, 20W, 230Vac, 65°, CRI≥80, 295 x 595 mm, 3000K, DALI | 355.00 | 24 |
| PNLD5020i-NW | HIVE LED Elite, 20W, 230Vac, 65°, CRI≥80, 295 x 595 mm, 4000K, DALI | 355.00 | 24 |
| STANDARD Versions | | | |
| PNL5020-WW | HIVE LED, 20W, 230Vac, 65°, CRI≥80, 295 x 595 mm, 3000K, on/off | 170.00 | 24 |
| PNL5020-NW | HIVE LED, 20W, 230Va, 65°, CRI≥80, 295 x 595 mm, 4000K, on/off | 170.00 | 24 |
| Accessories | | | |
| APNL1236S | Hanging Kit for suspended installation, steel cables, 2 m | 45.00 | 24 |
| APL3060-P | Sleeve for ceiling installation, 303 x 603 x 55 mm | 100.00 | 24 |
| APL3060-I | Sleeve for recessed installation, 310 x 610 | 78.00 | 24 |

ICE LED PANEL UP & DOWN • Light Panels for suspended installation

ICE LED Up & Down is a new dual-emission panel, 55% of the light projected downwards and 45% upwards, this allows good spread throughout the room, creating a comfortable and relaxing atmosphere. Built-in driver, UGR ≤ 19, CRI ≥ 80. Ideal to light up exhibition halls, offices, as well as waiting and meeting rooms. Dimmable version with 0-10V control.

| | | | |
|-----------------|---|--------|----|
| 120 x 30 | | | |
| IC3012-WW | ICE LED Panel, 40W, 230Vac, 110° x 80°, CRI≥80, 1195 x 295 mm, 3000K, on/off | 370.00 | 25 |
| IC3012-NW | ICE LED Panel, 40W, 230Vac, 110° x 80°, CRI≥80, 1195 x 295 mm, 4000K, on/off | 370.00 | 25 |
| IC3012V-WW | ICE LED Panel, 40W, 230Vac, 110° x 80°, CRI≥80, 1195 x 295 mm, 3000K, control 0-10V | 390.00 | 25 |
| IC3012V-NW | ICE LED Panel, 40W, 230Vac, 110° x 80°, CRI≥80, 1195 x 295 mm, 4000K, control 0-10V | 390.00 | 25 |
| 60 x 30 | | | |
| IC3060-WW | ICE LED Panel, 36W, 230Vac, 110° x 80°, CRI≥80, 595 x 295 mm, 3000K, on/off | 315.00 | 25 |
| IC3060-NW | ICE LED Panel, 36W, 230Vac, 110° x 80°, CRI≥80, 595 x 295 mm, 4000K, on/off | 315.00 | 25 |
| IC3060V-WW | ICE LED Panel, 36W, 230Vac, 110° x 80°, CRI≥80, 595 x 295 mm, 3000K, control 0-10V | 340.00 | 25 |
| IC3060V-NW | ICE LED Panel, 36W, 230Vac, 110° x 80°, CRI≥80, 595 x 295 mm, 4000K, control 0-10V | 340.00 | 25 |
| 30 x 30 | | | |
| IC3030-WW | ICE LED Panel, 15W, 230Vac, 110° x 80°, CRI≥80, 295 x 295 mm, 3000K, on/off | 150.00 | 25 |
| IC3030-NW | ICE LED Panel, 15W, 230Vac, 110° x 80°, CRI≥80, 295 x 295 mm, 4000K, on/off | 150.00 | 25 |

THOR LED PANEL • Light Panels for ceiling installation

Thor LED is a LED panel fitted with internal power supply. It can be easily mounted into ceilings and it is equipped with quick connection without the need to open the device. Cutting edge LEDs provide the unit with maximum luminous efficiency and excellent quality of light in few millimeters of thickness. Its LED light source ensures a comfortable visual effect, which is available with a color temperature of 3000 K, 4000 K and 6000 K, providing a CRI>80. Thor LED is ideal for offices, shops, malls, hotels, health care facilities and for all environments that require anti-glare illumination that is both uniform and constant in time.



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--------------------------|---|----------|-------|
| THOR LED 60 x 60 | | | |
| PNL2140-WW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, on/off | 130.00 | 26 |
| PNL2140-NW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, on/off | 130.00 | 26 |
| PNL2140-90-NW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥90 , 595 x 595 mm, 4000K, on/off | 140.00 | 26 |
| PNLD2140-WW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, control 0-10V | 185.00 | 26 |
| PNLD2140-NW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, control 0-10V | 185.00 | 26 |
| PNLD2140-90-NW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥90 , 595 x 595 mm, 4000K, control 0-10V | TBA | 26 |
| PNL2140i-WW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, on/off | 190.00 | 26 |
| PNL2140i-NW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, on/off | 190.00 | 26 |
| PNL2140i-90-NW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥90 , 595 x 595 mm, 4000K, on/off | 190.00 | 26 |
| PNLD2140i-WW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, DALI | 250.00 | 26 |
| PNLD2140i-NW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, DALI | 250.00 | 26 |
| PNLD2140i-90-NW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥90 , 595 x 595 mm, 4000K, DALI | 270.00 | 26 |
| THOR LED 30 x 30 | | | |
| PNL2120-WW | THOR LED Panel, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 3000K, on/off | 115.00 | 26 |
| PNL2120-NW | THOR LED Panel, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 4000K, on/off | 115.00 | 26 |
| PNLD2120-WW | THOR LED Panel, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 3000K, control 0-10V | 165.00 | 26 |
| PNLD2120-NW | THOR LED Panel, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 4000K, control 0-10V | 165.00 | 26 |
| PNL2120i-WW | THOR LED Panel Elite, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 3000K, on/off | 160.00 | 26 |
| PNL2120i-NW | THOR LED Panel Elite, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 4000K, on/off | 160.00 | 26 |
| PNLD2120i-WW | THOR LED Panel Elite, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 3000K, DALI | 210.00 | 26 |
| PNLD2120i-NW | THOR LED Panel Elite, 20W, 230Vac, 120°, CRI≥80, 295 x 295 mm, 4000K, DALI | 210.00 | 26 |
| THOR LED 30 x 120 | | | |
| PNL2145-WW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 3000K, on/off | 180.00 | 27 |
| PNL2145-NW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 4000K, on/off | 180.00 | 27 |
| PNLD2145-WW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 3000K, control 0-10V | 245.00 | 27 |
| PNLD2145-NW | THOR LED Panel, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 4000K, control 0-10V | 245.00 | 27 |
| PNL2145i-WW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 3000K, on/off | 235.00 | 27 |
| PNL2145i-NW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 4000K, on/off | 235.00 | 27 |
| PNLD2145i-WW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 3000K, DALI | 300.00 | 27 |
| PNLD2145i-NW | THOR LED Panel Elite, 40W, 230Vac, 120°, CRI≥80, 295 x 1195 mm, 4000K, DALI | 300.00 | 27 |
| THOR LED 30 x 60 | | | |
| PNL2125-WW | THOR LED Panel, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 3000K, on/off | 120.00 | 27 |
| PNL2125-NW | THOR LED Panel, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 4000K, on/off | 120.00 | 27 |
| PNLD2125-WW | THOR LED Panel, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 3000K, control 0-10V | 170.00 | 27 |
| PNLD2125-NW | THOR LED Panel, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 4000K, control 0-10V | 170.00 | 27 |
| PNL2125i-WW | THOR LED Panel Elite, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 3000K, on/off | 180.00 | 27 |
| PNL2125i-NW | THOR LED Panel Elite, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 4000K, on/off | 180.00 | 27 |
| PNLD2125i-WW | THOR LED Panel Elite, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 3000K, DALI | 210.00 | 27 |
| PNLD2125i-NW | THOR LED Panel Elite, 25W, 230Vac, 120°, CRI≥80, 295 x 595 mm, 4000K, DALI | 210.00 | 27 |
| THOR LED 60 x 120 | | | |
| PNL2172-WW | THOR LED Panel, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 3000K, on/off | 370.00 | 28 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--------------|--|----------|-------|
| PNL2172-NW | THOR LED Panel, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 4000K, on/off | 370.00 | 28 |
| PNLD2172-WW | THOR LED Panel, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 3000K, control 0-10V | 465.00 | 28 |
| PNLD2172-NW | THOR LED Panel, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 4000K, control 0-10V | 465.00 | 28 |
| PNL2172i-WW | THOR LED Panel Elite, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 3000K, on/off | 460.00 | 28 |
| PNL2172i-NW | THOR LED Panel Elite, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 4000K, on/off | 460.00 | 28 |
| PNLD2172i-WW | THOR LED Panel Elite, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 3000K, DALI | 540.00 | 28 |
| PNLD2172i-NW | THOR LED Panel Elite, 70W, 230Vac, 120°, CRI≥80, 595 x 1195 mm, 4000K, DALI | 540.00 | 28 |

ONDA LED PANEL • Light Panels for recessed or suspended installation

Onda LED panel with its anti-glare dark light coupled with the positioning of the light source fitted at the sides of the diffusing reflectors provides both a strong light output while maintaining uniformity in environments, with reduced power consumption. The PMMA body makes the unit very light shock-resistant. Onda LED is ideal for any type of applications such as offices, meeting rooms, doctors' offices, hospitals, shops and homes. Furthermore, Arena Luci provides accessories for installations of any type including surface-mounted, suspended and ceiling installations. All the components of the panel are individually replaceable, ensuring reparability.

| | | | |
|--------------|--|--------|----|
| PNL8640/S-WW | ONDA LED Panel, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 3000K, on/off | 340.00 | 28 |
| PNL8640/S-NW | ONDA LED Panel, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 4000K, on/off | 340.00 | 28 |
| PNLD8640-WW | ONDA LED Panel, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 3000K, DALI | 360.00 | 28 |
| PNLD8640-NW | ONDA LED Panel, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 4000K, DALI | 360.00 | 28 |
| PNL8640i-WW | ONDA LED Panel Elite, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 3000K, on/off | 390.00 | 28 |
| PNL8640i-NW | ONDA LED Panel Elite, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 4000K, on/off | 390.00 | 28 |
| PNLD8640i-WW | ONDA LED Panel Elite, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 3000K, DALI | 450.00 | 28 |
| PNLD8640i-NW | ONDA LED Panel Elite, 38W, 230Vac, 120°, CRI ≥ 95, 595 x 595 mm, 4000K, DALI | 450.00 | 28 |

Accessories

| | | | |
|-----------|---|--------|----|
| APL1200 | Sleeve for recessed installation, 600 x 600 | 85.00 | 28 |
| APL8640 | Sleeve for ceiling installation, 603 x 603 x 55 mm | 110.00 | 28 |
| APNL8640S | Hanging Kit for suspended installation, 4 steel cables, 1 m | 45.00 | 28 |

AGENA COMFORT LED PANEL • Light Panels for recessed or suspended installation

Agena Comfort LED is a 60x60 cm LED panel with comfortable light emission and fitted with internal power supply. It can be easily mounted into ceilings and it is equipped with quick connection without the need to open the device. Cutting edge LEDs provide the unit with maximum luminous efficiency and excellent quality of light in few mm thickness. This allows the unit to be employed in place of traditional 4x18W fixtures fitted with fluorescent tubes. Its LED light source ensures a comfortable visual effect, which is available with a color temperature of 3000 K and 4000 K, providing a CRI>80. Agena LED is ideal for offices, shops, malls, hotels, health care facilities and for all environments that require anti-glare illumination that is both uniform and constant in time.

| | | | |
|-------------|---|--------|----|
| PNL0141C-WW | AGENA COMFORT LED Panel, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, on/off | 200.00 | 29 |
| PNL0141C-NW | AGENA COMFORT LED Panel, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, on/off | 200.00 | 29 |

AGENA COMFORT ELITE LED PANEL • Light Panels for recessed or suspended installation

The Elite version of Agena Comfort LED, like all the products of the Elite Series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|---------------|---|--------|----|
| PNL0141Ci-WW | AGENA COMFORT ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, on/off | 260.00 | 29 |
| PNL0141Ci-NW | AGENA COMFORT ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, on/off | 260.00 | 29 |
| PNLD0141Ci-WW | AGENA COMFORT ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, DALI | 320.00 | 29 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------------|---|----------|-------|
| PNLD0141Ci-NW | AGENA COMFORT ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, DALI | 320.00 | 29 |

AGENA IP65 LED PANEL · Light Panels for recessed or suspended installation

Agena LED IP65 is a 60X60 cm LED panel and it comes with IP65 weather protection factor and it is fitted with internal power supply. It can be easily mounted into ceilings and it is equipped with quick connection without the need to open the device.

| | | | |
|------------|--|--------|----|
| PNL0141-WW | AGENA IP65 LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, on/off | 470.00 | 30 |
| PNL0141-NW | AGENA IP65 LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, on/off | 470.00 | 30 |

AGENA IP65 ELITE LED PANEL · Light Panels for recessed or suspended installation

The Elite version of Agena LED IP65 60X60, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|--------------|---|--------|----|
| PNL0141i-WW | AGENA IP65 ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, on/off | 530.00 | 30 |
| PNL0141i-NW | AGENA IP65 ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, on/off | 530.00 | 30 |
| PNLD0141i-WW | AGENA IP65 ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 3000K, DALI/Push | 590.00 | 30 |
| PNLD0141i-NW | AGENA IP65 ELITE LED, 40W, 230Vac, 120°, CRI≥80, 595 x 595 mm, 4000K, DALI/Push | 590.00 | 30 |

WIZARD DOWNLIGHT Series · trimless, for square holes of 120 x 120 mm

Square trimless recessed LED downlight for general and accent lighting. Smooth and white painted reflector finish. Color temperatures: 2700K, 3000K, 4000K. All versions have a high color rendering to ensure a comfortable color perception.

12W / 15°

| | | | |
|--------------|---|--------|----|
| DWL61215-RWW | WIZARD, 12W, 230Vac, CRI≥80, 15°, Aluminium, white, 119x119x160 mm, 2700K, on/off | 150.00 | 32 |
| DWL61215-WW | WIZARD, 12W, 230Vac, CRI≥80, 15°, Aluminium, white, 119x119x160 mm, 3000K, on/off | 150.00 | 32 |
| DWL61215-NW | WIZARD, 12W, 230Vac, CRI≥80, 15°, Aluminium, white, 119x119x160 mm, 4000K, on/off | 150.00 | 32 |

12W / 24°

| | | | |
|--------------|---|--------|----|
| DWL61224-RWW | WIZARD, 12W, 230Vac, CRI≥80, 24°, Aluminium, white, 119x119x160 mm, 2700K, on/off | 150.00 | 32 |
| DWL61224-WW | WIZARD, 12W, 230Vac, CRI≥80, 24°, Aluminium, white, 119x119x160 mm, 3000K, on/off | 150.00 | 32 |
| DWL61224-NW | WIZARD, 12W, 230Vac, CRI≥80, 24°, Aluminium, white, 119x119x160 mm, 4000K, on/off | 150.00 | 32 |

12W / 40°

| | | | |
|--------------|---|--------|----|
| DWL61240-RWW | WIZARD, 12W, 230Vac, CRI≥80, 40°, Aluminium, white, 119x119x160 mm, 2700K, on/off | 150.00 | 32 |
| DWL61240-WW | WIZARD, 12W, 230Vac, CRI≥80, 40°, Aluminium, white, 119x119x160 mm, 3000K, on/off | 150.00 | 32 |
| DWL61240-NW | WIZARD, 12W, 230Vac, CRI≥80, 40°, Aluminium, white, 119x119x160 mm, 4000K, on/off | 150.00 | 32 |

18W / 15°

| | | | |
|--------------|---|--------|----|
| DWL61815-RWW | WIZARD, 18W, 230Vac, CRI≥80, 15°, Aluminium, white, 119x119x160 mm, 2700K, on/off | 185.00 | 32 |
| DWL61815-WW | WIZARD, 18W, 230Vac, CRI≥80, 15°, Aluminium, white, 119x119x160 mm, 3000K, on/off | 185.00 | 32 |
| DWL61815-NW | WIZARD, 18W, 230Vac, CRI≥80, 15°, Aluminium, white, 119x119x160 mm, 4000K, on/off | 185.00 | 32 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--------------|---|----------|-------|
| | 18W / 24° | | |
| DWL61824-RWW | WIZARD, 18W, 230Vac, CRI≥80, 24°, Aluminium, white, 119x119x160 mm, 2700K, on/off | 185.00 | 32 |
| DWL61824-WW | WIZARD, 18W, 230Vac, CRI≥80, 24°, Aluminium, white, 119x119x160 mm, 3000K, on/off | 185.00 | 32 |
| DWL61824-NW | WIZARD, 18W, 230Vac, CRI≥80, 24°, Aluminium, white, 119x119x160 mm, 4000K, on/off | 185.00 | 32 |
| | 18W / 40° | | |
| DWL61840-RWW | WIZARD, 18W, 230Vac, CRI≥80, 40°, Aluminium, white, 119x119x160 mm, 2700K, on/off | 185.00 | 32 |
| DWL61840-WW | WIZARD, 18W, 230Vac, CRI≥80, 40°, Aluminium, white, 119x119x160 mm, 3000K, on/off | 185.00 | 32 |
| DWL61840-NW | WIZARD, 18W, 230Vac, CRI≥80, 40°, Aluminium, white, 119x119x160 mm, 4000K, on/off | 185.00 | 32 |

CORONA 25 DOWNLIGHT Series • for round holes of 200-210 mm Ø

Corona LED 25 is fitted with an anti-glare optics and an intense but comfortable luminous flux. Its high color rendering index (CRI 95) along with its elegant, thin and light and tough structure, makes it suitable for many applications such as shops, malls, offices, clinics and homes. The Elite version of Corona LED 25, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|--------------|--|--------|----|
| | CORONA 25 LED | | |
| DWL7024-WW | CORONA 25, 24W, 230Vac, CRI ≥ 95, 100°, Aluminium, white, Ø 245x49 mm, 3000K, on/off | 160.00 | 33 |
| DWL7024-NW | CORONA 25, 24W, 230Vac, CRI ≥ 95, 100°, Aluminium, white, Ø 245x49 mm, 4000K, on/off | 160.00 | 33 |
| | CORONA 25 LED ELITE | | |
| DWL7024i-WW | CORONA 25, 24W, 230Vac, CRI ≥ 95, 100°, Aluminium, white, Ø 245x49 mm, 3000K, on/off | 215.00 | 33 |
| DWL7024i-NW | CORONA 25, 24W, 230Vac, CRI ≥ 95, 100°, Aluminium, white, Ø 245x49 mm, 4000K, on/off | 215.00 | 33 |
| DWLD7024i-WW | CORONA 25, 24W, 230Vac, CRI ≥ 95, 100°, Aluminium, white, Ø 245x49 mm, 3000K, DALI | 255.00 | 33 |
| DWLD7024i-NW | CORONA 25, 24W, 230Vac, CRI ≥ 95, 100°, Aluminium, white, Ø 245x49 mm, 4000K, DALI | 255.00 | 33 |

CORONA 15 DOWNLIGHT Series • for round holes of 165-170 mm Ø

Corona LED 15 is fitted with an anti-glare optics and an intense but comfortable luminous flux. Its high color rendering index (CRI 95) along with its elegant, thin and light and tough structure, makes it suitable for many applications such as shops, malls, offices, clinics and homes. The Elite version of Corona LED 15, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|--------------|--|--------|----|
| | CORONA 15 LED | | |
| DWL7015-WW | CORONA 15, 15W, 230Vac, CRI ≥ 95, 115°, Aluminium, white, Ø 193x49 mm, 3000K, on/off | 140.00 | 33 |
| DWL7015-NW | CORONA 15, 15W, 230Vac, CRI ≥ 95, 115°, Aluminium, white, Ø 193x49 mm, 4000K, on/off | 140.00 | 33 |
| | CORONA 15 LED ELITE | | |
| DWL7015i-WW | CORONA 15, 15W, 230Vac, CRI ≥ 95, 115°, Aluminium, white, Ø 193x49 mm, 3000K, on/off | 195.00 | 33 |
| DWL7015i-NW | CORONA 15, 15W, 230Vac, CRI ≥ 95, 115°, Aluminium, white, Ø 193x49 mm, 4000K, on/off | 195.00 | 33 |
| DWLD7015i-WW | CORONA 15, 15W, 230Vac, CRI ≥ 95, 115°, Aluminium, white, Ø 193x49 mm, 3000K, DALI | 235.00 | 33 |
| DWLD7015i-NW | CORONA 15, 15W, 230Vac, CRI ≥ 95, 115°, Aluminium, white, Ø 193x49 mm, 4000K, DALI | 235.00 | 33 |


AZHA DOWNLIGHT Series · for round holes of 210-215 mm Ø

Azha LED 45 is an innovative recessed luminaire with a high color rendering index (CRI) and is fitted with a built-in LED with anti-glare optics that is recessed further in from the installation plane. The heat sink placed on the rear produces an optimized light output that is constant over time. It is ideal for any type of lighting: offices, shops, homes and public venues. Azha LED 45 produces a powerful light beam but at the same time offers high efficiency thanks to its reduced 45W consumption. The Elite version of Azha LED 45, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

AZHA 45 LED

| | | | |
|------------|---|--------|----|
| DWL8945-WW | AZHA 45, 45W, 230Vac, CRI≥80, 85°, Aluminium, white/chrome, Ø230x92 mm, 3000K, on/off | 210.00 | 34 |
| DWL8945-NW | AZHA 45, 45W, 230Vac, CRI≥80, 85°, Aluminium, white/chrome, Ø230x92 mm, 4000K, on/off | 210.00 | 34 |

AZHA 45 LED ELITE

| | | | |
|--------------|---|--------|----|
| DWL8945i-WW | AZHA 45, 45W, 230Vac, CRI≥80, 85°, Aluminium, white/chrome, Ø230x92 mm, 3000K, on/off | 260.00 | 34 |
| DWL8945i-NW | AZHA 45, 45W, 230Vac, CRI≥80, 85°, Aluminium, white/chrome, Ø230x92 mm, 4000K, on/off | 260.00 | 34 |
| DWLD8945i-WW | AZHA 45, 45W, 230Vac, CRI≥80, 85°, Aluminium, white/chrome, Ø230x92 mm, 3000K, DALI | 330.00 | 34 |
| DWLD8945i-NW | AZHA 45, 45W, 230Vac, CRI≥80, 85°, Aluminium, white/chrome, Ø230x92 mm, 4000K, DALI | 330.00 | 34 |

ALYA 30 DOWNLIGHT Series · for round holes of 210-215 mm Ø

Alya LED 30 is an innovative recessed luminaire with a high color rendering index (CRI) and is fitted with a built-in LED with anti-glare optics that is recessed further in from the installation plane. The heat sink placed on the rear produces an optimized light output that is constant over time. It is ideal for any type of lighting: offices, shops, homes and public venues. Alya LED 30 produces a powerful light beam but at the same time offers high efficiency thanks to its reduced 30W consumption. The Elite version of Alya LED 30, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

ALYA 30 LED

| | | | |
|------------|--|--------|----|
| DWL8930-WW | ALYA 30, 30W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø238x97 mm, 3000K, on/off | 130.00 | 34 |
| DWL8930-NW | ALYA 30, 30W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø238x97 mm, 4000K, on/off | 130.00 | 34 |

ALYA 30 LED ELITE

| | | | |
|-------------|--|--------|----|
| DWL8931-WW | ALYA 30, 30W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø238x97 mm, 3000K, on/off | 155.00 | 34 |
| DWL8931-NW | ALYA 30, 30W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø238x97 mm, 4000K, on/off | 155.00 | 34 |
| DWL8931D-WW | ALYA 30, 30W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø238x97 mm, 3000K, DALI | 195.00 | 34 |
| DWL8931D-NW | ALYA 30, 30W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø238x97 mm, 4000K, DALI | 195.00 | 34 |

ALYA 20 DOWNLIGHT Series · for round holes of 165-170 mm Ø

Alya LED 20 is an innovative recessed luminaire with a high color rendering index (CRI) and is fitted with a built-in LED with anti-glare optics that is recessed further in from the installation plane. The heat sink placed on the rear produces an optimized light output that is constant over time. It is ideal for any type of lighting: offices, shops, homes and public venues. Alya LED 20 produces a powerful light beam but at the same time offers high efficiency thanks to its reduced 20W consumption. The Elite version of Alya LED 20, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

ALYA 20 LED

| | | | |
|------------|--|-------|----|
| DWL8920-WW | ALYA 20, 20W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø182x75 mm, 3000K, on/off | 89.00 | 35 |
|------------|--|-------|----|



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--------------|--|----------|-------|
| DWL8920-NW | ALYA 20, 20W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø182x75 mm, 4000K, on/off | 89.00 | 35 |
| | ALYA 20 LED ELITE | | |
| DWL8921-WW | ALYA 20, 20W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø182x75 mm, 3000K, on/off | 140.00 | 35 |
| DWL8921-NW | ALYA 20, 20W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø182x75 mm, 4000K, on/off | 140.00 | 35 |
| DWLD8921D-WW | ALYA 20, 20W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø182x75 mm, 3000K, DALI | 180.00 | 35 |
| DWLD8921D-NW | ALYA 20, 20W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø182x75 mm, 4000K, DALI | 180.00 | 35 |

ALYA 15 DOWNLIGHT Series • for round holes of 110-115 mm Ø

Alya LED 15 is an innovative recessed luminaire with a high color rendering index (CRI) and is fitted with a built-in LED with anti-glare optics that is recessed further in from the installation plane. The heat sink placed on the rear produces an optimized light output that is constant over time. It is ideal for any type of lighting: offices, shops, homes and public venues. Alya LED 15 produces a powerful light beam but at the same time offers high efficiency thanks to its reduced 15W consumption. The Elite version of Alya LED 15, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|-------------|--|--------|----|
| | ALYA 15 LED | | |
| DWL8915-WW | ALYA 15, 15W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø132x54 mm, 3000K, on/off | 69.00 | 35 |
| DWL8915-NW | ALYA 15, 15W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø132x54 mm, 4000K, on/off | 69.00 | 35 |
| | ALYA 15 LED ELITE | | |
| DWL8916-WW | ALYA 15, 15W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø132x54 mm, 3000K, on/off | 110.00 | 35 |
| DWL8916-NW | ALYA 15, 15W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø132x54 mm, 4000K, on/off | 110.00 | 35 |
| DWL8916D-WW | ALYA 15, 15W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø132x54 mm, 3000K, DALI | 150.00 | 35 |
| DWL8916D-NW | ALYA 15, 15W, 230Vac, CRI≥80, 90°, Aluminium, white, Ø132x54 mm, 4000K, DALI | 150.00 | 35 |

PAVO DOWNLIGHT Series • for round holes of 145 mm Ø

Pavo LED 30 is a recessed adjustable down-light with COB technology. The product features an adjustable light beam thanks to a moving head with up to 60° tilt turnability from the ceiling plane. This makes the unit the ideal choice for many installations, such as exhibitions, museums, hotels, clinics, corridors and shops. The Elite version of Pavo LED 30, like all the products of the Elite series is made in Italy and contains premium components such as Italian-made power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|--------------|--|--------|----|
| | PAVO LED | | |
| DWL0330-WW | PAVO, 30W, 230Vac, CRI≥80, 30°, Aluminium, white, Ø162x116 mm, 3000K, on/off | 270.00 | 36 |
| DWL0330-NW | PAVO, 30W, 230Vac, CRI≥80, 30°, Aluminium, white, Ø162x116 mm, 4000K, on/off | 270.00 | 36 |
| | PAVO LED ELITE | | |
| DWL0330i-WW | PAVO, 30W, 230Vac, CRI≥80, 30°, Aluminium, white, Ø162x116 mm, 3000K, on/off | 325.00 | 36 |
| DWL0330i-NW | PAVO, 30W, 230Vac, CRI≥80, 30°, Aluminium, white, Ø162x116 mm, 4000K, on/off | 325.00 | 36 |
| DWLD0330i-WW | PAVO, 30W, 230Vac, CRI≥80, 30°, Aluminium, white, Ø162x116 mm, 3000K, DALI | 380.00 | 36 |
| DWLD0330i-NW | PAVO, 30W, 230Vac, CRI≥80, 30°, Aluminium, white, Ø162x116 mm, 4000K, DALI | 380.00 | 36 |



ARTIKEL BEZEICHNUNG VP (CHF) Seite

PEGASO DOWNLIGHT Series • for square holes of 195 x 195 mm

Pegaso LED is a recessed luminaire fitted with optical reflector and anti-glare light source placed at the rear, which is capable of providing an intense luminous flux without compromising comfort. Its high color rendering index (CRI), together with its elegant but sturdy structure make it the ideal product for a multitude of applications such as installations at retail shops, commercial galleries, but also offices, clinics and residential environments. The Elite version of Pegaso LED, like the whole Elite series, is produced in Italy and contains premium components such as Italian power supplies with ripple-free technology and a persistence of color temperature with high MacAdam classification.

PEGASO LED

| | | | |
|---------------|---|--------|----|
| DWL1530-18-WW | PEGASO, 30W, 230Vac, CRI≥80, 100°, Aluminium, white, 220x220x63 mm, 3000K, on/off | 180.00 | 36 |
| DWL1530-18-NW | PEGASO, 30W, 230Vac, CRI≥80, 100°, Aluminium, white, 220x220x63 mm, 4000K, on/off | 180.00 | 36 |

PEGASO LED ELITE

| | | | |
|--------------|---|--------|----|
| DWL1530i-WW | PEGASO, 30W, 230Vac, CRI≥80, 100°, Aluminium, white, 220x220x63 mm, 3000K, on/off | 235.00 | 36 |
| DWL1530i-NW | PEGASO, 30W, 230Vac, CRI≥80, 100°, Aluminium, white, 220x220x63 mm, 4000K, on/off | 235.00 | 36 |
| DWLD1530i-WW | PEGASO, 30W, 230Vac, CRI≥80, 100°, Aluminium, white, 220x220x63 mm, 3000K, DALI | 275.00 | 36 |
| DWLD1530i-NW | PEGASO, 30W, 230Vac, CRI≥80, 100°, Aluminium, white, 220x220x63 mm, 4000K, DALI | 275.00 | 36 |

PAL DOWNLIGHT Series • for round holes of 80 mm Ø

Pal LED is a recessed adjustable luminaire fitted with anti-glare optics that are available with different angles. The body is made of aluminum with IP54 protection and it mounts cutting-edge CREE COB 12W LEDs. Moreover, Pal LED offers an extraordinary flexibility of use since it can easily be installed into holes of a diameter ranging from 70 to 100 mm. This makes it the ideal unit for installations such as in exhibitions, museums, hotels, clinics corridors and retail shops. Moreover, its IP54 weather protection factor makes it more resistant to moisture than regular indoor luminaire that are usually equipped with IP20 protection. The Elite version of Pal LED, like the whole Elite series, is produced in Italy and contains premium components such as Italian power supplies with ripple-free technology and a persistence of color temperature with high MacAdam classification.

PAL 60° LED

| | | | |
|-------------|--|--------|----|
| DWL5063L-WW | PAL 60°, 12W, 230Vac, CRI≥85, 60°, Aluminium, white, Ø110x70 mm, 2700K, on/off | 150.00 | 37 |
| DWL5063L-NW | PAL 60°, 12W, 230Vac, CRI≥85, 60°, Aluminium, white, Ø110x70 mm, 4000K, on/off | 150.00 | 37 |

PAL 60° LED ELITE

| | | | |
|---------------|--|--------|----|
| DWL5063Li-WW | PAL 60°, 12W, 230Vac, CRI≥85, 60°, Aluminium, white, Ø110x70 mm, 2700K, on/off | 160.00 | 37 |
| DWL5063Li-NW | PAL 60°, 12W, 230Vac, CRI≥85, 60°, Aluminium, white, Ø110x70 mm, 4000K, on/off | 160.00 | 37 |
| DWLD5063Li-WW | PAL 60°, 12W, 230Vac, CRI≥85, 60°, Aluminium, white, Ø110x70 mm, 2700K, DALI | 190.00 | 37 |
| DWLD5063Li-NW | PAL 60°, 12W, 230Vac, CRI≥85, 60°, Aluminium, white, Ø110x70 mm, 4000K, DALI | 190.00 | 37 |

PAL 38° LED

| | | | |
|------------|--|-------|----|
| DWL5063-WW | PAL 38°, 12W, 230Vac, CRI≥85, 38°, Aluminium, white, Ø110x70 mm, 2700K, on/off | 95.00 | 37 |
| DWL5063-NW | PAL 38°, 12W, 230Vac, CRI≥85, 38°, Aluminium, white, Ø110x70 mm, 4000K, on/off | 95.00 | 37 |

PAL 38° LED ELITE

| | | | |
|--------------|--|--------|----|
| DWL5063i-WW | PAL 38°, 12W, 230Vac, CRI≥85, 38°, Aluminium, white, Ø110x70 mm, 2700K, on/off | 150.00 | 37 |
| DWL5063i-NW | PAL 38°, 12W, 230Vac, CRI≥85, 38°, Aluminium, white, Ø110x70 mm, 4000K, on/off | 150.00 | 37 |
| DWLD5063i-WW | PAL 38°, 12W, 230Vac, CRI≥85, 38°, Aluminium, white, Ø110x70 mm, 2700K, DALI | 190.00 | 37 |
| DWLD5063i-NW | PAL 38°, 12W, 230Vac, CRI≥85, 38°, Aluminium, white, Ø110x70 mm, 4000K, DALI | 190.00 | 37 |


ALRAI DOWNLIGHT Series • for square holes of 160 x 160 mm

Alrai is an LED recessed ceiling luminaire fitted with COB technology and high color rendering. The fixture is adjustable in all directions and is fitted with one light source. The frame is made of white cast aluminum, and upon request is available in gray or black trims. The fastening system allows installation in ceilings of different thickness ranging from 5 to 25 mm. This unit is ideal for illumination in retail shops, shopping centers, residential environments and offices. The Elite version of Alrai, like the whole Elite series, is produced in Italy and contains premium components such as Italian power supplies with ripple-free technology and a persistence of color temperature with high MacAdam classification.

ALRAI LED

| | | | |
|------------|--|--------|----|
| DWL9235-WW | ALRAI, 35W, 230Vac, CRI≥90, 30°, Aluminium, white/black, 171x171x114 mm, 3000K, on/off | 190.00 | 38 |
| DWL9235-NW | ALRAI, 35W, 230Vac, CRI≥90, 30°, Aluminium, white/black, 171x171x114 mm, 4000K, on/off | 190.00 | 38 |

ALRAI LED ELITE

| | | | |
|--------------|--|--------|----|
| DWL9235i-WW | ALRAI, 35W, 230Vac, CRI≥90, 30°, Aluminium, white/black, 171x171x114 mm, 3000K, on/off | 240.00 | 38 |
| DWL9235i-NW | ALRAI, 35W, 230Vac, CRI≥90, 30°, Aluminium, white/black, 171x171x114 mm, 4000K, on/off | 240.00 | 38 |
| DWLD9235i-WW | ALRAI, 35W, 230Vac, CRI≥90, 30°, Aluminium, white/black, 171x171x114 mm, 3000K, DALI | 280.00 | 38 |
| DWLD9235i-NW | ALRAI, 35W, 230Vac, CRI≥90, 30°, Aluminium, white/black, 171x171x114 mm, 4000K, DALI | 280.00 | 38 |

ALRAI TWIN DOWNLIGHT Series • for square holes of 310 x 160 mm

Alrai is an LED recessed ceiling luminaire fitted with COB technology and high color rendering. The fixture is adjustable in all directions and is fitted with two light sources. The frame is made of white cast aluminum, and upon request is available in gray or black trims. The fastening system allows installation in ceilings of different thicknesses ranging from 0.5 to 25 mm. This unit is ideal for illumination in retail shops, shopping centers, residential environments and offices.

ALRAI TWIN LED

| | | | |
|------------|---|--------|----|
| DWL9270-WW | ALRAI TWIN, 2x35W, 230Vac, CRI≥90, 2x30°, Alu, white/bl., 323x171x114 mm, 3000K, on/off | 430.00 | 38 |
| DWL9270-NW | ALRAI TWIN, 2x35W, 230Vac, CRI≥90, 2x30°, Alu, white/bl., 323x171x114 mm, 4000K, on/off | 430.00 | 38 |

ALRAI TWIN LED ELITE

| | | | |
|--------------|---|--------|----|
| DWL9270i-WW | ALRAI TWIN, 2x35W, 230Vac, CRI≥90, 2x30°, Alu, white/bl., 323x171x114 mm, 3000K, on/off | 530.00 | 38 |
| DWL9270i-NW | ALRAI TWIN, 2x35W, 230Vac, CRI≥90, 2x30°, Alu, white/bl., 323x171x114 mm, 4000K, on/off | 530.00 | 38 |
| DWLD9270i-WW | ALRAI TWIN, 2x35W, 230Vac, CRI≥90, 2x30°, Alu, white/bl., 323x171x114 mm, 3000K, DALI | 620.00 | 38 |
| DWLD9270i-NW | ALRAI TWIN, 2x35W, 230Vac, CRI≥90, 2x30°, Alu, white/bl., 323x171x114 mm, 4000K, DALI | 620.00 | 38 |

POLARIS DOWNLIGHT Series • for round (Ø 160 mm) & square holes (160 x 160 mm)

Polaris-i LED is an ultra slim LED downlight available in round or square shape, the anti-glare screen makes it possible to install it even in workplaces with VDT. The included power supply works directly with the mains voltage. Therefore it is ideal for lighting of shops, halls, clinics, offices and homes.

POLARIS ROUND

| | | | |
|-------------|---|-------|----|
| DWL0215T-WW | POLARIS ROUND, 15W, 230Vac, CRI≥80, 110°, Alu, white, Ø172x26 mm, 3000K, on/off | 85.00 | 39 |
| DWL0215T-NW | POLARIS ROUND, 15W, 230Vac, CRI≥80, 110°, Alu, white, Ø172x26 mm, 4000K, on/off | 85.00 | 39 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|-------------|---|----------|-------|
| | POLARIS SQUARE | | |
| DWL0215Q-WW | POLARIS SQUARE, 15W, 230Vac, CRI≥80, 110°, Alu, white, 172x172x24 mm, 3000K, on/off | 85.00 | 39 |
| DWL0215Q-NW | POLARIS SQUARE, 15W, 230Vac, CRI≥80, 110°, Alu, white, 172x172x24 mm, 4000K, on/off | 85.00 | 39 |

ART RGB DOWNLIGHT · for round (Ø 165 mm) holes

Ultra Slim Recessed LED downlight Ø 180mm in RGB light. Color management is possible through the wide range of controllers that Arena Luci provides, ideal for installation in suspended ceilings. **Power supply is not included.**

| | | | |
|-------------|--|--------|----|
| PNL1810-RGB | ART LED RGB, 12W, 24Vdc, RGB Full Color, 120°, Alu, white, Ø180x20 mm, external dimm | 160.00 | 39 |
|-------------|--|--------|----|

MINI LED DOWNLIGHT · for round (Ø 25 mm) holes

Mini LED downlight, 1.2 watt with 50° optical system, **the power supply LP2059 is not included.**

| | | | |
|-----------|---|-------|----|
| FL1303-WW | MINI LED, 1,2W, 350mA, CRI≥85, 50°, Alu/silver, Ø30x10 mm, 3200K, external power supply | 35.00 | 40 |
| FL1303-NW | MINI LED, 1,2W, 350mA, CRI≥85, 50°, Alu/silver, Ø30x10 mm, 4000K, external power supply | 35.00 | 40 |
| FL1303-W | MINI LED, 1,2W, 350mA, CRI≥85, 50°, Alu/silver, Ø30x10 mm, 6000K, external power supply | 35.00 | 40 |

Accessories (example)

| | | | |
|--------|---|-------|-----|
| LP2059 | Switching power supply constant current, 230Vac, 350mA, 6W, 57x40x21 mm | 31.50 | 124 |
|--------|---|-------|-----|

IP65 MINI LED MODULE · for round (Ø 25 mm) holes

This module consists of three high-brightness LEDs with 160° beam aperture, and a 80mm wheelbase. Its mechanical, optical and elevated light intensity makes it the ideal unit for uniform backlight illumination. The double-sided adhesive on the back of the modules allows for faster installation. The maximum number of modules that can be connected with a single input is 20 units, while the minimum is 1 unit. Code refers to one single module. Dimmable like an LED strip. **Power supply is not included.**

| | | | |
|------------|---|-------|----|
| MOD0003-WW | MINI LED MODULE, 1,9W, 12Vdc, CRI≥80, 160°, white, 92x17,5x7 mm, 3000K, external p.s. | 10.00 | 40 |
| MOD0003-WW | MINI LED MODULE, 1,9W, 12Vdc, CRI≥80, 160°, white, 92x17,5x7 mm, 6000K, external p.s. | 10.00 | 40 |

Accessories (example)

| | | | |
|-----------|---|-------|-----|
| LP9050-12 | Switching power supply constant voltage, 110-240Vac, 12Vdc, 50W, 185x64x22 mm | 59.00 | 121 |
|-----------|---|-------|-----|

IP67 MICRO LED MODULE · for round (Ø 8 mm) holes

Mini round LED module for recessed installations, beam aperture 30°. Available in 2 different colour temperatures. **Power supply not included.**

| | | | |
|------------|---|-------|----|
| MOD1580-WW | MICRO LED MODULE, 0,2W, 12Vdc, CRI≥80, 30°, Alu/silver, 12Øx27 mm, 3200K, external p.s. | 10.00 | 41 |
| MOD1580-W | MICRO LED MODULE, 0,2W, 12Vdc, CRI≥80, 30°, Alu/silver, 12Øx27 mm, 5500K, external p.s. | 10.00 | 41 |

Accessories (example)

| | | | |
|-----------|---|-------|-----|
| LP9012-12 | Switching power supply constant voltage, 110-240Vac, 12Vdc, 12W, 128x50x13 mm | 21.50 | 121 |
|-----------|---|-------|-----|



ARTIKEL BEZEICHNUNG VP (CHF) Seite

MINI LED MODULE • for round (Ø 13 mm) holes • white & fixed colors available

Mini round LED module for recessed installations, beam angle 30°. Available in 2 different colour temperatures and in red, green & blue. Easy installation thanks to the threaded locknut and steel springs integrated into the downlight. **Power supply not included.**

| | | | |
|-----------|---|-------|----|
| LS1547-WW | MICRO LED MODULE, 0,7W, 12Vdc, CRI≥80, 30°, Alu/silver, 17Øx16 mm, 3200K, external p.s. | 28.00 | 41 |
| LS1547-W | MICRO LED MODULE, 0,7W, 12Vdc, CRI≥80, 30°, Alu/silver, 17Øx16 mm, 5500K, external p.s. | 28.00 | 41 |
| LS1547-R | MICRO LED MODULE, 0,7W, 12Vdc, CRI≥80, 30°, Alu/silver, 17Øx16 mm, red, external p.s. | 28.00 | 41 |
| LS1547-G | MICRO LED MODULE, 0,7W, 12Vdc, CRI≥80, 30°, Alu/silver, 17Øx16 mm, green, external p.s. | 28.00 | 41 |
| LS1547-B | MICRO LED MODULE, 0,7W, 12Vdc, CRI≥80, 30°, Alu/silver, 17Øx16 mm, blue, external p.s. | 28.00 | 41 |

INSTALL HOUSINGS (for MR16 lampholders)

This Series is only available on request!

42

BLADE MODULE • Gypsum recessed ceiling light

Recessed luminaire in paintable plaster, complete with LED strip. The fixing of the luminaire is facilitated by the wings of metal mesh embedded in the body. It can be installed on the walls and it can be used, for example, as a helping light, to illuminate passages or border, or simply as a stair/steps light. **Power supply not included.**

| | | | |
|------------|--|--------|----|
| PLL1530-WW | BLADE, 9W, 12Vdc, CRI≥80, 35° asim., Gypsum/metall mesh, 550x60 mm, 3000K, ext. p.s. | 150.00 | 43 |
| PLL1530-W | BLADE, 9W, 12Vdc, CRI≥80, 35° asim., Gypsum/metall mesh, 550x60 mm, 6000K, ext. p.s. | 150.00 | 43 |
| PLL1530 | BLADE, without LED Strip | 85.00 | 43 |

LINEA MODULE • Gypsum recessed ceiling light

Ceiling-recessed lighting in paintable gypsum plaster. Developed to host LED strips of different models. The fixing of the ceiling lighting is facilitated by the embedded wings of metal mesh in the body. Designed for either individual installations and creation of multiple lines of cut light in ceilings or walls. The LED strip is easily applied after installation.

| | | | |
|---------|--|--------|----|
| PL1533C | LINEA, external dimensions: 310 x 100 mm, without LED strip & cover | 95.00 | 43 |
| PL1533 | LINEA, external dimensions: 510 x 100 mm, without LED strip & cover | 120.00 | 43 |
| PL1533B | LINEA, external dimensions: 810 x 100 mm, without LED strip & cover | 160.00 | 43 |
| PLC1533 | LINEA „L“, external dimensions: 165 x 165 mm (100 mm to line), without LED strip & cover | 85.00 | 43 |
| PLT1533 | LINEA „T“, external dimensions: 220 x 165 mm (100 mm to line), without LED strip & cover | 98.00 | 43 |

Accessories

| | | | |
|---------|--------------------------------------|-------|----|
| APL1533 | Milky cover (frosted) for LINEA, 2 m | 27.50 | 43 |
|---------|--------------------------------------|-------|----|

POLARIS-C SURFACE MOUNTING Series

Polaris-c LED is a ceiling or wall light available in round or square shape, this series combines the collections of the series Polaris-i. Ideal for lighting of shopping malls, shops, waiting rooms, clinics, corridors, offices, workplaces with VDT.

POLARIS-C ROUND

| | | | |
|-------------|--|-------|----|
| PLL0215T-WW | POLARIS-C ROUND, 15W, 230Vac, CRI≥80, 110°, Alu/white, Ø174x36 mm, 3000K, on/off | 89.00 | 44 |
| PLL0215T-NW | POLARIS-C ROUND, 15W, 230Vac, CRI≥80, 110°, Alu/white, Ø174x36 mm, 4000K, on/off | 89.00 | 44 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--------------|--|----------|-------|
| | POLARIS-C QUADRO | | |
| PLLL0215Q-WW | POLARIS-C QUADRO, 15W, 230Vac, CRI≥80, 110°, Alu/white, 173x173x36 mm, 3000K, on/off | 89.00 | 44 |
| PLL0215Q-NW | POLARIS-C QUADRO, 15W, 230Vac, CRI≥80, 110°, Alu/white, 173x173x36 mm, 4000K, on/off | 89.00 | 44 |

TUBO 20 SURFACE MOUNTING Series (suspended installation is also possible)

Aluminum made circular ceiling light for surface / suspension application, high brightness COB LED technology and reflector with high reflection treatment. Ideal for lighting shopping centers and even in home light. Available 40° beam angle on request.

| | | | |
|------------|--|--------|----|
| DWL0020-WW | TUBO 20, 20W, 230Vac, CRI≥80, 24°, Alu/white, Ø180x185 mm, 3000K, on/off | 280.00 | 45 |
| DWL0020-NW | TUBO 20, 20W, 230Vac, CRI≥80, 24°, Alu/white, Ø180x185 mm, 4000K, on/off | 280.00 | 45 |

CUBO SURFACE MOUNTING Series

Aluminum made circular ceiling light for surface / suspension application, high brightness COB LED technology and reflector with high reflection treatment. Ideal for lighting shopping centers and even in home light. Available 40° beam angle on request.

| | | | |
|-------------|--|--------|----|
| DWL0010N-WW | CUBO, 10W, 230Vac, CRI≥80, 43°, Alu/dark grey, 90x90x103 mm, 3000K, on/off | 210.00 | 45 |
| DWL0010N-NW | CUBO, 10W, 230Vac, CRI≥80, 43°, Alu/dark grey, 90x90x103 mm, 4000K, on/off | 210.00 | 45 |

PAINTER WALL MOUNTING Series (down & up/down) · IP65

LED wall fixture with one or two light beam with adjustable beam direction, all the projector body is aluminium made, suitable for indoor and outdoor installations. Easy installation with dedicated bracket included.

Single Beam (down)

| | | | |
|------------|---|--------|----|
| WAL3005-WW | PAINTER, 5W, 230Vac, CRI≥80, 90°, Alu/silver, 100x90x81 mm, 3000K, on/off | 210.00 | 46 |
| WAL3005-W | PAINTER, 5W, 230Vac, CRI≥80, 90°, Alu/silver, 100x90x81 mm, 6000K, on/off | 210.00 | 46 |

Double Beam (down / up)

| | | | |
|------------|--|--------|----|
| WAL3006-WW | PAINTER, 10W, 230Vac, CRI≥80, 2x90°, Alu/silver, 100x90x132 mm, 3000K, on/off | 315.00 | 46 |
| WAL3006-NW | PAINTER, 10W, 230Vac, CRI≥80, 2x90°, Alu/silver, 100x90x132 mm, 4000K, on/off | 315.00 | 46 |
| WAL3006-W | PAINTER, 10W, 230Vac, CRI≥80, 2x90°, Alu/silver, 100x90x132 mm, 6000K, on/off | 315.00 | 46 |
| WAL3007-WW | PAINTER, 10W, 230Vac, CRI≥80, 90°/1°, Alu/silver, 100x90x132 mm, 3000K, on/off | 335.00 | 46 |
| WAL3007-W | PAINTER, 10W, 230Vac, CRI≥80, 90°/1°, Alu/silver, 100x90x132 mm, 6000K, on/off | 335.00 | 46 |
| WAL3008-WW | PAINTER, 10W, 230Vac, CRI≥80, 2x1°, Alu/silver, 100x90x132 mm, 3000K, on/off | 370.00 | 46 |
| WAL3008-W | PAINTER, 10W, 230Vac, CRI≥80, 2x1°, Alu/silver, 100x90x132 mm, 6000K, on/off | 370.00 | 46 |

MUSA WALL MOUNTING Series (up/down)

LED wall fixture with one or two light beam with adjustable beam direction, all the projector body is aluminium made, suitable for indoor and outdoor installations. Easy installation with dedicated bracket included.

| | | | |
|------------|--|--------|----|
| WAL5020-WW | MUSA, 20W, 230Vac, CRI≥80, 2x120°, Alu/white, 250x169x97 mm, 3000K, on/off | 475.00 | 47 |
| WAL5020-NW | MUSA, 20W, 230Vac, CRI≥80, 2x120°, Alu/white, 250x169x97 mm, 4000K, on/off | 475.00 | 47 |
| WAL5020-W | MUSA, 20W, 230Vac, CRI≥80, 2x120°, Alu/white, 250x169x97 mm, 6000K, on/off | 475.00 | 47 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|
|---------|-------------|----------|-------|

IN WALL MOUNTING • round asymmetrical, IP65

Compact LED fixture with asymmetric beam used as marking steps or leader illumination. WAL0016 can be installed directly in plaster walls or false-ceiling thanks to two steel clamps integrated or through the included recessed box.

| | | | |
|-------------|--|--------|----|
| WAL0016-W/W | IN WALL ROUND, 3,5W, 230Vac, CRI≥80, 15°, Alu/silver, Ø80x55 mm, 3000K, on/off | 120.00 | 50 |
| WAL0016-W | IN WALL ROUND, 3,5W, 230Vac, CRI≥80, 15°, Alu/silver, Ø80x55 mm, 6000K, on/off | 120.00 | 50 |

ATRIA • on wall mounting, indirect lighting

This elegant and grey aluminum wall-mounted luminaire creates a reflection on the installation surface, with decorative and diffused backlight.

| | | | |
|------------|--|--------|----|
| PLL3015-WW | ATRIA, 15W, 230Vac, CRI>80, diffused backlight, Alu/grey, 180x180x51 mm, 3000K, on/off | 290.00 | 51 |
| PLL3015-NW | ATRIA, 15W, 230Vac, CRI>80, diffused backlight, Alu/grey, 180x180x51 mm, 4000K, on/off | 290.00 | 51 |

KUMA-S · on wall/ceiling mounting, IP65, Emergency Version available

Waterproof LED ceiling light, for passageways, walls, offices, homes and outdoor in general. ABS body, metal brackets for mounting.

| | | | |
|--------------------|---|---------------|----|
| PLL6512-NW | KUMA, 10W, 230Vac, CRI≥80, 110°, PMMA/ABS/white, Ø270x90 mm, 4000K, on/off | 140.00 | 51 |
| PLL6522-NW | KUMA, 20W, 230Vac, CRI≥80, 110°, PMMA/ABS/white, Ø324x100 mm, 4000K, on/off | 235.00 | 51 |
| PLLS6523-NW | same Features like PLL6522-NW, but with Sensor & Emergency-Kit included | 420.00 | 51 |

GEMMA-S Series • wall/ceiling mounting,

Gemma LED is the new series of fixtures with LED technology that Arena Luci offers in three different sizes and two colour temperatures, to meet all installation requirements. Ideal for walkways, above doors, offices, houses, stairways and interior in general. Polycarbonate housing with detachable mounting bracket.

13W / 240 mm Ø

| | | | |
|------------|---|-------|----|
| PLL2013-WW | GEMMA, 13W, 230Vac, CRI≥80, 120°, PC/white, Ø240x65 mm, 3200K, on/off | 98.00 | 52 |
| PLL2013-NW | GEMMA, 13W, 230Vac, CRI≥80, 120°, PC/white, Ø240x65 mm, 4500K, on/off | 98.00 | 52 |

17W / 290 mm Ø

| | | | |
|------------|---|--------|----|
| PLL2017-WW | GEMMA, 17W, 230Vac, CRI≥80, 120°, PC/white, Ø290x65 mm, 3200K, on/off | 120.00 | 52 |
| PLL2017-NW | GEMMA, 17W, 230Vac, CRI≥80, 120°, PC/white, Ø290x65 mm, 4500K, on/off | 120.00 | 52 |

22W / 330 mm Ø

| | | | |
|-------------|---|--------|----|
| PLL2022-W/W | GEMMA, 22W, 230Vac, CRI≥80, 120°, PC/white, Ø330x70 mm, 3200K, on/off | 165.00 | 52 |
| PLL2022-N/W | GEMMA, 22W, 230Vac, CRI≥80, 120°, PC/white, Ø330x70 mm, 4500K, on/off | 165.00 | 52 |

URANO • Suspension Chandelier (LED Lamp E27 included)

Suspension chandelier made of painted aluminum. Equipped with Globo LED lamp with E27 socket (interchangeable).

| | | | |
|------------|--|--------|----|
| LAM7060-WW | URANO, 21W, 230Vac, CRI≥80, 100°, Alu/grey, Ø300x250 mm, 3000K, on/off | 140.00 | 53 |
|------------|--|--------|----|



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|
|---------|-------------|----------|-------|

MERCURIO • Suspension Chandelier (LED Lamp E27 included)

Suspension chandelier made of painted aluminum. Equipped with Globo LED lamp with E27 socket (interchangeable).

| | | | |
|------------|---|--------|----|
| LAM6060-WW | MERCURIO, 21W, 230Vac, CRI≥80, 110°, Alu/grey, Ø280x380 mm, 3000K, on/off | 140.00 | 53 |
|------------|---|--------|----|

JUMBO RGBW • Fiber Optics LED Source

This powerful fiber optics luminaire is available only in the Elite series. It is fitted with an aluminum body and mounts a 250W LED light source. RGB+W color mixing is controllable via standard DMX signal. This makes it the ideal unit where both energy savings and flexibility of usage are required. The unit can mount fiber optics bundles with diameters from 8.3 to 28 mm in size. This luminaire, like all those of the Elite Series is made in Italy and contains premium components such as high performance power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|-------------|---|----------|----|
| AR2951-RGBW | JUMBO, 250W, 230Vac, RGBW, Alu/black, 399x257x153 mm, DMX/XLR5 in/out | 3'150.00 | 54 |
|-------------|---|----------|----|

DASHING LED • Fiber Optics LED Source

This fiber optics luminaire is available only in the Elite series and it is fitted with an aluminum body and utilizes an 80W LED light source. It is available with both a DMX dimmable version and an ON-OFF version. The fiber optics combined with LED light sources allow substantial energy saving, making it ideal where both energy efficiency and flexibility of usage are required. The unit can mount fiber optics bundles with diameters from 8.3 to 28 mm in size. This luminaire, like all those of the Elite Series is made in Italy and contains premium components such as high performance power supply featuring ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|----------|--|----------|----|
| AR2953-W | DASHING, 80W, 230Vac, 6000K, Alu/black, 299x257x153 mm, DMX/XLR5 in/out | 2'500.00 | 54 |
| AR2952-W | DASHING, 80W, 230Vac, 6000K, Alu/black, 299x257x153 mm, on/off (without DMX) | 1'630.00 | 54 |

PROMO 5 ELITE • Rotating Image-/Logo-Projector

Promo 5 LED is available only in the Elite version. It is a rotating image luminaire that features either a rotating or fixed gobo. A gobo consists of a glass or metal disc where a design of either simple or complex shapes can be applied to obtain the desired effect on the surface. The light source consists of cutting-edge dimmable COB LED available only in 5500K. Suitable for commercial applications, museums, architectural, theaters and TV studios as well as in residential environments. The body is made from a combination of extruded aluminum and steel parts, while the finish is obtained by means of scratch-resistant epoxy powder. This luminaire like all those of the Elite Series is made in Italy and contains premium components such as high performance power supply featuring, ripple-free technology and color temperature persistence with high MacAdam classification.

| | | | |
|-----------|--|----------|----|
| PRF0150-W | PROMO 5, 160W, 230Vac, 5500K, Alu/black, 20°-40° Zoom, CRI≥90, 1 rotating Gobo, continuous gobo rotation with on/off switch, double gobo accessory for water & snow effect is optional available | 1'820.00 | 55 |
|-----------|--|----------|----|

Accessories

| | | | |
|-------------|--|--------|----|
| COVER150 | Cover for outdoor installation | TBA | 55 |
| GOBOS501 | Glass Gobo with Stars Ø 50 mm | TBA | 55 |
| EFR0150 | Motor and plate kit for water & snow effects | TBA | 55 |
| KITACQUA150 | Kit with color filter & glasses for water effect | 330.00 | 55 |



ARTIKEL BEZEICHNUNG VP (CHF) Seite

LED BAR 50cm • IP66

LED Bar is a bar with IP66 protection factor that mounts cutting-edge high-power LEDs with 30° fixed optics and it is available in RGB, cool white (6000K) or warm white (3000K) versions. The 50 cm version mounts 12 LEDs. LED bar can be purchased with an optional diagonal anti-glare hood to prevent the light leakage from the sides in case this leakage is considered unsightly. LED Bar is ideal for use in both outdoor and indoor installations. The fastening brackets comes with adjustable angle in order to facilitate the orientation of the light beam. **Power supply is not included** (dimmable like an LED strip).

50 cm / 24W / 30°

| | | | |
|-------------|---|--------|----|
| BAR1060-WW | LED BAR 50, 24W, 24Vdc, CRI≥80, 30°, Alu/temp.Glass, 510x57x77 mm, 3000K | 460.00 | 56 |
| BAR1060-W | LED BAR 50, 24W, 24Vdc, CRI≥80, 30°, Alu/temp.Glass, 510x57x77 mm, 6000K | 460.00 | 56 |
| BAR1060-RGB | LED BAR 50, 24W, 24Vdc, CRI≥80, 30°, Alu/temp.Glass, 510x57x77 mm, RGB Full Color | 560.00 | 56 |

50 cm / 24W / 35°

| | | | |
|-------------|---|--------|----|
| BAR1070-WW | LED BAR 50, 24W, 24Vdc, CRI≥80, 35°, Alu/temp.Glass, 510x57x77 mm, 3000K | 460.00 | 56 |
| BAR1070-W | LED BAR 50, 24W, 24Vdc, CRI≥80, 35°, Alu/temp.Glass, 510x57x77 mm, 6000K | 460.00 | 56 |
| BAR1070-RGB | LED BAR 50, 24W, 24Vdc, CRI≥80, 35°, Alu/temp.Glass, 510x57x77 mm, RGB Full Color | 560.00 | 56 |

100 cm / 48W / 30°

| | | | |
|-------------|--|--------|----|
| BAR1062-WW | LED BAR 100, 48W, 24Vdc, CRI≥80, 30°, Alu/temp.Glass, 985x57x77 mm, 3000K | 660.00 | 56 |
| BAR1062-W | LED BAR 100, 48W, 24Vdc, CRI≥80, 30°, Alu/temp.Glass, 985x57x77 mm, 6000K | 660.00 | 56 |
| BAR1062-RGB | LED BAR 100, 48W, 24Vdc, CRI≥80, 30°, Alu/temp.Glass, 985x57x77 mm, RGB Full Color | 900.00 | 56 |

100 cm / 48W / 35°

| | | | |
|-------------|--|--------|----|
| BAR1072-WW | LED BAR 100, 48W, 24Vdc, CRI≥80, 35°, Alu/temp.Glass, 985x57x77 mm, 3000K | 660.00 | 56 |
| BAR1072-W | LED BAR 100, 48W, 24Vdc, CRI≥80, 35°, Alu/temp.Glass, 985x57x77 mm, 6000K | 660.00 | 56 |
| BAR1072-RGB | LED BAR 100, 48W, 24Vdc, CRI≥80, 35°, Alu/temp.Glass, 985x57x77 mm, RGB Full Color | 950.00 | 56 |

Accessories

| | | | |
|--------|---|-------|----|
| PR1060 | Diagonal anti glare hood, black, (like a fixed barndoor) for 50 cm LED BARs | 29.00 | 55 |
| PR1062 | Diagonal anti glare hood, black, (like a fixed barndoor) for 50 cm LED BARs | 57.00 | 55 |

Please ask for different IP66 connectors (male & female)!

VEGA 12 • for in-ground installation, IP67

This LED recessed carriageable luminaire, features a glossy stainless steel (inox 316) head. Its 12 surface-grazing light beams make it the ideal unit for illuminating paths and driveways, but also for decorative installations of indoor and outdoor facades and walls. The fixture is equipped with recessed box.

| | | | |
|------------|---|--------|----|
| ING0012-WW | VEGA, 8W, 230Vac, CRI≥80, 12 light beams, shiny steel, Ø88x92 mm, 3200K, on/off | 410.00 | 58 |
| ING0012-W | VEGA, 8W, 230Vac, CRI≥80, 12 light beams, shiny steel, Ø88x92 mm, 5500K, on/off | 410.00 | 58 |

NAVIGATION LIGHTS • for in-ground installation, IP67

Stainless steel (INOX AISI 316) carriageable recessed LED light with side light effect: 1/2/4 beams. The product can be used for a wide range of installations indoor or outdoor installations like paths and sidewalks. Thanks to small sizes the fixture can be installed in a wide range of applications. The fixture is equipped with recessed box.

1 light beam (120°)

| | | | |
|------------|--|--------|----|
| ING0010-WW | NAV, 3W, 24Vdc, CRI≥80, 1 light beam 120°, shiny steel, Ø70x98 mm, 3200K, without p.s. | 210.00 | 58 |
| ING0010-W | NAV, 3W, 24Vdc, CRI≥80, 1 light beam 120°, shiny steel, Ø70x98 mm, 5500K, without p.s. | 210.00 | 58 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------------------------------|--|----------|-------|
| ING0008-WW | NAV, 3W, 24Vdc, CRI≥80, 1 light beam 120°, shiny steel, Ø116x91 mm, 3200K, without p.s. | 320.00 | 59 |
| ING0008-W | NAV, 3W, 24Vdc, CRI≥80, 1 light beam 120°, shiny steel, Ø116x91 mm, 5500K, without p.s. | 320.00 | 59 |
| 2 light beams (2 x 120°) | | | |
| ING0011-WW | NAV, 3W, 24Vdc, CRI≥80, 2 light beams x 120°, shiny steel, Ø70x98 mm, 3200K, without p.s. | 210.00 | 58 |
| ING0011-W | NAV, 3W, 24Vdc, CRI≥80, 2 light beams x 120°, shiny steel, Ø70x98 mm, 5500K, without p.s. | 210.00 | 58 |
| ING0009-WW | NAV, 3W, 24Vdc, CRI≥80, 2 light beams x 120°, shiny steel, Ø116x91 mm, 3200K, without p.s. | 320.00 | 59 |
| ING0009-W | NAV, 3W, 24Vdc, CRI≥80, 2 light beams x 120°, shiny steel, Ø116x91 mm, 5500K, without p.s. | 320.00 | 59 |
| 4 light beams (4 x 80°) | | | |
| ING0007-WW | NAV, 3W, 24Vdc, CRI≥80, 4 light beams x 80°, shiny steel, Ø116x91 mm, 3200K, without p.s. | 320.00 | 59 |
| ING0007-W | NAV, 3W, 24Vdc, CRI≥80, 4 light beams x 80°, shiny steel, Ø116x91 mm, 5500K, without p.s. | 320.00 | 59 |

INGROUND POWER · for in-ground installation (1'760 kg load), round, IP67

Walk-over recessed LED light with symmetrical optical system. The product can be used for indoor or outdoor installations. Available in three different white color temperature 3000K, 4000K, 6000K. The fixture is equipped with recessed box. Dimmable with DMX interface but partially and with discrete levels only.

| | | | |
|------------|--|--------|----|
| ING0050-WW | 50W, 24Vdc, CRI≥80, 15°, Inox316L/Alu/temp.Glass, Ø250x190 mm, 3000K, without p.s. | 900.00 | 60 |
| ING0050-NW | 50W, 24Vdc, CRI≥80, 15°, Inox316L/Alu/temp.Glass, Ø250x190 mm, 4000K, without p.s. | 900.00 | 60 |
| ING0050-W | 50W, 24Vdc, CRI≥80, 15°, Inox316L/Alu/temp.Glass, Ø250x190 mm, 6000K, without p.s. | 900.00 | 60 |

INGROUND ROUND POWER – ADJUSTABLE BEAM · for in-ground installation, IP67

Recessed walk-on LED luminaire with narrow and adjustable optics. The product is fit for both indoor and outdoor installations. Its powerful light beam makes it the ideal product where you need light grazing through the columns and walls, even very large ones. The 316L frosted stainless steel and tempered glass upper head make this product ideal for various applications. Available in three white color temperatures: 3000K, 4000K, 6000K, and also RGB. Recessed box for walls is included in the package. Dimmable with DMX interface but partially and with discrete levels only.

| | | | |
|-------------|--|----------|----|
| ING0036-WW | 36W, 24Vdc, CRI≥80, 15°, Inox316L/Alu/temp.Glass, Ø250x190 mm, 3000K, without p.s. | 900.00 | 60 |
| ING0036-NW | 36W, 24Vdc, CRI≥80, 15°, Inox316L/Alu/temp.Glass, Ø250x190 mm, 4000K, without p.s. | 900.00 | 60 |
| ING0036-W | 36W, 24Vdc, CRI≥80, 15°, Inox316L/Alu/temp.Glass, Ø250x190 mm, 6000K, without p.s. | 900.00 | 60 |
| ING0036-RGB | 36W, 24Vdc, RGB, 15°, Inox316L/Alu/temp.Glass, Ø250x190 mm, without power supply | 1'140.00 | 60 |

INGROUND SQUARE ASYMMETRICAL · for in-ground installation, IP67

Walk-over recessed LED light with asymmetrical optical system. The product can be used for indoor or outdoor installations. The fixture is equipped with recessed box. Without power supply.

328 x 63 x 71 mm

| | | | |
|------------|--|--------|----|
| FL0056-WW | 7W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, 328x63x71 mm, 3200K | 330.00 | 61 |
| FL0056-W | 7W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, 328x63x71 mm, 5500K | 330.00 | 61 |
| FL0056-RGB | 9W, 24Vdc, RGB, 45° asymmetrical, Inox316/Alu/temp.Glass, 328x63x71 mm | 460.00 | 61 |

195 x 63 x 71 mm

| | | | |
|-----------|--|--------|----|
| FL0058-WW | 3.5W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, 195x63x71 mm, 3200K | 250.00 | 61 |
| FL0058-NW | 3.5W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, 195x63x71 mm, 3200K | 250.00 | 61 |
| FL0058-W | 3.5W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, 195x63x71 mm, 5500K | 250.00 | 61 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|------------|--|----------|-------|
| FL0058-RGB | 5W, 24Vdc, RGB, 45° asymmetrical, Inox316/Alu/temp.Glass, 195x63x71 mm | 300.00 | 61 |

INGROUND ROUND • for in-ground installation, IP67

Walk-over recessed LED lights with asymmetrical & symmetrical optical system. The product can be used for indoor or outdoor installations. The fixture is equipped with recessed box. Without power supply.

18/20W, 45° asymmetrical

| | | | |
|------------|--|--------|----|
| FL0066-WW | 18W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø173x77 mm, 3200K | 420.00 | 62 |
| FL0066-W | 18W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø173x77 mm, 5500K | 420.00 | 62 |
| FL0066-RGB | 20W, 24Vdc, RGB Full Color, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø173x77 mm | 540.00 | 62 |

18/20W, 30° symmetrical

| | | | |
|--------|---|--------|----|
| FL0067 | 18W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø173x77 mm, 3200K | 410.00 | 62 |
| FL0065 | 18W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø173x77 mm, 5500K | 410.00 | 62 |
| FL0070 | 20W, 24Vdc, RGB Full Color, 30° symmetrical, Inox316/Alu/temp.Glass, Ø173x77 mm | 525.00 | 62 |

10/11W, 45° asymmetrical

| | | | |
|------------|---|--------|----|
| FL0045-WW | 10W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm, 3200K | 250.00 | 63 |
| FL0045-W | 10W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm, 5500K | 250.00 | 63 |
| FL0045-RGB | 11W, 24Vdc, RGB Full Color, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm | 330.00 | 63 |

10/11W, 30° symmetrical

| | | | |
|-----------|--|--------|----|
| FL0042/24 | 10W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm, 3200K | 250.00 | 63 |
| FL0040/24 | 10W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm, 5500K | 250.00 | 63 |
| FL0050 | 11W, 24Vdc, RGB Full Color, 30° symmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm | 330.00 | 63 |

10W, 30° symmetrical, 230V

| | | | |
|--------|--|--------|----|
| FL0042 | 10W, 230Vac , CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm, 3200K | 280.00 | 63 |
| FL0040 | 10W, 230Vac , CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø108x108 mm, 5500K | 280.00 | 63 |

FINDER LED • PIVOTING LIGHT CONE (max. 20°). round, for in-ground installation, IP67

Floor recessed LED with adjustable light beam, thanks to a system placed on the side of the body of the headlight will be easy to orient the beam in the desired direction. Without power supply

| | | | |
|------------|--|--------|----|
| ING2110-WW | 10W, 24Vdc, CRI≥80, 15° spotlight / beam adjustable: 20°, Inox316/Alu/temp.Glass, Ø150x120 mm, 3000K | 340.00 | 63 |
| ING2110-W | 10W, 24Vdc, CRI≥80, 15° spotlight / beam adjustable: 20°, Inox316/Alu/temp.Glass, Ø150x120 mm, 6000K | 340.00 | 63 |

INGROUND MINI • for in-ground, wall or ceiling installation, IP67

Carriageable recessed LED light with asymmetrical optical system. The product can be used for indoor or outdoor installations. Thanks to the stainless steel springs the fixture can be installed directly in ceilings and walls. The fixture is equipped with recessed box.

3.5/4W, 45° asymmetrical, round

| | | | |
|------------|---|--------|----|
| FL1018-WW | 3.5W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø55x82 mm, 3200K | 150.00 | 64 |
| FL1018-W | 3.5W, 24Vdc, CRI≥80, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø55x82 mm, 5500K | 150.00 | 64 |
| FL1018-RGB | 4W, 24Vdc, RGB Full Color, 45° asymmetrical, Inox316/Alu/temp.Glass, Ø55x82 mm | 180.00 | 64 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|-------------|--|----------|-------|
| | 3.5/4W, 30° symmetrical, round | | |
| FL1009 | 3.5W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø55x82 mm, 3200K | 150.00 | 64 |
| FL1010 | 3.5W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, Ø55x82 mm, 5500K | 150.00 | 64 |
| FL1011 | 4W, 24Vdc, RGB Full Color, 30° symmetrical, Inox316/Alu/temp.Glass, Ø55x82 mm | 180.00 | 64 |
| | 3.5/4W, 30° symmetrical, square | | |
| ING8003-WW | 3.5W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, 55x55x82 mm, 3200K | 150.00 | 64 |
| ING8003-W | 3.5W, 24Vdc, CRI≥80, 30° symmetrical, Inox316/Alu/temp.Glass, 55x55x82 mm, 5500K | 150.00 | 64 |
| ING8003-RGB | 4W, 24Vdc, RGB Full Color, 30° symmetrical, Inox316/Alu/temp.Glass, 55x55x82 mm | 180.00 | 64 |

LED BAR INGROUND • IP67

Linear walk-over recessed LED light with symmetrical optical system. The product can be used for indoor or outdoor installations. The fixture is equipped with recessed box. Dimmable with DMX interface but partially and with discrete levels only. Without power supply.

| | | | |
|-------------|--|--------|----|
| | 3000K / 20° | | |
| ING0016A-WW | INGROUND LED BAR, 22W, 24Vdc, CRI≥80, 20°, Inox316/Alu/temp.Glass, 549x68x32 mm | 620.00 | 65 |
| ING0031A-WW | INGROUND LED BAR, 45W, 24Vdc, CRI≥80, 20°, Inox316/Alu/temp.Glass, 1025x68x32 mm | 930.00 | 65 |
| | 6000K / 20° | | |
| ING0016A-W | INGROUND LED BAR, 22W, 24Vdc, CRI≥80, 20°, Inox316/Alu/temp.Glass, 549x68x32 mm | 620.00 | 65 |
| ING0031A-W | INGROUND LED BAR, 45W, 24Vdc, CRI≥80, 20°, Inox316/Alu/temp.Glass, 1025x68x32 mm | 930.00 | 65 |

SOUL LED Series • Garden- & Outdoorspots • IP65

The excellent performance of this projector in terms of energy savings and light levels, accompanied by long-term freedom from maintenance and an IP65 protection make it ideal for most outdoor applications. The latest generation of LED light sources, in addition to the powerful light beam, provide a high color rendering index (CRI) in both the white color temperatures, making it a suitable to prevent change in the nocturnal perception of colors. RGB Versions must have a driver/power supply (not included).

| | | | |
|-------------|--|----------|----|
| | 45 Series / 45W | | |
| SPT2045-WW | SOUL 45, 45W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 265x160x150 mm, 3000K, on/off | 790.00 | 66 |
| SPT2045-W | SOUL 45, 45W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 265x160x150 mm, 6000K, on/off | 790.00 | 66 |
| SPT2045-RGB | SOUL 45, 45W, 24Vdc, RGB Full Color, 25°, Alu/temp.G./grey, 265x160x150 mm | 1'000.00 | 66 |
| | 25 Series / 25W | | |
| SPT2025-WW | SOUL 25, 25W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 227x120x150 mm, 3000K, on/off | 560.00 | 66 |
| SPT2025-W | SOUL 25, 25W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 227x120x150 mm, 6000K, on/off | 560.00 | 66 |
| SPT2025-RGB | SOUL 25, 25W, 24Vdc, RGB Full Color, 25°, Alu/temp.G./grey, 227x120x150 mm | 715.00 | 66 |
| | 17 Series / 17W | | |
| SPT2017-WW | SOUL 17, 17W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 170x112x112 mm, 3000K, on/off | 370.00 | 67 |
| SPT2017-W | SOUL 17, 17W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 170x112x112 mm, 6000K, on/off | 370.00 | 67 |
| SPT2017-RGB | SOUL 17, 17W, 24Vdc, RGB Full Color, 25°, Alu/temp.G./grey, 170x112x112 mm | 470.00 | 67 |
| | 8 Series / 8W | | |
| SPT2008-WW | SOUL 8, 8W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 144x95x95 mm, 3000K, on/off | 300.00 | 67 |
| SPT2008-W | SOUL 8, 8W, 230Vac, CRI≥80, 38°, Alu/temp.G./grey, 144x95x95 mm, 6000K, on/off | 300.00 | 67 |
| SPT2008-RGB | SOUL 8, 8W, 24Vdc, RGB Full Color, 25°, Alu/temp.G./grey, 144x95x95 mm | 335.00 | 67 |


ARCHITECTURAL LIGHTING
CATALOGUE
Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------------------|----------|-------|
| | Accessories | | |
| PR2025 | Spike for all SOUL LEDs | 23.50 | 66+67 |

REAL LED Series • Outdoorspot • IP65

Spot light illuminator with LED technology, powerful and concentrated beam, the protection rating IP65 makes it suitable for the most varied applications in both indoor and outdoor environments. Ideal for lighting monuments, columns and special places, even at considerable distances.

| | | | |
|-------------|--|--------|----|
| SPT1236-WW | REAL, 36W, 230Vac, CRI≥80, 30°, Alu/temp.G./grey, 237x165x82 mm, 3000K, on/off | 560.00 | 68 |
| SPT1236-W | REAL, 36W, 230Vac, CRI≥80, 30°, Alu/temp.G./grey, 237x165x82 mm, 6000K, on/off | 560.00 | 68 |
| SPT1236-RGB | REAL, 36W, 24Vdc, RGB Full Color, 30°, Alu/temp.G./grey, 237x165x82 mm | 640.00 | 68 |

15W LED SPOT • Outdoorspot • IP65

Spot light illuminator with LED technology, powerful and concentrated beam, the protection rating IP65 makes it suitable for the most varied applications in both indoor and outdoor environments. Ideal for lighting monuments, columns and special places, even at considerable distances.

| | | | |
|-------------|--|--------|----|
| SPT0016-WW | 15W, 230Vac, CRI≥80, 15°, Alu/temp.G./grey, 237x165x82 mm, 3000K, on/off | 390.00 | 68 |
| SPT0016-W | 15W, 230Vac, CRI≥80, 15°, Alu/temp.G./grey, 237x165x82 mm, 6000K, on/off | 390.00 | 68 |
| SPT0016-RGB | 15W, 24Vdc, RGB Full Color, 30°, Alu/temp.G./grey, 237x165x82 mm | 475.00 | 68 |

Accessories

| | | | |
|----------|----------------------------|-------|----|
| ASPT0016 | Spike for all 15W LED Spot | 25.00 | 68 |
|----------|----------------------------|-------|----|

10W LED SPOT • Outdoorspot • IP65

Aluminium LED Spot with adjustable beam direction thanks to the graduated bracket. It is also available a dedicated spike for ground installations.

| | | | |
|--------------|---|--------|----|
| SPT0126-WW | 10W, 230Vac, CRI≥80, 25°, Alu/temp.G./grey, 136x59x99 mm, 3200K, on/off | 245.00 | 69 |
| SPT0126-W | 10W, 230Vac, CRI≥80, 25°, Alu/temp.G./grey, 136x59x99 mm, 5500K, on/off | 245.00 | 69 |
| SPT0126-RGB | 10W, 24Vdc, RGB Full Color, 25°, Alu/temp.G./grey, 136x59x99 mm | 290.00 | 69 |
| SPT0126p-WW | 10W, 230Vac, CRI≥80, 25°, Alu/temp.G./grey, 136x59x99 mm, 3200K, on/off | 245.00 | 69 |
| SPT0126p-W | 10W, 230Vac, CRI≥80, 25°, Alu/temp.G./grey, 136x59x99 mm, 5500K, on/off | 245.00 | 69 |
| SPT0126p-RGB | 10W, 24Vdc, RGB Full Color, 25°, Alu/temp.G./grey, 136x59x99 mm | 290.00 | 69 |

EYE LED SPOT • Outdoorspot • IP65

Diffusing illuminator with LED technology with adjustable wall mount. Its IP65 rating makes it suitable for the most varied applications in both indoor and outdoor environments. Ideal for lighting walls, halls, shop windows, galleries, shops and anywhere you want a diffused lighting.

| | | | |
|------------|--|-------|----|
| SPT0003-WW | 3,5W, 230Vac, CRI≥80, 38°, Alu/grey, 101x65x65 mm, 3000K, on/off | 99.00 | 69 |
| SPT0003-W | 3,5W, 230Vac, CRI≥80, 25°, Alu/grey, 101x65x65 mm, 6000K, on/off | 99.00 | 69 |



| | | | |
|---------|-------------|----------|-------|
| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|

PAR LED RGBWA • Outdoorspot • IP65

PAR LED RGBWA is a professional projector, its 15W 9 LED lights (red, green, blue, white and amber in one single package) can create all the colours, thanks to the perfect mixing of tonalities. Its high performance optics create a powerful and uniform beam with an opening angle of 35°. It is possible to control it by DMX standard signal or to set directly on display. The IP65 rating makes PAR LED RGBWA perfect for installations for architectural and scenic lighting, both indoor and outdoor. Since it is flicker free, it can be easily used in TV and photo studios. **For other professional Show/Theater lighting – we have a separate catalogue! Please ask for it!**

| | | | |
|--------------|--|--------|----|
| AR3333-RGBWA | RGBWA PAR Spot 90W, 100-240Vac, CRI≥90, 35°, Alu/black, max noise: 0 dB, DMX | 720.00 | 70 |
| AR3304-MKII | we don't sell this product – please ask for alternatives! | - | 70 |

ARIEL LED 12W / 24W • In-/Outdoor Floodlight • IP65

Illuminator with LED technology, slim and stylish, the degree of protection IP65 makes it suitable for the most varied applications in both indoor and outdoor environments, thin and light can also be used with a binary attachment with three lines (code APL1443). Ideal for lighting above the door, in the hallways, windows, shops and everywhere diffused lighting is needed.

| | | | |
|-----------|---|--------|----|
| AR8012-WW | 12W, 230Vac, CRI≥80, 105°, Alu/grey/white, 138x128x25 mm, 3000K, on/off | 75.00 | 72 |
| AR8012-NW | 12W, 230Vac, CRI≥80, 105°, Alu/grey/white, 138x128x25 mm, 4000K, on/off | 75.00 | 72 |
| AR8024-WW | 24W, 230Vac, CRI≥80, 105°, Alu/grey/white, 138x128x25 mm, 3000K, on/off | 140.00 | 72 |
| AR8024-NW | 24W, 230Vac, CRI≥80, 105°, Alu/grey/white, 198x180x28 mm, 4000K, on/off | 140.00 | 72 |

CHRONO LED Series • In-/Outdoor Floodlight with Light Sensors • IP65

Crono floodlight is suitable to light up architectural details as well as homogeneous wall washer for facades and vertical surfaces, also suitable for parking lots, parks, gardens and monuments. Crono is equipped with 100-400 Lux ambient light sensor with hysteresis +/- 50 Lux and sampling every minute for automatic on/off function.

| | | | |
|-------------|---|--------|----|
| AR10010-WW | 10W, 240Vac, CRI≥80, 110°, Alu/white, 115x115x42 mm, 3000K, on/off, light sensor | 80.00 | 73 |
| AR10010-NW | 10W, 240Vac, CRI≥80, 110°, Alu/white, 115x115x42 mm, 4000K, on/off, light sensor | 80.00 | 73 |
| AR10020-WW | 20W, 240Vac, CRI≥80, 110°, Alu/white, 179x176x44 mm, 3000K, on/off, light sensor | 115.00 | 73 |
| AR10020-NW | 20W, 240Vac, CRI≥80, 110°, Alu/white, 179x176x44 mm, 4000K, on/off, light sensor | 115.00 | 73 |
| AR10020s-WW | 20W, 240Vac, CRI≥80, 110°, Alu/white, 179x176x44 mm, 3000K, on/off, bi-level motion sens. | 130.00 | 73 |
| AR10020s-NW | 20W, 240Vac, CRI≥80, 110°, Alu/white, 179x176x44 mm, 4000K, on/off, bi-level motion sens. | 130.00 | 73 |
| AR10030-WW | 30W, 240Vac, CRI≥80, 110°, Alu/white, 205x185x53 mm, 3000K, on/off, light sensor | 165.00 | 73 |
| AR10030-NW | 30W, 240Vac, CRI≥80, 110°, Alu/white, 205x185x53 mm, 4000K, on/off, light sensor | 165.00 | 73 |
| AR10030s-WW | 30W, 240Vac, CRI≥80, 110°, Alu/white, 205x185x53 mm, 3000K, on/off, bi-level motion sens. | 180.00 | 73 |
| AR10030s-NW | 30W, 240Vac, CRI≥80, 110°, Alu/white, 205x185x53 mm, 4000K, on/off, bi-level motion sens. | 180.00 | 73 |
| AR10050-WW | 50W, 240Vac, CRI≥80, 110°, Alu/black, 248x240x55 mm, 3000K, on/off, light sensor | 315.00 | 74 |
| AR10050-NW | 50W, 240Vac, CRI≥80, 110°, Alu/black, 248x240x55 mm, 4000K, on/off, light sensor | 315.00 | 74 |
| AR10050s-WW | 50W, 240Vac, CRI≥80, 110°, Alu/black, 248x240x55 mm, 3000K, on/off, bi-level motion sens. | 330.00 | 74 |
| AR10050s-NW | 50W, 240Vac, CRI≥80, 110°, Alu/black, 248x240x55 mm, 4000K, on/off, bi-level motion sens. | 330.00 | 74 |
| AR10100-WW | 100W, 240Vac, CRI≥80, 110°, Alu/black, 285x271x70 mm, 3000K, on/off, light sensor | 545.00 | 74 |
| AR10100-NW | 100W, 240Vac, CRI≥80, 110°, Alu/black, 285x271x70 mm, 4000K, on/off, light sensor | 545.00 | 74 |
| AR10100s-WW | 100W, 240Vac, CRI≥80, 110°, Alu/bl., 285x271x70 mm, 3000K, on/off, bi-level motion sensor | 560.00 | 74 |
| AR10100s-NW | 100W, 240Vac, CRI≥80, 110°, Alu/bl., 285x271x70 mm, 4000K, on/off, bi-level motion sensor | 560.00 | 74 |
| AR10150-WW | 150W, 240Vac, CRI≥80, 110°, Alu/black, 320x300x85 mm, 3000K, on/off, light sensor | 810.00 | 75 |
| AR10150-NW | 150W, 240Vac, CRI≥80, 110°, Alu/black, 320x300x85 mm, 4000K, on/off, light sensor | 810.00 | 75 |
| AR10150s-WW | 150W, 240Vac, CRI≥80, 110°, Alu/bl., 320x300x85 mm, 3000K, on/off, bi-level motion sensor | 825.00 | 75 |
| AR10150s-NW | 150W, 240Vac, CRI≥80, 110°, Alu/bl., 320x300x85 mm, 4000K, on/off, bi-level motion sensor | 825.00 | 75 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|-------------|---|----------|-------|
| AR10200-WW | 200W, 240Vac, CRI≥80, 110°, Alu/black, 335x365x85 mm, 3000K, on/off, light sensor | 1'050.00 | 75 |
| AR10200-NW | 200W, 240Vac, CRI≥80, 110°, Alu/black, 335x365x85 mm, 4000K, on/off, light sensor | 1'050.00 | 75 |
| AR10200s-WW | 200W, 240Vac, CRI≥80, 110°, Alu/bl., 335x365x85 mm, 3000K, on/off, bi-level motion sensor | 1'065.00 | 75 |
| AR10200s-NW | 200W, 240Vac, CRI≥80, 110°, Alu/bl., 335x365x85 mm, 4000K, on/off, bi-level motion sensor | 1'065.00 | 75 |

ATIK LED Series • In-/Outdoor Floodlight • IP65

ATIK is a floodlight with SMD LED technology, able to grant excellent luminous efficiency and **high CRI**. Equipped with aluminium reflector with high-reflection treatment and cut-off optical system. The heat sink accelerates the LED module cooling process. This can grant high-brightness, long duration and makes this device perfect for any kind of application. The installation is really easy thanks to its adjustable stainless bracket. The clear front-glass, the incorporated gasket kit and the anti-fog system allow this product to be used both for indoor and outdoor installations. Suitable for the illumination of gardens, parks, bushes, trees, facades, monuments and also cycling lanes and paths.

| | | | |
|-----------|---|----------|----|
| AR7010-WW | 10W, 240Vac, CRI≥85, 100°, Alu/grey, 130x158x55 mm, 3000K, on/off | 75.00 | 76 |
| AR7010-NW | 10W, 240Vac, CRI≥85, 100°, Alu/grey, 130x158x55 mm, 4000K, on/off | 75.00 | 76 |
| AR7030-WW | 30W, 240Vac, CRI≥85, 100°, Alu/grey, 214x238x67 mm, 3000K, on/off | 155.00 | 76 |
| AR7030-NW | 30W, 240Vac, CRI≥85, 100°, Alu/grey, 214x238x67 mm, 4000K, on/off | 155.00 | 76 |
| AR7050-WW | 50W, 240Vac, CRI≥85, 100°, Alu/grey, 253x290x74 mm, 3000K, on/off | 250.00 | 76 |
| AR7050-NW | 50W, 240Vac, CRI≥85, 100°, Alu/grey, 253x290x74 mm, 4000K, on/off | 250.00 | 76 |
| AR7070-WW | 70W, 240Vac, CRI≥85, 100°, Alu/grey, 253x290x74 mm, 3000K, on/off | 415.00 | 76 |
| AR7070-NW | 70W, 240Vac, CRI≥85, 100°, Alu/grey, 253x290x74 mm, 4000K, on/off | 415.00 | 76 |
| AR7100-WW | 100W, 240Vac, CRI≥85, 100°, Alu/grey, 331x359x110 mm, 3000K, on/off | 500.00 | 77 |
| AR7100-NW | 100W, 240Vac, CRI≥85, 100°, Alu/grey, 331x359x110 mm, 4000K, on/off | 500.00 | 77 |
| AR7102-WW | 100W, 240Vac, CRI≥85, 90° asymmetric, Alu/grey, 331x359x110 mm, 3000K, on/off | 600.00 | 77 |
| AR7102-NW | 100W, 240Vac, CRI≥85, 90° asymmetric, Alu/grey, 331x359x110 mm, 4000K, on/off | 600.00 | 77 |
| AR7150-WW | 150W, 240Vac, CRI≥85, 100°, Alu/grey, 315x391x186 mm, 3000K, on/off | 1'090.00 | 77 |
| AR7150-NW | 150W, 240Vac, CRI≥85, 100°, Alu/grey, 315x391x186 mm, 4000K, on/off | 1'090.00 | 77 |
| AR7200-WW | 200W, 240Vac, CRI≥85, 100°, Alu/grey, 345x415x186 mm, 3000K, on/off | 1'300.00 | 77 |
| AR7200-NW | 200W, 240Vac, CRI≥85, 100°, Alu/grey, 345x415x186 mm, 4000K, on/off | 1'300.00 | 77 |

VAL LED 50 / 100 / 150 / 200 Series • Modular In-/Outdoor Projectors • IP65

VAL LED is a high power modular LED projector, suitable for the most different applications both indoor and outdoor. Available as standard in 4000 K CRI>85 version, on request it is also available in 3000 K and 6000 K versions. The optical system is designed to be composed with the use of various optics, thus optimizing the light distribution as a function of the required results. The LED modules are individually adjustable and there is the possibility to include different optics in a single projector. The device is compatible with different control systems, ON/OFF and dimmable 0/1-10V.

| | | | |
|-------------|---|--------|----|
| AR2001-NW-A | 50W, 240Vac, CRI≥85, 15°, Alu/black, 270x149x271 mm, 4000K, on/off | 530.00 | 78 |
| AR2001-NW-B | 50W, 240Vac, CRI≥85, 30°, Alu/black, 270x149x271 mm, 4000K, on/off | 530.00 | 78 |
| AR2001-NW-C | 50W, 240Vac, CRI≥85, 60°, Alu/black, 270x149x271 mm, 4000K, on/off | 530.00 | 78 |
| AR2001-NW-D | 50W, 240Vac, CRI≥85, 110°, Alu/black, 270x149x271 mm, 4000K, on/off | 530.00 | 78 |
| AR2001-NW-E | 50W, 240Vac, CRI≥85, 135°x65°, Alu/black, 270x149x271 mm, 4000K, on/off | 530.00 | 78 |

VAL LED „DUO“ (2 x 50W)

| | | | |
|-------------|---|--------|----|
| AR2002-NW-A | 100W, 240Vac, CRI≥85, 15°, Alu/black, 262x235x274 mm, 4000K, on/off | 830.00 | 78 |
| AR2002-NW-B | 100W, 240Vac, CRI≥85, 30°, Alu/black, 262x235x274 mm, 4000K, on/off | 830.00 | 78 |
| AR2002-NW-C | 100W, 240Vac, CRI≥85, 60°, Alu/black, 262x235x274 mm, 4000K, on/off | 830.00 | 78 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|------------------------------------|--|----------|-------|
| AR2002-NW-D | 100W, 240Vac, CRI≥85, 110°, Alu/black, 262x235x274 mm, 4000K, on/off | 830.00 | 78 |
| AR2002-NW-E | 100W, 240Vac, CRI≥85, 135°x65°, Alu/black, 262x235x274 mm, 4000K, on/off | 830.00 | 78 |
| VAL LED „TRIO“ (3 x 50W) | | | |
| AR2003-NW-A | 150W, 240Vac, CRI≥85, 15°, Alu/black, 262x355x274 mm, 4000K, on/off | 990.00 | 78 |
| AR2003-NW-B | 100W, 240Vac, CRI≥85, 30°, Alu/black, 262x355x274 mm, 4000K, on/off | 990.00 | 78 |
| AR2003-NW-C | 150W, 240Vac, CRI≥85, 60°, Alu/black, 262x355x274 mm, 4000K, on/off | 990.00 | 78 |
| AR2003-NW-D | 150W, 240Vac, CRI≥85, 110°, Alu/black, 262x355x274 mm, 4000K, on/off | 990.00 | 78 |
| AR2003-NW-E | 150W, 240Vac, CRI≥85, 135°x65°, Alu/black, 262x355x274 mm, 4000K, on/off | 990.00 | 78 |
| VAL LED „QUATTRO“ (4 x 50W) | | | |
| AR2004-NW-A | 200W, 240Vac, CRI≥85, 15°, Alu/black, 235x483x274 mm, 4000K, on/off | 1'230.00 | 78 |
| AR2004-NW-B | 200W, 240Vac, CRI≥85, 30°, Alu/black, 235x483x274 mm, 4000K, on/off | 1'230.00 | 78 |
| AR2004-NW-C | 200W, 240Vac, CRI≥85, 60°, Alu/black, 235x483x274 mm, 4000K, on/off | 1'230.00 | 78 |
| AR2004-NW-D | 200W, 240Vac, CRI≥85, 110°, Alu/black, 235x483x274 mm, 4000K, on/off | 1'230.00 | 78 |
| AR2004-NW-E | 200W, 240Vac, CRI≥85, 135°x65°, Alu/black, 235x483x274 mm, 4000K, on/off | 1'230.00 | 78 |

MEGA VAL LED 400 & 1000 Series · Modular In-/Outdoor Projectors · IP65

Modular LED luminaire that is the ideal replacement for traditional lamps that produce an output of over 2000W. The unit fits both outdoor and indoor settings such as sport stadiums, football fields, golf courses, racetracks, and so on. It is also optimal for settings such as loading and unloading areas, parking lots, port and rail storage and ice arenas. The unit's optics produce a uniform and powerful luminous flux suitable for a wide range of applications.

| | | | |
|-------------|---|----------|----|
| AR2014-NW-A | 400W, 240Vac, CRI≥80, 10°, Steel/Alu/grey, 419x221x270 mm, 4000K, on/off | 3'490.00 | 79 |
| AR2014-NW-B | 400W, 240Vac, CRI≥80, 30°, Steel/Alu/grey, 419x221x270 mm, 4000K, on/off | 3'490.00 | 79 |
| AR2014-NW-C | 400W, 240Vac, CRI≥80, 60°, Steel/Alu/grey, 419x221x270 mm, 4000K, on/off | 3'490.00 | 79 |
| AR2014-NW-D | 400W, 240Vac, CRI≥80, 120°, Steel/Alu/grey, 419x221x270 mm, 4000K, on/off | 3'490.00 | 79 |
| AR2016-NW-A | 1'000W, 240Vac, CRI≥80, 10°, Steel/Alu/grey, 600x340x225 mm, 4000K, on/off | 8'550.00 | 79 |
| AR2016-NW-B | 1'000W, 240Vac, CRI≥80, 30°, Steel/Alu/grey, 419x221x270 mm, 4000K, on/off | 8'550.00 | 79 |
| AR2016-NW-C | 1'000W, 240Vac, CRI≥80, 60°, Steel/Alu/grey, 419x221x270 mm, 4000K, on/off | 8'550.00 | 79 |
| AR2016-NW-D | 1'000W, 240Vac, CRI≥80, 120°, Steel/Alu/grey, 419x221x270 mm, 4000K, on/off | 8'550.00 | 79 |

TOWN BEAM LED 250 & 400 Series · Outdoor Beam Projectors · IP65

LED Illuminator with **super narrow optics**, the powerful beam of only 2.5°/4.5° remains uniform up to 200 meters away. The body is composed of a cast alloy of aluminum and magnesium with excellent characteristics for both the mechanical strength and heat dissipation. The weight is limited to only 17kg. Controllable with standard DMX512 (-RGBW), the logarithmic dimmer enables the proportional maintenance of colour preset. Ideal for architectural lighting of buildings, monuments, bridges, also excellent for use as a long-throw pointer.

| | | | |
|-------------|---|-----------|----|
| TC0066-NW | 250W, 240Vac, CRI≥80, 2.5°-4.5° , Alu/white, 734x394x121 mm, 4000K, on/off | 4'990.00 | 80 |
| TC0066-RGBW | 250W, 240Vac, CRI≥80, 2.5°-4.5° , Alu/white, 734x394x121 mm, RGBW, DMX | 6'930.00 | 80 |
| TC0132-NW | 400W, 240Vac, CRI≥80, 2.5°-4.5° , Alu/white, 782x707x260 mm, 4000K, on/off | 9'500.00 | 80 |
| TC0132-RGBW | 400W, 240Vac, CRI≥80, 2.5°-4.5° , Alu/white, 734x394x121 mm, RGBW, DMX | 14'220.00 | 80 |



| | | | |
|---------|-------------|----------|-------|
| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|

LEDA LED Series • Outdoor Bollard Light • IP65

Floor outdoor LED luminaire fitted with aluminum body, **adjustable head** ($\pm 20^\circ$) and downwards light output. This makes it the ideal unit to light up gardens and walkways.

| | | | |
|------------|--|--------|----|
| ARP0020-WW | 20W, 230Vac, CRI \geq 80, 35°, Alu/dark grey, 900x270x45 mm, 3000K, on/off | 435.00 | 82 |
| ARP0020-W | 20W, 230Vac, CRI \geq 80, 35°, Alu/dark grey, 900x270x45 mm, 6000K, on/off | 435.00 | 82 |

FERRET LED Series • Outdoor Bollard Light • IP65

Outdoor floor LED stand light fitted with aluminum body flat on the back with downward light output. Its shape makes it the ideal unit both for wall installations and for gardens and walkways.

| | | | |
|------------|--|--------|----|
| ARP0010-WW | 10W, 230Vac, CRI \geq 80, 50°, Alu/dark grey, 400x100x50 mm, 3000K, on/off | 175.00 | 82 |
| ARP0010-W | 10W, 230Vac, CRI \geq 80, 50°, Alu/dark grey, 400x100x50 mm, 6000K, on/off | 175.00 | 82 |

GARDEN LED Series • Outdoor Bollard Light • IP65

Floor Outdoor LED stand light, aluminum body + PMMA. Circular light emission. Ideal for lighting paths and gardens. Available in two versions: 485mm and 785mm. Interchangeable lamp.

785 mm high

| | | | |
|------------|--|--------|----|
| ARP0001-WW | 7W, 230Vac, CRI \geq 80, 360°, Alu/grey, 785x60Ø mm, 3000K, on/off | 460.00 | 82 |
| ARP0001-W | 7W, 230Vac, CRI \geq 80, 360°, Alu/grey, 785x60Ø mm, 6000K, on/off | 460.00 | 82 |

485 mm high

| | | | |
|------------|--|--------|----|
| ARP0002-WW | 7W, 230Vac, CRI \geq 80, 360°, Alu/grey, 485x60Ø mm, 3000K, on/off | 430.00 | 82 |
| ARP0002-W | 7W, 230Vac, CRI \geq 80, 360°, Alu/grey, 485x60Ø mm, 6000K, on/off | 430.00 | 82 |

DELTA LED 60 & 90 Series • STREET LAMPS • IP65

LED street lighting with adjustable jointed arm, suitable for top pole installation and also for horizontal installation. Modern design and high efficiency of LED technology make it ideal for street lighting, cycle paths, parking lots and green areas. The advanced system for the management of thermal dissipation helps to maintain a luminous flux unparalleled. The powder coating and the anti-corrosion treatment guarantee a good durability.

| | | | |
|------------|--|--------|----|
| LST5061-NW | 63W, 100-277Vac, CRI \geq 80, 140° x 60° , Alu/grey, 437x280x62 mm, 4000K, on/off | 660.00 | 83 |
| LST5091-NW | 93W, 100-277Vac, CRI \geq 80, 140° x 60° , Alu/grey, 437x280x62 mm, 4000K, on/off | 660.00 | 83 |



ARTIKEL

BEZEICHNUNG

VP (CHF) Seite

STRADA LED Series • STREET LAMPS • IP65

STRADA LED is an innovative street lighting appliance. Body: Die-cast aluminum and designed with a windproof surface. The cooling fins are integrated. Available in four different options:

- Mobile joint for top pole mounting or pastoral pole with 60mm diameter
- Side connection for round poles
- Side connection for square poles
- Adjustable fork for wall mounting

Optics: In PMMA, highly resistant to temperature and UV radiation.

Resistant to mechanical shocks and thermal shocks (UNI-EN 12150-1:2001).

Finishing: Scratch-resistant and weather-resistant powder coating

Built-in automatic temperature control with automatic reset

Manufactured according to EN60598-1, CEI 34-21

Degree of protection IP65 compliant with EN 60529

The modern design, the modular system together to the high efficiency of LED technology, make it ideal for street lighting, bike lanes, parkings and green areas.

STRADA 70

| | | | |
|------------|--|--------|----|
| LST3075-NW | 70W, 100-260Vac, CRI≥80, 140°x70°, Alu/grey, 290x231/430 mm, 4000K, on/off | 580.00 | 84 |
|------------|--|--------|----|

STRADA 120

| | | | |
|------------|---|--------|----|
| LST3120-NW | 120W, 100-260Vac, CRI≥80, 140°x70°, Alu/grey, 290x337/536 mm, 4000K, on/off | 840.00 | 84 |
|------------|---|--------|----|

STRADA 150

| | | | |
|------------|---|--------|----|
| LST3150-NW | 150W, 100-260Vac, CRI≥80, 140°x70°, Alu/grey, 290x337/536 mm, 4000K, on/off | 870.00 | 84 |
|------------|---|--------|----|

STRADA 240

| | | | |
|------------|---|----------|----|
| LST3240-NW | 240W, 100-260Vac, CRI≥80, 140°x70°, Alu/grey, 346x540/740 mm, 4000K, on/off | 1'420.00 | 85 |
|------------|---|----------|----|

STRADA 300

| | | | |
|------------|---|----------|----|
| LST3300-NW | 300W, 100-260Vac, CRI≥80, 140°x70°, Alu/grey, 346x540/740 mm, 4000K, on/off | 1'560.00 | 85 |
|------------|---|----------|----|

JUPITER 2 LED Series • High Power Industrial Lights (in- & outdoor) • IP65

Jupiter-2 is a 1-10V dimmable LED projector equipped with an integrated and interchangeable mean well driver. The LEDs are Philips 3030. Optic with anti-condensation system that guarantees a powerful and uniform light output, constant over time. Equipped with suspension hook. The pure aluminum body ensures efficient dissipation and does not require forced ventilation for cooling. Thanks to its IP65 protection rating, it is ideal for any installation both indoors and outdoors, such as loading / unloading warehouses and production areas. It is perfect in all situations that require diffused and comfortable lighting from above. Color temperature 4000 K, on request also 3000 K and 6000 K. Standard 90° optics, available on request also 60° and 120°.

JUPITER 2 DIM 200W

| | | | |
|------------|--|--------|----|
| AR4202V-NW | 200W, 100-277Vac, CRI≥80, 90°, Alu/black, Ø 340 x 135/180mm, 4000K, 1-10V DIM or on/off | 790.00 | 86 |
| AR4203V-NW | 200W, 100-277Vac, CRI≥80, 120°, Alu/black, Ø 340 x 135/180mm, 4000K, 1-10V DIM or on/off | 790.00 | 86 |
| AR4204V-NW | 200W, 100-277Vac, CRI≥80, 60°, Alu/black, Ø 340 x 135/180mm, 4000K, 1-10V DIM or on/off | 790.00 | 86 |

JUPITER 2 DIM 150W

| | | | |
|------------|--|--------|----|
| AR4152V-NW | 150W, 100-277Vac, CRI≥80, 90°, Alu/black, Ø 340 x 135/180mm, 4000K, 1-10V DIM or on/off | 600.00 | 87 |
| AR4153V-NW | 150W, 100-277Vac, CRI≥80, 120°, Alu/black, Ø 340 x 135/180mm, 4000K, 1-10V DIM or on/off | 600.00 | 87 |
| AR4154V-NW | 150W, 100-277Vac, CRI≥80, 60°, Alu/black, Ø 340 x 135/180mm, 4000K, 1-10V DIM or on/off | 600.00 | 87 |

JUPITER 2 DIM 100W

| | | | |
|------------|---|--------|----|
| AR4102V-NW | 100W, 100-277Vac, CRI≥80, 90°, Alu/black, Ø 290 x 125/170mm, 4000K, 1-10V DIM or on/off | 460.00 | 87 |
|------------|---|--------|----|



ARCHITECTURAL LIGHTING CATALOGUE

Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|------------|--|----------|-------|
| AR4103V-NW | 100W, 100-277Vac, CRI≥80, 120°, Alu/black, Ø 290 x 125/170mm, 4000K, 1-10V DIM or on/off | 460.00 | 87 |
| AR4104V-NW | 100W, 100-277Vac, CRI≥80, 60°, Alu/black, Ø 290 x 125/170mm, 4000K, 1-10V DIM or on/off | 460.00 | 87 |

ROUND LED Series • High Power Industrial Lights (in- & outdoor) • IP65

Round is an LED light engine (Hi-Bay) equipped with hanging system and bracket for feeling installation. The fixture is IP65. The dye cast aluminum body allows the proper dissipation and do not require forced ventilation, ideal for any installation environment inside and outside, such as warehouses, production areas, areas for loading and unloading and in any environment where it is needed diffused lighting from above.

ROUND 100

| | | | |
|-----------|---|--------|----|
| AR9100-NW | 100W, 100-240Vac, CRI≥80, 120° (optional 60°), Alu/grey, Ø 340 x 133mm, 4000K, on/off | 690.00 | 88 |
|-----------|---|--------|----|

ROUND 150

| | | | |
|-----------|---|--------|----|
| AR9150-NW | 150W, 100-240Vac, CRI≥80, 120° (optional 60°), Alu/grey, Ø 430 x 139mm, 4000K, on/off | 880.00 | 88 |
|-----------|---|--------|----|

ROUND 200

| | | | |
|-----------|---|----------|----|
| AR9200-NW | 200W, 100-240Vac, CRI≥80, 120° (optional 60°), Alu/grey, Ø 520 x 140mm, 4000K, on/off | 1'150.00 | 88 |
|-----------|---|----------|----|

ROUND 240

| | | | |
|-----------|---|----------|----|
| AR9240-NW | 240W, 100-240Vac, CRI≥80, 120° (optional 60°), Alu/grey, Ø 520 x 140mm, 4000K, on/off | 1'390.00 | 88 |
|-----------|---|----------|----|

ALU-PLUS LED Series • Watertight Industrial Lights (in- & outdoor) • IP66

ALU-PLUS is a watertight ceiling lamp with integrated LEDs and 140° optics. Suitable for application in the most varied installations, civil, industrial, commercial, underground parking and common areas. The IP65 degree of protection makes it suitable both indoors and outdoors. Die-cast aluminum body and anti-glare cover in polycarbonate, unbreakable and self-extinguishing, of high mechanical resistance thanks to the structure reinforced by mini internal ribs that also help the uniform distribution of the light emitted. The smooth external finish facilitates the cleaning operation, necessary to always have the maximum luminous efficiency. The 90Vac up to 265Vac power supply ensures constant light even during power surges. Equipped with quick connectors for electrical connection both inlet and outlet 2P + T. The same ceiling lamps are also available on request with an integrated emergency kit with a 2-hour ignition duration in the absence of mains power.

60 cm

| | | | |
|------------|--|--------|----|
| PSL0621-NW | 20W, 200-240Vac, CRI≥80, 140°, Alu/grey, 600x93x87 mm, 4000K, on/off | 190.00 | 90 |
| PSL0631-NW | 30W, 200-240Vac, CRI≥80, 140°, Alu/grey, 600x93x87 mm, 4000K, on/off | 200.00 | 90 |

120 cm

| | | | |
|-------------|---|--------|----|
| PSL1241-NW | 40W, 200-240Vac, CRI≥80, 140°, Alu/grey, 1200x93x87 mm, 4000K, on/off | 305.00 | 90 |
| PSL1251-NW | 50W, 200-240Vac, CRI≥80, 140°, Alu/grey, 1200x93x87 mm, 4000K, on/off | 335.00 | 90 |
| PSLE1251-NW | 50W, 200-240Vac, CRI≥80, 140°, Alu/grey, 1200x93x87 mm, 4000K, on/off, emergency kit 2h | 510.00 | 90 |

150 cm

| | | | |
|-------------|---|--------|----|
| PSL1551-NW | 50W, 200-240Vac, CRI≥80, 140°, Alu/grey, 1500x93x87 mm, 4000K, on/off | 380.00 | 90 |
| PSL1561-NW | 60W, 200-240Vac, CRI≥80, 140°, Alu/grey, 1500x93x87 mm, 4000K, on/off | 390.00 | 90 |
| PSL1581-NW | 80W, 200-240Vac, CRI≥80, 140°, Alu/grey, 1500x93x87 mm, 4000K, on/off | 460.00 | 90 |
| PSLE1561-NW | 60W, 200-240Vac, CRI≥80, 140°, Alu/grey, 1500x93x87 mm, 4000K, on/off, emergency kit 2h | 600.00 | 90 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|
|---------|-------------|----------|-------|

FENIKS LED Series • Industrial Lights (in- & outdoor) • IP65

IP65 ceiling light with integrated LEDs and 110° optics. Ideal for application in the most varied civil, industrial and commercial installations, but also for underground car parks and common areas. Shatterproof and self-extinguishing polycarbonate body with high mechanical resistance thanks to the reinforced structure. The opal diffuser guarantees functional, comfortable and uniform lighting, avoiding glare. The smooth external finish facilitates the cleaning operations necessary to ensure maximum brightness efficiency. Also available in the version with integrated emergency kit.

60 cm

| | | | |
|--------------|--|--------|----|
| PSL30620-NW | 20W, 220-240Vac, CRI≥80, 110°, Alu/grey, 600x80x64 mm, 4000K, on/off | 80.00 | g1 |
| PSLE30620-NW | 20W, 220-240Vac, CRI≥80, 110°, Alu/grey, 600x80x64 mm, 4000K, on/off, emergency kit 2hr. | 160.00 | g1 |
| PSLE30620-W | 20W, 220-240Vac, CRI≥80, 100°, Alu/grey, 600x80x64 mm, 5000K, on/off, emergency kit 2hr | 160.00 | g1 |

120 cm

| | | | |
|--------------|--|--------|----|
| PSL31240-NW | 40W, 220-240Vac, CRI≥80, 110°, Alu/grey, 1198x80x64 mm, 4000K, on/off | 130.00 | 91 |
| PSLE31235-NW | 35W, 220-240Vac, CRI≥80, 110°, Alu/grey, 1198x80x64 mm, 4000K, on/off, emergency kit 2hr | 200.00 | 91 |
| PSLE31235-W | 35W, 220-240Vac, CRI≥80, 100°, Alu/grey, 1198x80x64 mm, 5000K, on/off, emergency kit 2hr | 200.00 | 91 |

150 cm

| | | | |
|--------------|--|--------|----|
| PSL31560-NW | 60W, 220-240Vac, CRI≥80, 110°, Alu/grey, 1198x80x64 mm, 4000K, on/off | 180.00 | 91 |
| PSLE31551-NW | 51W, 220-240Vac, CRI≥80, 110°, Alu/grey, 1198x80x64 mm, 4000K, on/off, emergency kit 2hr | 250.00 | 91 |
| PSLE31551-W | 51W, 220-240Vac, CRI≥80, 100°, Alu/grey, 1198x80x64 mm, 5000K, on/off, emergency kit 2hr | 250.00 | 91 |

ARROW SYSTEM LED Series · for Food & Product Displays with high CRI (≥ 95)

Arrow LED is an innovative modular bar system dedicated to illuminate products placed on shelves, counters and display fridges. The product covers the full range of professional lighting to aimed at improving color brilliance for goods on display. In addition to the four sizes that allow modular composition in order to obtain the desired length, the unit comes equipped with swiveling mounting brackets for light beam trajectory optimization. The maximum length of the array is 8 meters in total with power supply input only from one side. **Comes without power supply!**

30 cm

| | | | |
|-------------|---|-------|----|
| BAR0005-GWW | 5W, 24Vdc, CRI≥95, 120°, Alu/silver, 260x20x16 mm, 3000K (warm white, natural gold) | 30.00 | 92 |
| BAR0005-NW | 5W, 24Vdc, CRI≥95, 120°, Alu/silver, 260x20x16 mm, 4000K (natural white) | 30.00 | 92 |
| BAR0005-DW | 5W, 24Vdc, CRI≥95, 120°, Alu/silver, 260x20x16 mm, 6000K (natural daylight) | 30.00 | 92 |
| BAR0005-R | 5W, 24Vdc, CRI≥95, 120°, Alu/silver, 260x20x16 mm, natural pink (for food display) | 30.00 | 93 |

60 cm

| | | | |
|--------------|--|-------|----|
| BAR0010-GW/W | 10W, 24Vdc, CRI≥95, 120°, Alu/silver, 560x20x16 mm, 3000K (warm white, natural gold) | 47.00 | 92 |
| BAR0010-NW | 10W, 24Vdc, CRI≥95, 120°, Alu/silver, 560x20x16 mm, 4000K (natural white) | 47.00 | 92 |
| BAR0010-DW | 10W, 24Vdc, CRI≥95, 120°, Alu/silver, 560x20x16 mm, 6000K (natural daylight) | 47.00 | 92 |
| BAR0010-R | 10W, 24Vdc, CRI≥95, 120°, Alu/silver, 560x20x16 mm, natural pink (for food display) | 47.00 | 93 |

90 cm

| | | | |
|--------------|---|-------|----|
| BAR0015-GW/W | 15W, 24Vdc, CRI≥95, 120°. Alu./silver, 860x20x16 mm, 3000K (warm white, natural gold) | 73.00 | 92 |
| BAR0015-NW | 15W, 24Vdc, CRI≥95, 120°. Alu./silver, 860x20x16 mm, 4000K (natural white) | 73.00 | 92 |
| BAR0015-DW | 15W, 24Vdc, CRI≥95, 120°. Alu./silver, 860x20x16 mm, 6000K (natural daylight) | 73.00 | 92 |
| BAR0015-R | 15W, 24Vdc, CRI≥95, 120°. Alu./silver, 860x20x16 mm, natural pink (for food display) | 73.00 | 93 |

120 cm

| | | | |
|-------------|--|-------|----|
| BAR0020-GWW | 20W, 24Vdc, CRI≥95, 120°, Alu./silver, 1160x20x16 mm, 3000K (warm white, natural gold) | 85.00 | 92 |
| BAR0020-NW | 20W, 24Vdc, CRI≥95, 120°, Alu./silver, 1160x20x16 mm, 4000K (natural white) | 85.00 | 92 |
| BAR0020-DW | 20W, 24Vdc, CRI≥95, 120°, Alu./silver, 1160x20x16 mm, 6000K (natural daylight) | 85.00 | 92 |



ARCHITECTURAL LIGHTING CATALOGUE

Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|-----------|--|----------|-------|
| BAR0020-R | 20W, 24Vdc, CRI≥95, 120°, Alu/silver, 1160x20x16 mm, natural pink (for food display) | 85.00 | 93 |

T8 LED Series • Natural Food Light

Arena Luci presents its new T8 LED tubes range, which is dedicated to the illumination of displayed foodstuffs. These products are the result of accurate lighting engineering research, and are specifically designed to augment the visual appearance of food on display. Research shows that we judge a product's quality by looking at its appearance, therefore, exalting food freshness and appearance is crucial to captivate customers during their shopping experience. Arena Luci makes available a wide range of T8 LED tubes that are the ideal for butcher shops, bakers, food retailers and supermarkets. These products thanks to their specific luminous spectrum and the lack of UV and IR rays, increase cost-efficiency, as cooling systems work less.

| | | | |
|-----------|--|--------|----|
| LLF0611-R | 11W, 220-240Vac, 120°, Alu/white, (60cm) 588 x Ø26mm, G13, natural pink (for food display) | 107.00 | 93 |
| LLF0916-R | 17W, 220-240Vac, 120°, Alu/white, (90cm) 894 x Ø26mm, G13, natural pink (for food display) | 125.00 | 93 |
| LLF1220-R | 20W, 220-240Vac, 120°, Alu/white, (120cm) 1198 x Ø26mm, G13, natural pink (for food display) | 147.00 | 93 |
| LLF1524-R | 24W, 220-240Vac, 120°, Alu/white, (150cm) 1498 x Ø26mm, G13, natural pink (for food display) | 175.00 | 93 |

HL STRIP Series • LED Strip with high CRI (≥ 90)

HL is the new series of LED strips 24V obtained from the experience of Arena Luci. This innovative technology has made it possible to achieve very high luminous fluxes **with a high color rendering index CRI>90**, something that was unthinkable until recently. There are four color temperatures, 2700K, 3000K, 4000K and 6000K, for all possible uses. A wide range of power supplies is available with different sizes and dimming controls such as: push-button or rotary dimmer, 0-10V dimmer, DALI dimmer and DMX dimmer. Indispensable for the installation, our aluminum profiles complete with opals, semi-opals and transparent covers.

42W/m • max. continuous connection: 3m • comes with 3M adhesive tape integrated

| | | | |
|------------|--|--------|----|
| LS3042-RWW | 129W @ 3m, 24Vdc, CRI≥90, 2700K, 240 LEDs/m, width: 12mm, price for 3m | 390.00 | 94 |
| LS3042-WWW | 129W @ 3m, 24Vdc, CRI≥90, 3000K, 240 LEDs/m, width: 12mm, price for 3m | 390.00 | 94 |
| LS3042-NWW | 129W @ 3m, 24Vdc, CRI≥90, 4000K, 240 LEDs/m, width: 12mm, price for 3m | 390.00 | 94 |
| LS3042-W | 129W @ 3m, 24Vdc, CRI≥90, 6000K, 240 LEDs/m, width: 12mm, price for 3m | 390.00 | 94 |

20W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated

| | | | |
|------------|--|--------|----|
| LS3025-RWW | 100W @ 5m, 24Vdc, CRI≥90, 2700K, 240 LEDs/m, width: 10mm, price for 5m | 185.00 | 94 |
| LS3025-WWW | 100W @ 5m, 24Vdc, CRI≥90, 3000K, 240 LEDs/m, width: 10mm, price for 5m | 185.00 | 94 |
| LS3025-NWW | 100W @ 5m, 24Vdc, CRI≥90, 4000K, 240 LEDs/m, width: 10mm, price for 5m | 185.00 | 94 |
| LS3025-W | 100W @ 5m, 24Vdc, CRI≥90, 6000K, 240 LEDs/m, width: 10mm, price for 5m | 185.00 | 94 |

9,6W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated

| | | | |
|------------|--|--------|----|
| LS3009-RWW | 48W @ 5m, 24Vdc, CRI≥90, 2700K, 240 LEDs/m, width: 9mm, price for 5m | 102.00 | 94 |
| LS3009-WWW | 48W @ 5m, 24Vdc, CRI≥90, 3000K, 240 LEDs/m, width: 9mm, price for 5m | 102.00 | 94 |
| LS3009-NWW | 48W @ 5m, 24Vdc, CRI≥90, 4000K, 240 LEDs/m, width: 9mm, price for 5m | 102.00 | 94 |
| LS3009-W | 48W @ 5m, 24Vdc, CRI≥90, 6000K, 240 LEDs/m, width: 9mm, price for 5m | 102.00 | 94 |

HP-2 STRIP Series • LED Strip with very high efficiency

HP-2 is the new series of LED strips, obtained from the experience of Arena Luci. This innovated technology has enabled us to achieve a luminous flux LED, something unthinkable a short time ago. There is a wide range of power supplies with different sizes and dimming controls such as button or rotary dimmer, 0-10V dimmer, DALI dimmer and DMX dimmer. Necessary for the installations are our aluminum profiles complete with covers: opals, semi-opals and transparent.

23W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated

| | | | |
|------------|--|--------|----|
| LS2923-WWW | 115W @ 5m, 24Vdc, CRI≥80, 3000K, 120 LEDs/m, width: 10mm, price for 5m | 153.00 | 95 |
| LS2923-NWW | 115W @ 5m, 24Vdc, CRI≥80, 4000K, 120 LEDs/m, width: 10mm, price for 5m | 153.00 | 95 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|------------|--|----------|-------|
| LS2923-W | 115W @ 5m, 24Vdc, CRI≥80, 6000K, 120 LEDs/m, width: 10mm, price for 5m | 153.00 | 95 |
| | 16W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated | | |
| LS2916-WW | 80W @ 5m, 24Vdc, CRI≥80, 3000K, 84 LEDs/m, width: 10mm, price for 5m | 120.00 | 95 |
| LS2916-NW | 80W @ 5m, 24Vdc, CRI≥80, 4000K, 84 LEDs/m, width: 10mm, price for 5m | 120.00 | 95 |
| LS2916-W | 80W @ 5m, 24Vdc, CRI≥80, 6000K, 84 LEDs/m, width: 10mm, price for 5m | 120.00 | 95 |
| | 12W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated | | |
| LS2912-WW | 60W @ 5m, 24Vdc, CRI≥80, 3000K, 60 LEDs/m, width: 10mm, price for 5m | 98.00 | 95 |
| LS2912-NW | 60W @ 5m, 24Vdc, CRI≥80, 4000K, 60 LEDs/m, width: 10mm, price for 5m | 98.00 | 95 |
| LS2912-W | 60W @ 5m, 24Vdc, CRI≥80, 6000K, 60 LEDs/m, width: 10mm, price for 5m | 98.00 | 95 |
| LS2912-RGB | 60W @ 5m, 24Vdc, CRI≥80, RGB Full Color, 60 LEDs/m, width: 10mm, price for 5m | 160.00 | 95 |

HP-2 IP STRIP Series • LED Strip with very high efficiency • IP65

HP-2 IP has the same features like „HP-2“, but comes with transparent sheath for IP65 certification.

| | | | |
|------------|--|--------|----|
| | 16W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated | | |
| LS2816-WW | 80W @ 5m, 24Vdc, CRI≥80, 3000K, 84 LEDs/m, width: 15mm, price for 5m | 160.00 | 95 |
| LS2816-NW | 80W @ 5m, 24Vdc, CRI≥80, 4000K, 84 LEDs/m, width: 15mm, price for 5m | 160.00 | 95 |
| LS2816-W | 80W @ 5m, 24Vdc, CRI≥80, 6000K, 84 LEDs/m, width: 15mm, price for 5m | 160.00 | 95 |
| | 12W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated | | |
| LS2812-WW | 60W @ 5m, 24Vdc, CRI≥80, 3000K, 60 LEDs/m, width: 15mm, price for 5m | 149.00 | 95 |
| LS2812-NW | 60W @ 5m, 24Vdc, CRI≥80, 4000K, 60 LEDs/m, width: 15mm, price for 5m | 149.00 | 95 |
| LS2812-W | 60W @ 5m, 24Vdc, CRI≥80, 6000K, 60 LEDs/m, width: 15mm, price for 5m | 149.00 | 95 |
| LS2812-RGB | 60W @ 5m, 24Vdc, CRI≥80, RGB Full Color, 60 LEDs/m, width: 10mm, price for 5m | 185.00 | 95 |

VERY HIGH BRIGHTNESS STRIP Series • LED Strip with very high brightness

The high brightness strip 24Vdc is suitable for application in indoor environments where there is the need for a high brightness. The possibility of a minimum cutting size of 2.94 cm, make this type of LED Strip very dynamic for any type of application. Exclusive installation on dissipating extruded aluminium bar.

| | | | |
|-----------|--|--------|----|
| | 25W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated | | |
| LS1900-WW | 125W @ 5m, 24Vdc, CRI≥80, 3000K, 204 LEDs/m, width: 10mm, price for 5m | 420.00 | 96 |
| LS1900-NW | 125W @ 5m, 24Vdc, CRI≥80, 4000K, 204 LEDs/m, width: 10mm, price for 5m | 420.00 | 96 |
| LS1900-W | 125W @ 5m, 24Vdc, CRI≥80, 6000K, 204 LEDs/m, width: 10mm, price for 5m | 420.00 | 96 |

DOUBLE STRIP Series • LED Strip for long distances without feeding point (up to 15m!)

Innovative flexible LED strip with double row, high brightness LED chips. The LED strip can be connected up to 15 meters in a single line. Suitable for indoor applications where high brightness and long LED strip line without any interruptions are requested. This type of LED strip is dynamic and suitable for multiple applications.

| | | | |
|-----------|---|--------|----|
| | 16W/m • max. continuous connection: 15m • comes with 3M adhesive tape integrated | | |
| LS2016-WW | 240W @ 15m, 36Vdc , CRI≥80, 3000K, 120 LEDs/m, width: 15mm, price for 15m | 527.00 | 96 |
| LS2016-NW | 240W @ 15m, 36Vdc , CRI≥80, 4000K, 120 LEDs/m, width: 15mm, price for 15m | 527.00 | 96 |
| LS2016-W | 240W @ 15m, 36Vdc , CRI≥80, 6000K, 120 LEDs/m, width: 15mm, price for 15m | 527.00 | 96 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|-------------|----------|-------|
|---------|-------------|----------|-------|

RGBW STRIP • LED Strip to colouring and whitening environments

RGBW Strip is an innovative flexible light strip with SMD LED RGBW 4-in-1 chip technology.

19,2W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated

| | | | |
|-------------|--|--------|----|
| LS2992-RGBW | 92W @ 5m, 24Vdc, CRI≥80, RGBW Full Color, 60 LEDs/m, width: 10mm, price for 5m | 240.00 | 97 |
|-------------|--|--------|----|

HIGH BRIGHTNESS STRIP Series • 12V LED Strip with high brightness

The high light strip IP20 is suitable for indoor (IP20) and outdoor (IP65) application where high brightness is needed, the low power guarantees performance and warranties in addition all the other strip.

15W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated • IP20

| | | | |
|-----------|---|--------|----|
| LS1532-WW | 75W @ 5m, 12Vdc , CRI≥80, 3200K, 120 LEDs/m, width: 10mm, price for 5m | 235.00 | 97 |
| LS1532-W | 75W @ 5m, 12Vdc , CRI≥80, 6000K, 120 LEDs/m, width: 10mm, price for 5m | 235.00 | 97 |

15W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated • IP65

| | | | |
|-----------|---|--------|----|
| LS1558-WW | 75W @ 5m, 12Vdc , CRI≥80, 3200K, 120 LEDs/m, width: 10mm, price for 5m | 305.00 | 97 |
| LS1558-W | 75W @ 5m, 12Vdc , CRI≥80, 6000K, 120 LEDs/m, width: 10mm, price for 5m | 305.00 | 97 |

STANDARD STRIP • LED Strip single colour, warm white & cool white • IP65

The LED strip IP65 ARENA LUCI is suitable for indoor and outdoor installation It is recommended during the installation to meet the corner minimum bending (10 cm) to avoid damaging the product.

6W/m • max. continuous connection: 5m • comes with 3M adhesive tape integrated

| | | | |
|----------|---|--------|----|
| LS1550 | 30W @ 5m, 12Vdc , CRI≥80, red , 60 LEDs/m, width: 11mm, price for 5m | 169.00 | 98 |
| LS1551 | 30W @ 5m, 12Vdc , CRI≥80, yellow , 60 LEDs/m, width: 11mm, price for 5m | 169.00 | 98 |
| LS1552 | 30W @ 5m, 12Vdc , CRI≥80, blue , 60 LEDs/m, width: 11mm, price for 5m | 169.00 | 98 |
| LS1553 | 30W @ 5m, 12Vdc , CRI≥80, green , 60 LEDs/m, width: 11mm, price for 5m | 169.00 | 98 |
| LS1554/S | 30W @ 5m, 12Vdc , CRI≥80, 6000K , 60 LEDs/m, width: 11mm, price for 5m | 150.00 | 98 |
| LS1555/S | 30W @ 5m, 12Vdc , CRI≥80, 3200K , 60 LEDs/m, width: 11mm, price for 5m | 140.00 | 98 |

STANDARD STRIP • LED Strip • IP20

The standard LED strip IP20 is suitable for indoor environments where a bright accent light is needed, low power consumption makes this product unbeatable.

6W/m • 12Vdc • max. continuous connection: 5m • comes with adhesive tape integrated

| | | | |
|---------------|---|--------|----|
| LS1525/S-2700 | 30W @ 5m, 12Vdc , CRI≥80, 2700K, 60 LEDs/m, width: 8mm, price for 5m | 115.00 | 98 |
| LS1525/S | 30W @ 5m, 12Vdc , CRI≥80, 3200K, 60 LEDs/m, width: 8mm, price for 5m | 115.00 | 98 |
| LS1524/S | 30W @ 5m, 12Vdc , CRI≥80, 6000K, 60 LEDs/m, width: 8mm, price for 5m | 115.00 | 98 |

6W/m • 24Vdc • max. continuous connection: 5m • comes with adhesive tape integrated

| | | | |
|-----------|---|--------|----|
| LS1515-WW | 30W @ 5m, 24Vdc , CRI≥80, 3000K, 60 LEDs/m, width: 8mm, price for 5m | 115.00 | 98 |
| LS1515-NW | 30W @ 5m, 24Vdc , CRI≥80, 4000K, 60 LEDs/m, width: 8mm, price for 5m | 115.00 | 98 |



ARTIKEL BEZEICHNUNG VP (CHF) Seite

SUPER FLEX NEON LED • PVC cast-in LED Strip • IP66

The flexible LED tube consists of an extruded plastic tube with a series of LEDs inside. The flexible LED tube is available in both single color or RGB versions. The flexible LED tube is powered with 24Vdc, this along with a complete set of accessories, such as power cable, power transformer, connectors, clips and ducts for wall mounting, can satisfy any installation requirements.

14,4W/m • 24Vdc • max. continuous connection: 20m / 15m (RGB-Version)

| | | | |
|------------|---|--------|----|
| FX1224-WW | 72W @ 5m, 24Vdc, 3000K, every 10 cm can be cut to length, width: 22mm, price for 1m | 115.00 | 98 |
| FX1224-W | 72W @ 5m, 24Vdc, 6000K, every 10 cm can be cut to length, width: 22mm, price for 1m | 115.00 | 98 |
| FX1224-RGB | 72W @ 5m, 24Vdc, RGB Full C., every 10 cm can be cut to length, width: 22mm, price for 1m | 115.00 | 98 |
| FX1224-B | 72W @ 5m, 24Vdc, blue, every 10 cm can be cut to length, width: 22mm, price for 1m | 120.00 | 98 |
| FX1224-G | 72W @ 5m, 24Vdc, green, every 10 cm can be cut to length, width: 22mm, price for 1m | 120.00 | 98 |
| FX1224-R | 72W @ 5m, 24Vdc, red, every 10 cm can be cut to length, width: 22mm, price for 1m | 120.00 | 98 |
| FX1224-Y | 72W @ 5m, 24Vdc, yellow, every 10 cm can be cut to length, width: 22mm, price for 1m | 120.00 | 98 |

Accessories

| | | | |
|---------|--|-------|----|
| PR5524 | Connecting cable, 1m, for single color or white | 41.00 | 98 |
| PR5525 | Connecting cable, 1m, for RGB | 41.00 | 98 |
| PR1535 | End Cup | 2.00 | 98 |
| PR1538F | Waterproof gasket (silicon) for end cup and connector | 2.00 | 98 |
| PR1539F | Inner lock clip for end cup and connector | 2.00 | 98 |
| PR1540F | Outer lock clip for end cup and connector | 7.80 | 98 |
| PR1541F | External install screws for end cup and connector | 2.00 | 98 |
| PR5536S | Aluminium mounting clip for LED Flex Neon install use, 2cm | 2.00 | 98 |

ALUMINIUM PROFILES FOR LED STRIPS

The aluminum profiles for LED strips have a length of **2 meters**. There are milky, frosted and clear covers. All LED strips from ARENA LUCI are provided with an adhesive tape and can thus be glued directly into the aluminum profiles. **For dimensions please see catalog.**

LED STRIP RECESSED BAR • Heat Sink Capacity: 30W / m

| | | | |
|-----------|---|-------|-----|
| ALSK5030 | Profile for recessed mounting, m. depth: 13.9 mm, comes with milky cover & two end cups | 53.00 | 100 |
| ALSK5030O | Profile for recessed mounting, m. depth: 13.9 mm, comes with frosted cover & two end cups | 53.00 | 100 |
| ALSK5030T | Profile for recessed mounting, m. depth: 13.9 mm, comes with clear cover & two end cups | 53.00 | 100 |
| TC-5030 | End Cup | 3.90 | 100 |
| TF-5030 | End Cup with hole | 3.90 | 100 |

LED STRIP WIDE BAR • Heat Sink Capacity: 30W / m

| | | | |
|-----------|---|-------|-----|
| ALSK4001 | Profile for surface mounting, comes with: milky cover, 2 end cups & 2 mounting brackets | 53.00 | 100 |
| ALSK4001T | Profile for surface mounting, comes with: clear cover, 2 end cups & 2 mounting brackets | 53.00 | 100 |
| PR4002 | End Cup | 3.90 | 100 |
| PR4003 | End Cup with hole | 3.90 | 100 |
| PR4004 | Mounting bracket | 3.90 | 100 |

LED STRIP BAR • Heat Sink Capacity: 30W / m

| | | | |
|-----------|---|-------|-----|
| ALSK4031 | Profile for surface mounting, comes with: milky cover, 2 end cups & 2 mounting brackets | 43.00 | 100 |
| ALSK4031O | Profile for surface mounting, comes with: frosted cover, 2 end cups & 2 mounting brackets | 43.00 | 100 |
| ALSK4031T | Profile for surface mounting, comes with: clear cover, 2 end cups & 2 mounting brackets | 43.00 | 100 |
| TC-5031 | End Cup | 3.90 | 100 |
| TF-5031 | End Cup with hole | 3.90 | 100 |



ARCHITECTURAL LIGHTING CATALOGUE

Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--|---|----------|-------|
| TL-5031 | Mounting bracket | 3.90 | 100 |
| LED STRIP ROUND BAR • Heat Sink Capacity: 40W / m | | | |
| ALSK4036 | Profile for surface mounting, comes with: milky cover, 2 end cups & 2 mounting brackets | 69.00 | 100 |
| ALSK4036T | Profile for surface mounting, comes with: clear cover, 2 end cups & 2 mounting brackets | 69.00 | 100 |
| PR4087 | End Cup with hole | 3.90 | 100 |
| PR4089 | Mounting bracket | 3.90 | 100 |
| LED STRIP TRIANGULAR BAR • Heat Sink Capacity: 35W / m | | | |
| ALSK5035 | Profile for surface mounting, comes with: milky cover, 2 end cups & 2 mounting brackets | 78.00 | 101 |
| ALSK5035O | Profile for surface mounting, comes with: frosted cover, 2 end cups & 2 mounting brackets | 78.00 | 101 |
| ALSK5035T | Profile for surface mounting, comes with: clear cover, 2 end cups & 2 mounting brackets | 78.00 | 101 |
| TC-5035 | End Cup | 3.90 | 101 |
| TF-5035 | End Cup with hole | 3.90 | 101 |
| CL-5035 | Mounting bracket | 3.90 | 101 |
| LED STRIP SLIM BAR • Heat Sink Capacity: 15W / m | | | |
| ALS1521 | Profile for surface mounting, comes with: milky cover | 36.00 | 101 |
| ALS1521O | Profile for surface mounting, comes with: frosted cover | 36.00 | 101 |
| ALS1521T | Profile for surface mounting, comes with: clear cover | 36.00 | 101 |
| PR1582 | End Cup | 3.90 | 101 |
| PR1583 | End Cup with hole | 3.90 | 101 |
| PR1584M | Mounting bracket, metal | 5.90 | 101 |
| LED STRIP SLIM RECESSED BAR • Heat Sink Capacity: 15W / m | | | |
| ALS1520 | Profile for recessed mounting, mounting depth: 5.5 mm, comes with: milky cover | 36.00 | 101 |
| ALS1520O | Profile for recessed mounting, mounting depth: 5.5 mm, comes with: frosted cover | 36.00 | 101 |
| ALS1520T | Profile for recessed mounting, mounting depth: 5.5 mm, comes with: clear cover | 36.00 | 101 |
| PR1597 | End Cup | 3.90 | 101 |
| PR1596 | End Cup with hole | 3.90 | 101 |
| LED STRIP DOUBLE SLIM BAR • Heat Sink Capacity: 30W / m | | | |
| ALS1538O | Profile for surface mounting, comes with: frosted cover | 53.00 | 101 |
| ALS1538T | Profile for surface mounting, comes with: clear cover | 53.00 | 101 |
| PR4806 | End Cup | 5.90 | 101 |
| PR4805 | End Cup with hole | 5.90 | 101 |
| PR4807 | Mounting bracket | 5.90 | 101 |
| LED STRIP RECESSED BAR • Heat Sink Capacity: 30W / m | | | |
| ALS1530 | Profile for recessed mounting, mounting depth: 13.5 mm, comes with: milky cover | 71.00 | 102 |
| ALS1530O | Profile for recessed mounting, mounting depth: 13.5 mm, comes with: frosted cover | 71.00 | 102 |
| ALS1530T | Profile for recessed mounting, mounting depth: 13.5 mm, comes with: clear cover | 71.00 | 102 |
| PR1585 | End Cup | 5.90 | 102 |
| PR1586 | End Cup with hole | 5.90 | 102 |
| LED STRIP STANDARD BAR • Heat Sink Capacity: 30W / m | | | |
| ALS1531 | Profile for surface mounting, comes with: milky cover | 71.00 | 102 |
| ALS1531O | Profile for surface mounting, comes with: frosted cover | 71.00 | 102 |
| ALS1531T | Profile for surface mounting, comes with: clear cover | 71.00 | 102 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---|---|----------|-------|
| PR1582 | End Cup | 5.90 | 102 |
| PR1583 | End Cup with hole | 5.90 | 102 |
| PR1584M | Mounting bracket | 5.90 | 102 |
| LED STRIP TRIANGULAR BAR • Heat Sink Capacity: 35W / m | | | |
| ALS1535 | Profile for surface mounting, comes with: milky cover | 71.00 | 102 |
| ALS1535O | Profile for surface mounting, comes with: frosted cover | 71.00 | 102 |
| ALS1535T | Profile for surface mounting, comes with: clear cover | 71.00 | 102 |
| PR1590 | End Cup | 5.90 | 102 |
| PR1591 | End Cup with hole | 5.90 | 102 |
| PR1592 | Mounting bracket, metal | 7.90 | 102 |
| LED STRIP PRO WIDE BAR • Heat Sink Capacity: 30W / m | | | |
| PRO001 | Anodized profile for surface mounting, without accessories, 2m | 34.00 | 102 |
| PRO002S | Milky cover, 2m | 28.00 | 102 |
| PRO002 | Clear cover, 2m | 26.00 | 102 |
| PRO003 | End Cup | 3.90 | 102 |
| PRO004 | Mounting bracket, metal | 2.00 | 102 |
| LED STRIP CONCEALED RECESSED BAR • Heat Sink Capacity: 45W / m | | | |
| ALS1537 | Profile for recessed mounting, with polished reflector, comes with: milky cover | 165.00 | 103 |
| ALS1537O | Profile for recessed mounting, with polished reflector, comes with: frosted cover | 165.00 | 103 |
| ALS1537T | Profile for recessed mounting, with polished reflector, comes with: clear cover | 165.00 | 103 |
| PR1598 | End Cup (right) | 5.90 | 103 |
| PR1599 | End Cup (left) | 5.90 | 103 |
| LED STRIP QUADRO (35 x 35 mm) BAR • Heat Sink Capacity: 50W / m | | | |
| ALS1642O | Profile for surface mounting, comes with: frosted cover | 125.00 | 103 |
| ALS1642T | Profile for surface mounting, comes with: clear cover | 125.00 | 103 |
| PR1642 | End Cup | 7.80 | 103 |
| LED STRIP RECESSED QUADRO (35 x 35 mm) BAR • Heat Sink Capacity: 50W / m | | | |
| ALS1641O | Profile for recessed mounting, comes with: frosted cover | 116.00 | 103 |
| ALS1641T | Profile for recessed mounting, comes with: clear cover | 116.00 | 103 |
| PR1643 | End Cup | 7.80 | 103 |
| PR1644 | Mounting clip | 7.80 | 103 |

ROUND ENCAPSULATED LED STRIP • IP65 • High CRI (≥ 90)

Extruded aluminum bar **encapsulated in UV-stabilized PC tube**. The cover is available in transparent or opal finishing, caps aluminium, IP65 rating, metal cable gland, anti-condensation valve. Ideal for indoor and outdoor lighting such as backlights, linear lighting, architectural lighting.

1060 mm x 25 mm • milky tube

| | | | |
|--------------|--|--------|-----|
| ALSK6100-WW | 20W, 24Vdc, CRI≥90, 3000K, 240 LEDs/m, UV-stabilized milky PC tube | 237.00 | 104 |
| ALSK6100-NW | 20W, 24Vdc, CRI≥90, 4000K, 240 LEDs/m, UV-stabilized milky PC tube | 237.00 | 104 |
| ALSK6100-RGB | 15W, 24Vdc, CRI≥90, RGB Full Color, 60 LEDs/m, UV-stabilized milky PC tube | 237.00 | 104 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------------|--|----------|-------|
| | 1060 mm x 25 mm • milky tube | | |
| ALSK6100T-WW | 20W, 24Vdc, CRI≥90, 3000K, 240 LEDs/m, UV-stabilized clear PC tube | 237.00 | 104 |
| ALSK6100T-NW | 20W, 24Vdc, CRI≥90, 4000K, 240 LEDs/m, UV-stabilized clear PC tube | 237.00 | 104 |
| ALSK6100T-RGB | 15W, 24Vdc, CRI≥90, RGB Full Color, 60 LEDs/m, UV-stabilized clear PC tube | 237.00 | 104 |
| | 2060 mm x 25 mm • milky tube | | |
| ALSK6200-WW | 20W, 24Vdc, CRI≥90, 3000K, 240 LEDs/m, UV-stabilized milky PC tube | 320.00 | 104 |
| ALSK6200-NW | 20W, 24Vdc, CRI≥90, 4000K, 240 LEDs/m, UV-stabilized milky PC tube | 320.00 | 104 |
| ALSK6200-RGB | 15W, 24Vdc, CRI≥90, RGB Full Color, 60 LEDs/m, UV-stabilized milky PC tube | 320.00 | 104 |
| | 2060 mm x 25 mm • milky tube | | |
| ALSK6200T-WW | 20W, 24Vdc, CRI≥90, 3000K, 240 LEDs/m, UV-stabilized clear PC tube | 320.00 | 104 |
| ALSK6200T-NW | 20W, 24Vdc, CRI≥90, 4000K, 240 LEDs/m, UV-stabilized clear PC tube | 320.00 | 104 |
| ALSK6200T-RGB | 15W, 24Vdc, CRI≥90, RGB Full Color, 60 LEDs/m, UV-stabilized clear PC tube | 320.00 | 104 |

UNDERWATER LED SPOT • IP68

Underwater LED spot, AISI 316L and ultra-transparent tempered glass for use exclusively in underwater applications, adjustable light directions with 30° beam angle.

| | | | |
|------------|---|--------|-----|
| UW3025-W | 24W, 24Vdc, CRI≥80, 30°, INOX316L/silver, 128x188x99 mm, 6000K | 560.00 | 105 |
| UW3025-RGB | 24W, 24Vdc, CRI≥80, 30°, INOX316L/silver, 128x188x99 mm, RGB Full color | 715.00 | 105 |

UNDERWATER RECESSED LED POINT SOURCE • IP68

Recessed underwater LED, 24Vdc, 2W white light version, 6W RGB version, IP68, all-steel AISI 316L body, tempered glass, 30° optics, plastic recessed box included.

| | | | |
|------------|--|--------|-----|
| UW0002-W | 2W, 24Vdc, CRI≥80, 30°, INOX316L/silver, 44.5x82.5 mm (only inlet), 6000K | 239.00 | 105 |
| UW0002-RGB | 6W, 24Vdc, CRI≥80, 30°, INOX316L/silver, 98x95 mm (only inlet), RGB Full color | 373.00 | 105 |

UNDERWATER POOL PAR56 LED SPOT • IP68

LED lamp/fixture for underwater, wide optics 120° available with White light or RGB Full Colour. Protection IP68. **The lamp LL0291 can be placed in a standard PAR56 fixture commonly used for swimming pools and fountains.** Connection with screw terminal and water proof sealing. The lamp can accept only AC power supply.

| | | | |
|------------|--|--------|-----|
| LL0291-W | 30W, 12-15Vac , CRI≥80, 120°, PC/white, Ø 175 x 59 mm, 5500K | 375.00 | 105 |
| LL0291-RGB | 30W, 12-15Vac , CRI≥80, 120°, PC/white, Ø 175 x 59 mm, RGB Full Color | 550.00 | 105 |
| PLI1310 | Recessed box, without lamp (see above) | 450.00 | 105 |
| RESINA015 | Bicomponent insulation for safety contacts (for 2 pcs.) | 65.00 | 105 |
| LC2041 | Controller / Switchboard with remote control | 527.00 | 105 |

LED LAMPS • „Retrofit“ for Halogen lamps

Lamps with transparent glass and LED filament

| | | | |
|-----------|---|-------|-----|
| LL2040-WW | HALO 13 • 13W, 230Vac, CRI≥80, 2700K, 360°, E27, 175 mm x Ø 125 mm | 34.00 | 106 |
| LL2039-WW | HALO 7.5 • 7.5W, 230Vac, CRI≥80, 2700K, 360°, E27, 104 mm x Ø 60 mm | 18.00 | 106 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|--|--|----------|-------|
| LL2043-WW | HALO 4 • 4W, 230Vac, CRI≥80, 2700K, E14, 360°, 96 mm x Ø 35 mm | 9.90 | 106 |
| Lamps with milky glass and high luminous efficiency | | | |
| LL2042-WW | GLOBE 21 • 21W, 230Vac, CRI≥80, 3000K, E27, 270°, 170 mm x Ø 120 mm | 29.50 | 106 |
| LL2042-NW | GLOBE 21 • 21W, 230Vac, CRI≥80, 4000K, E27, 270°, 170 mm x Ø 120 mm | 29.50 | 106 |
| LL2041-WW | BULBO 16 • 16W, 230Vac, CRI≥80, 3000K, E27, 300°, 128 mm x Ø 70 mm | 11.90 | 106 |
| LL2041-NW | BULBO 16 • 16W, 230Vac, CRI≥80, 4000K, E27, 300°, 128 mm x Ø 70 mm | 11.90 | 106 |
| LL2044-WW | BULBO 6 • 6W, 230Vac, CRI≥80, 3000K, E14, 220°, 82 mm x Ø 45 mm | 11.90 | 106 |
| Lamps with reflector and high luminous efficiency | | | |
| LL1209-WW | DICRO 6 • 6W, 12Vac/dc, CRI≥80, 3000K, GU5.3, 35°, 50 mm x Ø 50 mm | 13.70 | 107 |
| LL1209-NW | DICRO 6 • 6W, 12Vac/dc, CRI≥80, 4000K, GU5.3, 35°, 50 mm x Ø 50 mm | 13.70 | 107 |
| LL1207-WW | DIM DICRO 7 • 7.5W, 230Vac, CRI≥80, 3000K, GU10, 35°, 58 mm x Ø 50 mm, dimmbable! | 13.70 | 107 |
| LL1207-NW | DIM DICRO 7 • 7.5W, 230Vac, CRI≥80, 4000K, GU10, 35°, 58 mm x Ø 50 mm, dimmbable! | 13.70 | 107 |
| LL1208-WW | DIM DICRO 7 • 7W, 230Vac, CRI≥80, 3000K, GU10, 120°, 58 mm x Ø 50 mm, dimmbable! | 7.90 | 107 |
| LL1208-NW | DIM DICRO 7 • 7W, 230Vac, CRI≥80, 4000K, GU10, 120°, 58 mm x Ø 50 mm, dimmbable! | 7.90 | 107 |
| Recessed round frame for GU5.3 & GU10 lamps | | | |
| PL1414 | Frame Chrome, directable 35°, 95 x 83 mm, Ø hole: 73 mm, without lamp socket | 27.50 | 107 |
| PL1414B | Frame White, directable 35°, 95 x 83 mm, Ø hole: 73 mm, without lamp socket | 17.80 | 107 |
| PL1414NS | Frame Satin, directable 35°, 95 x 83 mm, Ø hole: 73 mm, without lamp socket | 27.50 | 107 |
| Recessed square frame for GU5.3 & GU10 lamps | | | |
| PL1417B | Frame White, directable 35°, 90 x 85 mm, Ø hole: 75 mm, without lamp socket | 21.50 | 107 |
| PL1417NS | Frame Satin, directable 35°, 90 x 85 mm, Ø hole: 75 mm, without lamp socket | 35.50 | 107 |
| Accessories for recessed round & square frames | | | |
| PLI001 | Lamp Holder for GU10, 2A/250V | 3.90 | 107 |
| 010PL | Lamp Holder for GU5.3 / 12V | 7.90 | 107 |
| LED lamp AR111 / G53 | | | |
| LL0627-WW | AR111 • 15W, 12Vac/dc, CRI≥80, 3000K, G53 (screws), 30°, 60 mm x Ø 111 mm | 53.00 | 108 |
| LL0627-NW | AR111 • 15W, 12Vac/dc, CRI≥80, 4000K, G53 (screws), 30°, 60 mm x Ø 111 mm | 53.00 | 108 |
| LED lamp R7s | | | |
| LL1004-WW | R7s • 10W, 100-230Vac, CRI≥80, 3000K, G53 (screws), 360°, 118 mm x 22 mm | 34.00 | 108 |
| Small LED lamp 24V / E14 | | | |
| LL2010-A | VOTIVE • 0.5W, 12Vac/dc, CRI≥80, amber, E14, 300°, 47 mm x Ø 19 mm | 3.90 | 108 |
| LL2010-B | VOTIVE • 0.5W, 12Vac/dc, CRI≥80, blue, E14, 300°, 47 mm x Ø 19 mm | 3.90 | 108 |
| LL2010-G | VOTIVE • 0.5W, 12Vac/dc, CRI≥80, green, E14, 300°, 47 mm x Ø 19 mm | 5.10 | 108 |
| LL2010-R | VOTIVE • 0.5W, 12Vac/dc, CRI≥80, red, E14, 300°, 47 mm x Ø 19 mm | 5.10 | 108 |
| LL2010-WW | VOTIVE • 0.5W, 12Vac/dc, CRI≥80, 3000K, E14, 300°, 47 mm x Ø 19 mm | 3.90 | 108 |
| LL2010-W | VOTIVE • 0.5W, 12Vac/dc, CRI≥80, 6000K, E14, 300°, 47 mm x Ø 19 mm | 3.90 | 108 |
| Small LED lamp 230V / E14 | | | |
| LL2010-A | VOTIVE • 0.5W, 230Vac, CRI≥80, amber, E14, 300°, 47 mm x Ø 19 mm | 5.10 | 108 |
| LL2010-B | VOTIVE • 0.5W, 230Vac, CRI≥80, blue, E14, 300°, 47 mm x Ø 19 mm | 5.90 | 108 |
| LL2010-G | VOTIVE • 0.5W, 230Vac, CRI≥80, green, E14, 300°, 47 mm x Ø 19 mm | 4.90 | 108 |
| LL2010-R | VOTIVE • 0.5W, 230Vac, CRI≥80, red, E14, 300°, 47 mm x Ø 19 mm | 4.90 | 108 |
| LL2010-WW | VOTIVE • 0.5W, 230Vac, CRI≥80, 3000K, E14, 300°, 47 mm x Ø 19 mm | 5.90 | 108 |



ARCHITECTURAL LIGHTING CATALOGUE

Verkaufspreisliste gültig ab 1. Juli 2019

| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|------------|--|----------|-------|
| LL2010-W | VOTIVE • 0,5W, 230Vac, CRI≥80, 6000K, E14, 300°, 47 mm x Ø 19 mm | 5.90 | 108 |
| | Mini LED lamp 12V / GU4 | | |
| LL0006-W/W | Mini • 1,2W, 12Vac/dc, CRI≥80, 3000K, GU4, 80°, 31 mm x Ø 12 mm | 11.90 | 108 |
| LL0006-W | Mini • 1,2W, 12Vac/dc, CRI≥80, 6000K, GU4, 80°, 31 mm x Ø 12 mm | 11.90 | 108 |
| LL0009-W/W | Mini • 2,8W, 12Vac/dc, CRI≥80, 3000K, GU4, 80°, 45 mm x Ø 18 mm | 25.50 | 108 |
| LL0009-W | Mini • 2,8W, 12Vac/dc, CRI≥80, 6000K, GU4, 80°, 45 mm x Ø 18 mm | 25.50 | 108 |

CONTROLLER & POWER SUPPLIES

Here you will find a huge selection of power supplies and controller to operate all kinds of LED's. For details please refer to the catalog!

| | | | |
|------------|---|--------|-----|
| LC5003 | Built-in LED RGBW Controller, PWM, DMX | 270.00 | 110 |
| LC2808 | Remote Controller (RF) for LC5003 | 70.00 | 110 |
| LC5001 | Built-in LED Dimmer Controller, PWM, DMX | 127.00 | 110 |
| LC2828 | Remote Controller (RF) for LC5001 | 70.00 | 110 |
| LC1052S | Push Dimmer 1 Out | 95.00 | 111 |
| LC2501 | Push Dimmer 4 Out Sync | 160.00 | 111 |
| LC1002MS | Push LED Controller RGB/RGBW | 150.00 | 111 |
| LC1009FA | WIFI System RGB/RGBW: RGB/RGBW interface receiver | 230.00 | 112 |
| LC2818WITR | WIFI System RGB/RGBW: WIFI/RF converter | 180.00 | 112 |
| LC2819 | WIFI System RGB/RGBW: RF remote control | 260.00 | 112 |
| LC2810 | RF Touch RGB Controller (touch & push) | 159.00 | 112 |
| LC1006EA | RF Touch RGB Controller (Receiver/Dimmer) | 159.00 | 112 |
| LC2304 | Dali & Push Dimmer LED 1ch – 4 Out | 255.00 | 113 |
| LC2303B | Dali Dimmer RGB / RGBW | 220.00 | 113 |
| LC6002 | 1-10V Dimmer 4ch. LED | 112.00 | 113 |
| LC2012S | DMX Dimmer Interface Single Color | 89.00 | 114 |
| LC2102 | DMX Dimmer Interface RGB / RGBW | 165.00 | 114 |
| LC2003 | Power Repeater 4ch. | 112.00 | 114 |
| LC2104 | DMX-RDM Professional Interface/Dimmer, 4ch. | 240.00 | 115 |
| CO695S | Splitter DMX Professional (4 x optoisolated DMX512) | 660.00 | 115 |
| LC1029S | Mini Touch Sensor Dim. & on/off | 28.00 | 116 |
| LC2001 | Sensore on/off PIR | 74.90 | 116 |
| LC2005B | IR Sensor on/off | 88.00 | 116 |
| LC1008 | Reflection Sensor on/off, 230V | 67.00 | 116 |
| LC8001 | Sensor on/off, 230V | 71.00 | 116 |
| CO101-D1 | Dali Lux Sensor & Push Dimmer | 530.00 | 117 |
| LC101-DV1 | User Remote Control, for CO101-D1 | 80.00 | 117 |
| LC101-DV2 | Advanced Remote Control, for CO101-D1 | 140.00 | 117 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|---------|--|----------|-------|
| CO616 | LED Player Controller (USB/DMX-PC Interface, Software & IR-Remote) | 670.00 | 117 |
| CO690 | DMX Controller | 415.00 | 117 |

PROFESSIONAL Series

| | | | |
|----------|---|--------|-----|
| LP122479 | IP67 Constant Voltage Driver LED, 75W | 110.00 | 118 |
| LP122511 | IP67 Constant Voltage Driver LED, 150W | 140.00 | 118 |
| LP122322 | Ultra Slim Constant Voltage Driver LED, 25W | 47.00 | 119 |
| LP122750 | Constant Voltage Driver LED, 75W | 86.00 | 119 |
| LP122754 | Constant Voltage Driver LED, 150W | 175.00 | 119 |

DIMMABLE POWER SUPPLIES CONSTANT VOLTAGE

| | | | |
|-----------------|---|--------|-----|
| LC9001-24-75WCV | Pro Dim, 75W / 24Vdc, Dimmer: Push / RF | 217.00 | 120 |
| LP-200-24-UNDIM | Pro Dim, 200W / 24Vdc, Dimmer: AC-Push / Triac / 0 1-10V / Dali | 455.00 | 120 |

SWITCHING POWER SUPPLIES CONSTANT VOLTAGE

| | | | |
|-----------|---|--------|-----|
| LP9006-12 | Input: 100-240Vac, Output: 12Vdc / 6W, on/off, 50x32x18,5 mm | 13.90 | 121 |
| LP9006-24 | Input: 100-240Vac, Output: 24Vdc / 6W, on/off, 50x32x18,5 mm | 13.90 | 121 |
| LP9012-12 | Input: 230Vac, Output: 12Vdc / 12W, on/off, 128x50x13 mm | 22.00 | 121 |
| LP9020-12 | Input: 230Vac, Output: 12Vdc / 20W, on/off, 128x50x13 mm | 27.50 | 121 |
| LP9030-12 | Input: 230Vac, Output: 12Vdc / 30W, on/off, 155x53x16 mm | 41.00 | 121 |
| LP9050-12 | Input: 230Vac, Output: 12Vdc / 50W, on/off, 185x64x22 mm | 59.00 | 121 |
| LP9012-24 | Input: 230Vac, Output: 24Vdc / 12W, on/off, 128x50x13 mm | 22.00 | 121 |
| LP9020-24 | Input: 230Vac, Output: 24Vdc / 20W, on/off, 128x50x13 mm | 27.50 | 121 |
| LP9030-24 | Input: 230Vac, Output: 24Vdc / 30W, on/off, 155x53x16 mm | 41.00 | 121 |
| LP9050-24 | Input: 230Vac, Output: 24Vdc / 50W, on/off, 185x64x22 mm | 59.00 | 121 |
| LP9075-12 | Input: 220-240Vac, Output: 12Vdc / 75W, on/off, 184x61x32 mm | 65.00 | 121 |
| LP9075-24 | Input: 220-240Vac, Output: 24Vdc / 75W, on/off, 184x61x32 mm | 65.00 | 121 |
| LP9100-12 | Input: 100-240Vac, Output: 12Vdc / 100W, on/off, 184x61x32 mm | 65.00 | 121 |
| LP9100-24 | Input: 100-240Vac, Output: 24Vdc / 100W, on/off, 184x61x32 mm | 65.00 | 121 |
| LP2021 | Input: 230Vac, Output: 12Vdc / 30W, on/off, 99x82x30 mm | 41.00 | 121 |
| LP2026 | Input: 230Vac, Output: 12Vdc / 60W, on/off, 99x97x30 mm | 53.00 | 121 |
| LP2025 | Input: 230Vac, Output: 12Vdc / 120W, on/off, 203x98x42 mm | 69.00 | 121 |
| LP2029 | Input: 230Vac, Output: 12Vdc / 150W, on/off, 159x97x30 mm | 71.00 | 121 |
| LP2027 | Input: 230Vac, Output: 12Vdc / 250W, on/off, 200x110x50 mm | 98.00 | 121 |
| LP2024-24 | Input: 230Vac, Output: 24Vdc / 312W, on/off, 288x115x50 mm | 185.00 | 121 |
| LP2022-24 | Input: 230Vac, Output: 24Vdc / 100W, on/off, 201x99x42 mm | 55.00 | 121 |
| LP2028-24 | Input: 230Vac, Output: 24Vdc / 200W, on/off, 201x110x42 mm | 96.00 | 121 |
| LP2015-24 | Input: 230Vac, Output: 24Vdc / 60W, on/off, 99x97x30 mm | 49.00 | 121 |
| LP8300 | Input: 90-264Vac, Output: 12Vdc / 300W, on/off, 127x82x38 mm | 41.00 | 121 |
| LP8300-24 | Input: 90-264Vac, Output: 24Vdc / 300W, on/off, 127x82x38 mm | 41.00 | 121 |



| ARTIKEL | BEZEICHNUNG | VP (CHF) | Seite |
|-----------|---|----------|-------|
| LP2000 | Input: 100-250Vac, Output: 12Vdc / 50W, on/off, 115x50x31 mm | 79.00 | 122 |
| LP2010-24 | Input: 100-250Vac, Output: 12Vdc / 100W, on/off, 136x58x40 mm | 80.00 | 122 |

SWITCHING POWER SUPPLIES CONSTANT VOLTAGE · IP67

| | | | |
|-----------|---|--------|-----|
| LP4021-12 | Input: 90-264Vac, Output: 12Vdc / 20W, on/off, 118x35x26 mm, IP67 | 32.00 | 122 |
| LP4021-24 | Input: 90-264Vac, Output: 24Vdc / 20W, on/off, 118x35x26 mm, IP67 | 32.00 | 122 |
| LP4035-12 | Input: 90-264Vac, Output: 12Vdc / 36W, on/off, 148x40x30 mm, IP67 | 45.00 | 122 |
| LP4035-24 | Input: 90-264Vac, Output: 24Vdc / 36W, on/off, 148x40x30 mm, IP67 | 45.00 | 122 |
| LP4060-12 | Input: 90-264Vac, Output: 12Vdc / 60W, on/off, 163x43x32 mm, IP67 | 51.00 | 122 |
| LP4060-12 | Input: 90-264Vac, Output: 24Vdc / 60W, on/off, 163x43x32 mm, IP67 | 51.00 | 122 |
| LP4101-12 | Input: 90-264Vac, Output: 12Vdc / 102W, on/off, 190x52x37 mm, IP67 | 85.00 | 122 |
| LP4101-24 | Input: 90-264Vac, Output: 24Vdc / 100,8W, on/off, 190x52x37 mm, IP67 | 85.00 | 122 |
| LP4151-12 | Input: 180-305Vac, Output: 12Vdc / 120W, on/off, 191x53x38 mm, IP67 | 115.00 | 122 |
| LP4151-24 | Input: 180-305Vac, Output: 24Vdc / 151,2W, on/off, 191x53x38 mm, IP67 | 115.00 | 122 |

SWITCHING POWER SUPPLIES CONSTANT CURRENT · dimmable

| | | | |
|----------|--|--------|-----|
| LP2044 | Input: 230Vac, Output: 350-1050mA / max. 50W (1-14 LED's), Dali / 0-10V / Push | 120.00 | 123 |
| LP122424 | Input: 230Vac, Output: 350-700mA / max. 32W (1-12 LED's), Dali | 99.90 | 123 |
| LP125421 | Input: 230Vac, Output: 350-700mA / max. 32W (1-12 LED's), 0-10V / Push | 99.90 | 123 |
| LP2043 | Input: 230Vac, Output: 250-600mA / max. 32W (1-15 LED's), 0-10V / Push | 112.00 | 123 |
| LP2056 | Input: 220-240Vac, Output: 100-380mA / max. 20W (15/16 LED's), 0-10V / Push | 98.00 | 123 |

SWITCHING POWER SUPPLIES CONSTANT CURRENT

| | | | |
|----------|---|-------|-----|
| LP30250 | Input: 110-240Vac, Output: 250-380mA / max. 30W (1-15 LED's) | 67.00 | 123 |
| LP5050 | Input: 110-240Vac, Output: 300-1050mA / max. 50W (1-25 LED's) | 57.00 | 124 |
| LP2059 | Input: 230Vac, Output: 350mA / max. 6W (1-4 LED's) | 31.50 | 124 |
| LP122217 | Input: 110-240Vac, Output: 250-1000mA / max. 32W (1-12 LED's) | 57.00 | 124 |
| LP2102 | Input: 230Vac, Output: 350mA / max. 15W (1-11 LED's) | 47.00 | 124 |
| LP2103 | Input: 230Vac, Output: 700mA / max. 12W (1-4 LED's) | 61.00 | 124 |

